

HOW TO "READ" FM TUNER SPECIFICATIONS


Popular Electronics

WORLD'S LARGEST-SELLING ELECTRONICS MAGAZINE JANUARY 1975/75¢

PROJECT BREAKTHROUGH!

World's First Minicomputer Kit to Rival Commercial Models...

"ALTAIR 8800" SAVE OVER \$1000




ALSO IN THIS ISSUE:


- An Under-\$90 Scientific Calculator Project
- CCD's—TV Camera Tube Successor?
- Thyristor-Controlled Photoflashers

TEST REPORTS:

Technics 200 Speaker System
 Pioneer RT-1011 Open-Reel Recorder
 Tram Diamond-40 CB A
 Edmund Scientific
 Hewlett-Packard



18101



**There can
be only
one best.**





3,025 possible tonal compensations with unique twin stepped tone controls (SX-1010, SX-939)

Selector that permits FM recording while listening to records and vice versa. Up to three pairs of speakers may be connected to each model.

INPUTS	SX-1010	SX-939	SX-838
Tape monitor/4-ch. adaptor	3	2	2
Phono	2	2	2
Microphone	2	2	1
Auxiliary	1	1	1
Noise reduction	1	1	1
OUTPUTS			
Speakers	3	3	3
Tape Rec./4-ch. adaptor	3	2	2
Headsets	2	2	1
Noise reduction	1	1	1
4-channel MPX	1	1	1

Master control system capability

Pioneer's engineers have surpassed themselves with a combination of control features never before found in a single receiver. All three units include: pushbutton function selection with illuminated readouts on the ultra wide tuning dial, FM and audio muting, loudness contour, hi/low filters, dual tuning meters and a dial dimmer.

Never before used on a receiver are the twin stepped bass and treble tone controls found on the SX-1010 and SX-939. They offer over 3,000 tonal variations. A tone defeat switch provides flat response instantly throughout the audio spectrum. The SX-838 features

switched turnover bass and treble controls for more precise tonal compensation for room acoustics and other program source characteristics.

In their respective price ranges, these are unquestionably the finest values in stereo receivers the world has ever known. Audition their uniqueness at your Pioneer dealer. SX-1010 — \$699.95; SX-939 — \$599.95, SX-838 — \$499.95. Prices include walnut cabinets.

Also new and more moderately priced.


Pioneer's most complete and finest line of receivers ever, presents equally outstanding values starting at \$239.95. Shown here are the SX-535 — \$299.95, SX-636 — \$349.95, SX-737 — \$399.95. All with walnut cabinets.

U.S. Pioneer Electronics Corp.,
75 Oxford Drive, Moonachie,
New Jersey 07074
West: 13300 S. Estrella, Los Angeles
90248/Midwest: 1500 Greenleaf,
Elk Grove Village, Ill. 60007/Canada:
S.H. Parker Co.

PIONEER
when you want something better



SX-535



SX-636



SX-737



CIRCLE NO. 36 ON READER SERVICE CARD

Earn an extra \$2000 per year

Find out how you can earn an extra \$2000 *or more* per year restoring only a few color and black and white tubes per week. Full color brochure shows you how to make more money and satisfy more customers on almost every call. **Write to-day!**



New



467 CRT
Restorer/Analyzer
\$279*

With the profit restorer!

Profit in the home. After replacing a component you've often noticed a less than perfect picture. It's almost always due to a weak picture tube. The few minutes you spend with the 467 Restorer will give your customer brilliance and sharpness that will make her pleased to pay for the improved picture.

Profit in the shop. "Sixty-five dollars and the picture still doesn't look as good as it used to!" How many times have your customers said that to you? You need not hear it again! Use the 467 Restorer on every major job and your customer will thank you for returning his set working like new.

Most-Powerful Rejuvenation, but most gentle too. There's only one CRT Restorer that restores the picture to like new and analyzes tube condition so accurately that you can safely guarantee restoration for up to five years. You get extra safety from our automatic restoration method that prevents cathode stripping.

TriDynamic true test. The B & K TriDynamic method tests all three guns simultaneously. It measures true beam current that passes through G1 aperture, unlike other testers that measure meaningless cathode to G1 current. Leakage indication even includes cathode-to-cathode and there's an exclusive B & K focus continuity test.

Simplest operation. Exclusive integrated circuitry lets you test all picture tubes with the same, defined-on-the-front-panel procedure . . . including "in-line", Trinitron and tubes with common G1 and G2. See your distributor or write Dynascan.

*Six sockets included;
optional sockets also shown.

B&K PRODUCTS OF
DYNASCAN
1801 W. Belle Plaine Ave.
Chicago, IL 60613 • (312) 327-7270

CIRCLE NO. 7 ON READER SERVICE CARD

POPULAR ELECTRONICS

Popular Electronics®

WORLD'S LARGEST-SELLING ELECTRONICS MAGAZINE

FEATURE ARTICLES

THYRISTOR CIRCUITRY FOR ELECTRONIC PHOTOFLASHERS	Michele Frank	39
<i>An SCR trigger provides faster recycling, more flashes and quick recharge.</i>		
SOLID-STATE IMAGE SENSORS—TV CAMERA TUBE SUCCESSOR?	Harry Garland & Roger Melen	43
KEYING AND VCA CIRCUITS FOR ELECTRONIC MUSIC INSTRUMENTS, PART I	Don Lancaster	60
HOW TO "READ" FM TUNER SPECS	Julian D. Hirsch	68
LIGHTNING DAMAGE INSURANCE JOBS	John T. Frye	72
<i>How lightning damage occurs and how to prevent it.</i>		

CONSTRUCTION ARTICLES

ALTAIR 8800 MINICOMPUTER, PART I	H. Edward Roberts & William Yates	33
<i>The most powerful minicomputer project ever presented—for under \$400.</i>		
AN IGNITION TIMING LIGHT FOR IMPROVING GAS ECONOMY	Anthony Caristi	50
BUILD AN UNDER-\$90 SCIENTIFIC CALCULATOR	Martin Meyer	53
<i>Ten-digit, full-function, pocket-size.</i>		
IC SPEED CONTROLLER FOR HO MODEL RAILROADS	Robert D. Pascoe	58
BUILD THE TRANSISTOR IDENTOMETER	John T. Bailey	69
<i>Identifies leads and polarities and shows up bad devices.</i>		
SIMPLE SQUELCHING CIRCUIT FOR STEREO FM TUNERS	Lawrence N. Dworsky	71

COLUMNS

STEREO SCENE	Ralph Hodges	22
<i>Mikes and miking.</i>		
SOLID STATE	Lou Garner	88
<i>Predictions for 1975.</i>		
CB SCENE	Len Buckwalter	92
<i>CB's Red Baron.</i>		
AMATEUR RADIO	Herbert S. Brier	94
<i>Reception and the atmosphere.</i>		
TEST EQUIPMENT SCENE	Leslie Solomon	98
<i>Rejuvenating elderly equipment.</i>		
HOBBY SCENE	Editorial Staff	102

PRODUCT TEST REPORTS

TECHNICS BY PANASONIC MODEL T-200 SPEAKER SYSTEM	78
PIONEER MODEL RT-1011L STEREO TAPE RECORDER	79
HEWLETT-PACKARD MODEL 5381A FREQUENCY COUNTER	80
TRAM DIAMOND 40 AM CB TRANSCEIVER	81
EDMUND SCIENTIFIC KIRLIAN ELECTROPHOTOGRAPHY KIT	82

DEPARTMENTS

EDITORIAL	Art Salsberg	4
<i>The Home Computer Is Here!</i>		
LETTERS		6
NEW PRODUCTS		12
NEW LITERATURE		16
NEWS HIGHLIGHTS		26
ELECTRONICS LIBRARY		100

POPULAR ELECTRONICS, January 1975, Volume 7, Number 1. Published monthly at One Park Avenue, New York, NY 10016. One year subscription rate for U.S., Possessions and Canada, \$6.98; all other countries, \$8.98. Second class Postage paid at New York, NY and at additional mailing offices. Authorized as second class mail by the Post Office Department, Ottawa, Canada and for payment of postage in cash. Subscription service and Forms 3579; P.O. Box 2774, Boulder, CO 80302.

POPULAR ELECTRONICS Including ELECTRONICS WORLD, Trade Mark Registered. Indexed in the Reader's Guide to Periodical Literature. COPYRIGHT ©1974 BY ZIFF-DAVIS PUBLISHING COMPANY. ALL RIGHTS RESERVED.

Ziff-Davis also publishes Boating, Car and Driver, Cycle, Flying, Modern Bride, Popular Photography, Skiing and Stereo Review.

Forms 3579 and all subscription correspondence should be addressed to POPULAR ELECTRONICS, Circulation Dept., P. O. Box 2774, Boulder, CO 80302. Please allow at least eight weeks for change of address. Include your old address, as well as new—enclosing, if possible, an address label from a recent issue.

Editorial contributions must be accompanied by return postage and will be handled with reasonable care; however publisher assumes no responsibility for return or safety of art work, photographs, models, or manuscripts.



EDGAR W. HOPPER
Publisher

ARTHUR P. SALSBERG
Editorial Director

LESLIE SOLOMON
Technical Editor

JOHN R. RIGGS
Managing Editor

EDWARD I. BUXBAUM
Art Director

ALEXANDER W. BURAWA
Associate Editor

JOHN McVEIGH
Assistant Editor

ANDRE DUZANT
Technical Illustrator

HERBERT S. BRIER
LEN BUCKWALTER
LOU GARNER
GLENN HAUSER
JULIAN D. HIRSCH
RALPH HODGES
WALTER G. JUNG
ART MARGOLIS
Contributing Editors

JOSEPH E. HALLORAN
Advertising Director

JOHN J. CORTON
Advertising Sales

LINDA BLUM
Advertising Service Manager

PEGI McENEANEY
Executive Assistant

STANLEY NEUFELD
Associate Publisher

FURMAN H. HEBB
Group VP, Electronics & Photo

ZIFF-DAVIS PUBLISHING COMPANY
Popular Electronics

Editorial and Executive Offices
One Park Avenue New York, New York 10016
212-725-3500

Hershel B. Sarbin, President

Furman Hebb, Executive Vice President and Treasurer
Phillip T. Heffernan, Senior Vice President, Marketing
Edward D. Muhlfeld, Senior Vice President, Sports Division
Philip Sine, Senior Vice President

Frank Pomerantz, Vice President, Creative Services

Arthur W. Butzow, Vice President, Production

Lawrence Sporn, Vice President, Circulation

George Morrissey, Vice President

Sydney H. Rogers, Vice President

Sidney Holtz, Vice President

Charles B. Seton, Secretary

Edgar W. Hopper, Vice President, Electronics Div.

William Ziff, Chairman

W. Bradford Briggs, Vice Chairman

Midwestern Office

The Pattis Group, 4761 West Touhy Ave.,
Lincolnwood, Illinois 60644, 312 679-1100

GERALD E. WOLFE, GEORGE B. MANNION
DAVID ALLEN

Western Office

9025 Wilshire Boulevard, Beverly Hills, CA 90211
213 273-8050; BRadshaw 2-1161

Western Advertising Manager, BUD DEAN

Japan: James Yagi

Oji Palace Aoyama; 6-25, Minami Aoyama
6 Chome, Minato-Ku, Tokyo 407-1930/6821,
582-2851



Member Audit Bureau
of Circulations

MEMBER
INSTITUTE OF
HIGH FIDELITY

The publisher has no knowledge of any proprietary rights which will be violated by the making or using of any items disclosed in this issue.

THE HOME COMPUTER IS HERE!

For many years, we've been reading and hearing about how computers will one day be a household item. Therefore, we're especially proud to present in this issue the first *commercial type* of minicomputer project ever published that's priced within reach of many households—the *Altair 8800*, with an under-\$400 complete kit cost, including cabinet.

To give you some insight to our editorial goal for this momentous project, we were determined *not* to present a digital computer demonstrator with blinking LED's that would simply be fun to build and watch, but suffer from limited usefulness. High chip costs would have made this a most expensive toy. What we wanted for our readers was a state-of-the-art minicomputer whose capabilities would match those of currently available units at a mere fraction of the cost.

After turning down three computer project proposals that did not meet these requirements, the breakthrough was made possible with the availability of the Intel 8080 n-channel CPU (central processor unit)—the highest-performance, single-chip processor available at this time. As a result, *Altair 8800* offers up to 65,000 words of memory, 256 inputs and outputs simultaneously, buss line expansion, subroutines that are enormously deep, and fast cycle time, among other desirable characteristics. Peripheral equipment such as a "smart" CRT terminal is expected to be available, too, to make up a within-pocket-book-reach sophisticated minicomputer system.

Unlike a calculator—and we're presenting an under-\$90 scientific calculator in this issue, too—computers can make logical *decisions* for an accounting system, navigation computer, time-shared computer, sophisticated intrusion system, and thousands of other applications. The "power" of *Altair 8800* is such that it can handle many programs simultaneously.

What we're presenting to you, the POPULAR ELECTRONICS reader, therefore, is a minicomputer that will grow with your needs, rather than one that will be obsoleted as you move more deeply into computerized applications. With minicomputers exhibiting an annual growth rate of some 50%, according to the E.I.A., and with predictions that six out of ten computers sold by 1975 will be mini's, you can be sure that there will be manifold uses we cannot even think of at this time.

There'll be more coverage on the subject in future issues. Meanwhile, the home computer age is here—finally.

Art Salsberg

Radio Shack deals... from the top of its decks!

The top of our Realistic® line. An Auto-Reverse Dolby deck for 2-hour stereo recordings without flipping the cassette



319⁹⁵

FREE New 1975 Radio Shack Catalog

OVER 2000 PRODUCTS
EXCLUSIVES ON EVERY PAGE
BEAUTIFUL FULL COLOR

Stereo • Quadraphonic • Phonographs
TV Antennas • Radios • Citizens Band
Kits • Recorders • Tape • Tools
Auto Tune-Up • Electronic Parts
Test Instruments • More!



164 pages of the finest in home and hobby electronics. Respected brand names like Realistic, Micronta, Archer, Science Fair — and they're available only at Radio Shack stores and dealers nationwide! See what's really new in electronics by getting this catalog now.

SEND FOR YOURS TODAY!
FILL OUT COUPON BELOW

1975 Mail to Radio Shack, P. O. Box 1052, Ft. Worth, Texas 76101. (Please print.)

467

Name _____ Apt. No. _____

Street _____

City _____


State _____ ZIP _____

The Realistic SCT-7 with Auto-Reverse. What convenience! You can record or play an entire concert, on both sides of the tape, for two uninterrupted hours. Or record or play on just one side with Auto-Stop. Or play an entire cassette over and over without stopping. The SCT-7 does it all—automatically. And what features and sound! Dolby* noise reduction system. Bias switch for CrO₂ or standard tape. Record edit button to insert silence between selections. Headphone jack. Big, illuminated VU meters. And lighted indicators for record, tape travel direction and Dolby. U.L. listed. What a deal! #14-897.

*Dolby is a trademark of Dolby Laboratories, Inc.

... and an 8-track deck that's loaded!

149⁹⁵



The Realistic TR-801 with Digital Timer. It couldn't be easier to use. The unique timer shows the minutes and seconds recorded on each cartridge—you always know exactly how much time remains. And pushbuttons control everything. Auto-Stop and eject at the end of each program or just program-4. Repeat and continuous play. Pause and fast forward. Manual power-eject. It makes you a recording pro. U.L. listed. #14-925.

There's only one place you can find them . . .



Radio Shack®
A TANDY CORPORATION COMPANY

Master Charge or
Bank Americard at
participating stores


OVER 3000 STORES • 50 STATES • 7 COUNTRIES

Retail prices may vary at individual stores and dealers.

The Ultimate in Ignition Systems!

★ **ELIMINATES BREAKER POINTS.**
Perfect Timing and Dwell never change!

★ **Eliminates Tune-ups.**
Never wears out or needs any Maintenance.



★ **The Most Advanced**
"OPTO-ELECTRIC SYSTEM"

● The Allison Breakerless System eliminates the Points and Condenser, replacing them with an Opto-Electronic Trigger, using a Light-Emitting Diode and Phototransistor. Also completely eliminates wiper-arm "friction" wear. The only "TRUE" Electronic Ignition ... that you can install for under \$100. Gives 40-times more Timing Accuracy than ANY system using mechanical Breaker-Points! Unlimited RPM. Smoother running. (No timing fluctuation as with Magnetic units). Unaffected by Temperature, Moisture, or Vibration! All Solid-State Components. Easier Starting under any condition! Increased Horsepower. Sparkplugs last longer. Perfect timing increases engine Efficiency and Gas Mileage up to 30%!

● **Quick and Easy Installation!**

★ **Tested and Proven reliability.**

Only **\$49⁹⁵** ● **SATISFACTION GUARANTEED!**

● Complete. ● **1-YEAR FACTORY WARRANTY.**

(State Make, Year, Engine Size). (Calif. Res. add Tax).

● **CONVERT YOUR "C-D" UNIT TO BREAKERLESS!**
"TRIGGER-UNIT" ONLY \$34.95

★ **Send Postcard for FREE BROCHURE Today.**

ALLISON AUTOMOTIVE CO.

P. O. Box 881-P, TEMPLE CITY, CAL. 91780

CIRCLE NO. 2 ON READER SERVICE CARD

**COMING UP IN
THE FEBRUARY**

Popular Electronics

**Build the First, Low-Cost
All-Solid-State TV Camera**

**A VU Meter with
No Moving Parts**

**How Phase-Locked
Loops Work**

Test Reports:

Marantz 4270 Stereo Receiver
Garrard Zero 100 SB Turntable
Ortofon VMS-20E Phono Cartridge
Lafayette Com-Phone 23 CB

Transceiver
Data Technology Models
20 & 21 DMM's.



Letters

RUMOR IS NO SECRET

I was surprised to discover, in your October issue, that Radio Canada International is engaged in "clandestine" broadcasting to Russia from Sines in Portugal, over a station which (as stated on page 56) is "reported to be secretly owned by the West German government."

There was no need for the author to have recourse to rumors about the Sines transmitter, for what he advances as a conspiratorial secret is published in a more accurate version ... in the current *World Radio Handbook*, page 92, with cross references as to users.

ALAN BROWN
Radio Canada International
Montreal, Can.

AN IC BY ANOTHER NUMBER

The Exar integrated circuit used in my "Private Messages With a Voice Scrambler" project (September 1974) has a new part number. It is now called the XR2208CP. Please advise your readers of this change.

JOSEPH B. WICKLUND, JR.
Northwest Engineering
Bothell, Wash.

SETTING THE RECORD STRAIGHT

Mr. Lancaster's series of articles on electronic music synthesizers has served a useful service to your readers. However, "Selecting an Electronic Music Synthesizer" (October 1974) contains a few inaccuracies:

1. The ElectroComp 101 is manufactured by Electronic Music Laboratories (EML), which has no connection with EMSA;

2. The Synthi 100 is manufactured by EMS (London) Ltd., who also manufacture live-performance EM systems that Mr. Lancaster failed to mention. (The Synthi 100 sells for \$30,000—not \$20,000);

3. Electronic Music Studios of America, Inc., (EMSA) is not a manufacturer but the American distributor for EMS (London) Ltd's products;

4. EMSA and ARP do not have the same zip code; EMSA's is 01002.

JANICE B. ANDRES
Managing Director
EMSA Inc.
Amherst, Mass.

PE ON THE AIR

Just a note of appreciation for the new larger format. You have made a great magazine a lot more enjoyable. Over the years, I have used or adopted a number of ideas presented in *POPULAR ELECTRONICS* here at radio station KORI (FM), a trick that often saved a great deal of time—let alone the money involved when equated against the cost of commercial equivalents.

TOM WIRCH
Chief Engineer
KSLM/KORI (FM)
Salem, Ore.

THE PARTS PROCUREMENT DILEMMA

I would like to build the "Nine-Channel Stereo Equalizer" (May 1974) but I am having difficulty finding a dealer who handles the 5558 op-amp IC's required. Another problem is that no pin numbers are shown for the IC in the schematic.

JOHN E. RICE
Georgetown, Ontario, Canada

You can obtain these IC's from Southwest Technical Products Corp. (see the Parts List in the article for the address). As for pin numbering, the omission was intentional. The 5558 is available in several package configurations, all with different lead identification.

In "Suppressing Transients in Solid-State Equipment" (July 1974), it was stated that the General Electric 6RS20-SP4B4 thyrector should be available at local electronics stores. Well, I've tried six different stores within a 20-mile radius of my home and haven't been able to locate one that handles this device. Can you help me with a mail-order address?

KENNETH L. METCALF
Woodstown, N.J.

The 6RS20-SP4B4 thyrector is available from Newark Electronics, 500 N. Pulaski Rd., Chicago, IL 60624. However, there is \$25 minimum for mail orders. The GE distributor nearest you is at 200 Main Avenue, Clifton, NJ 07014.

THE AMATEUR RADIO SCENE

Congratulations on the return of your "Amateur Radio" column. I was very pleased to see it in the October 1974 issue. I can hardly wait for the next column to appear. My only criticism is that the column is a quarterly; it should be a monthly.

Edward LeBlanc, VE1AMN
Prince Edward Island, Canada

In the October 1974 "Amateur Radio" column there appear to be two discrepancies in callsigns. The San Francisco station's callsign should be K101, not K-101, while I believe the correct callsign for King Hussein is JY1—nor WJ1.

Fred Becker
North Attleboro, Mass.

POPULAR ELECTRONICS

free



IT'S THE ONLY NATIONALLY DISTRIBUTED
 FULL-LINE CATALOG WITH A MAJOR
 SHOWING OF THE NEWEST NAME-BRAND
 ELECTRONICS PRODUCTS
 FOR 1975!

SEND FOR IT
 TODAY!

The "NEW LOOK" 1975 LAFAYETTE RADIO ELECTRONICS CATALOG

If you're interested in electronics you NEED this catalog! Completely re-designed for easier-than-ever ordering, with the newest and best Lafayette and national-brand products for '75. And you get the same quality and service that has made Lafayette a leader for 55 years. Iron-clad guarantees! Lowest Prices! Professional Service! State-of-the-art Equipment! Pick and choose from over 18,000 quality electronics products! Now, more than ever, we're your "Single-trip" shopping center for everything in electronics.

SAVE ON EXCLUSIVE LAFAYETTE PRODUCTS PLUS THE BEST MAJOR BRAND NAMES

- Stereo and 4-Channel Music Systems
- Tape Recording Equipment • Car Stereo and Accessories • CB and Ham Gear • Police/Public Service Receivers • Car Stereo and Accessories • Antennas • Cameras • TV • PA and Test Equipment • Music Instruments and Amplifiers • Books • Electronic Calculators • Security Systems • PLUS PARTS, TUBES, BATTERIES, HARDWARE — ALL YOU NEED FOR QUALITY LIVING THROUGH ELECTRONICS

Lafayette
 Listen to us, you can't go wrong.

STORES COAST TO COAST Check Your Yellow Pages or Shop by Mail

NEW! Bigger Pages
NEW! More Full Color
NEW! Easier-to-Read Type

free
 MAIL TODAY!

Lafayette Radio Electronics
 111 Jericho Tpke., Syosset, L.I., N.Y. 11791

35015

Send me your FREE 1975 Catalog.

Send a 1975 Electronics Catalog to my friend.

Name _____ Apt. _____

Name _____ Apt. _____

Street _____

Street _____

City _____

City _____


State _____ Zip _____

State _____ Zip _____

CIRCLE NO. 21 ON READER SERVICE CARD

The real way to learn digital electronics!

NRI is the only school to train you at home on a real digital computer.



Learn computer design, construction, maintenance and programming techniques on your own digital computer using a professional digital multimeter!

Qualified technicians are urgently needed for careers in the exciting new field of digital and computer electronics . . . and the best way to learn digital logic and operations is now available to you in NRI's Complete Computer Electronics Course.

This exclusive course trains you at home on your own digital computer! This is no beginner's "logic trainer", but a complete programmable digital computer that contains a memory and is fully automatic. You build it yourself and use it to define and flow-chart a program, code your program, store your program and data in the memory bank. Press the start button and the computer solves your


**NOW . . .
YOUR OWN DIGITAL (3½ DIGITS)
MULTIMETER INCLUDED
AT NO EXTRA COST!**

The latest in digital testing equipment . . . along with valuable training experiments in digital techniques.

problem and displays the result instantly.

The NRI digital computer is one of 10 kits you receive in the NRI Complete Computer Electronics Course. You build and use your own 3½ digit digital multimeter . . . while you perform hundreds of experiments, building hundreds of circuits, learning organization, operation, troubleshooting and programming.

Only NRI offers you five TV/Audio Servicing Courses



Color TV repair is another big opportunity field right now and NRI can train you at home to service and repair any color or black & white TV, hi-fi equipment, AM-FM radios, and sound systems.

You can choose from

5 courses, starting with a basic servicing course with 65 lessons . . . up to a Master Color TV course, complete with 25" diagonal solid state color TV in handsome woodgrain cabinet. No other school offers so many choices or so much value.

All courses are available with low down payment and convenient monthly payments to fit your budget. And all courses provide professional tools and equipment along with NRI-designed kits for hands-on training. With the Master Course, for instance, you receive your own 5" wide-band triggered sweep solid state oscilloscope, TV pattern generator, 3½ digit digital multimeter and a NRI 25" diagonal solid state television receiver expressly designed for color TV training.

YOU PAY LESS WITH NRI TRAINING AND YOU GET MORE FOR YOUR MONEY.

NRI employs no salesmen, pays no commissions. We pass the savings on to you in reduced tuitions and extras in the way of professional equipment, testing instruments, etc. You can pay more, but you can't get better training.

NRI's complete communication course includes your own CB Training Transceiver



NRI prepares you for a career in the rapidly expanding field of communications . . . a field destined to double in the next decade! NRI can train you at home for one of the thousands of service and

maintenance jobs opening in AM and FM Transmission and Reception, TV Broadcasting, Microwave Systems, Teletype, Radar, Marine Electronics, Mobile Communications and Aircraft Electronics. You train on your own 23-channel Johnson Transceiver and AC power supply; a digital multimeter, for digital experiments and precise testing; bite-size lessons leading to your FCC license and the communications field of your choice.

NEARLY ONE MILLION STUDENTS IN 60 YEARS HAVE LEARNED AT HOME THE NRI WAY.

Mail the insert card and discover for yourself why NRI is the recognized leader in home study training. No salesman will call. Do it today and get started on that new career.

APPROVED UNDER GI BILL

For the career minded, we are approved for veterans benefits. Check box on card for details.


MAIL THE INSERT CARD FOR YOUR FREE NRI CATALOG

No salesman will call



NRI SCHOOLS
McGraw-Hill Continuing Education Center
3939 Wisconsin Avenue,
Washington, D.C. 20016






New Products

Additional information on new products covered in this section is available from the manufacturers. Either circle the item's code number on the Reader Service Card inside the back cover or write to the manufacturer at the address given.

HUNNICUT DIGITAL LOGIC PROBE

The model LCA-2 Logic Circuit Analyzer, made by Hunnicut Digital Electronics, displays not only the logic state of a test point but also the quality of the logic condition. Four lamps indicate voltage/logic levels: Good "0," Bad "0," Bad "1," and Good "1." The LCA-2 is compatible with DTL and TTL. Voltages up to 200 V ac or dc, claims the manufacturer, can be applied to the



input. The LCA-2 is supplied with a 4-foot coaxial cable, BNC connector, and three input adapters. It can indicate polarity/duty cycle of pulse trains as high as 25 MHz. The probe measures 5½-in. long and ⅝-in. in diameter. \$69.50.

CIRCLE NO. 70 ON READER SERVICE CARD

PORTABLE FREQUENCY COUNTER

The C-65A Frequency Counter by Great American Miniatures is a completely portable unit with a frequency range of 10 Hz to 65 MHz (1 Hz to 65 MHz optional). The counter uses TTL circuitry and a 6-digit LED readout. An internal nickel-cadmium power source delivers 5 volts @ 2.2 Ah. A 2.5-MHz crystal oscillator is used as a time base, and the unit can be used as a secondary frequency standard when calibrated against WWV. Sensitivity is 500 mV, and short-term stability is 1 part in 10⁶/24 hours. Dimensions of the C-65A, costing \$269, are 6" × 3.5" × 2.9". Weight is 27 ounces. Optional accessories include a 300-MHz prescaler, ac power supply, battery charger, coaxial probe, and a carrying case for any or all of the above.

CIRCLE NO. 71 ON READER SERVICE CARD

"ISO-TIP" SOLDERING ACCESSORIES

The Wahl Clipper Corporation has introduced a line of accessories for its "Iso-Tip" cordless soldering iron. The Soldering Iron Kit (Cat. #7600) includes the iron itself (only 8" long and 6 ounces in weight) with a "safety lock" feature to prevent accidental tip heating, a wall mounting bracket, a battery recharging unit, a #7535 general-purpose tip and instruction booklet. Optional accessories include #7545 fine tip, #7546 heavy-duty tip, #7595 protective carrier and the #7585 auto charger plug assembly that fits into a car cigarette lighter for recharging in transit.

CIRCLE NO. 72 ON READER SERVICE CARD


ALTEC "STONEHENGE I" LOUSPEAKER

The Altec Corp. has introduced the Stonehenge I medium-efficiency loudspeaker system designed for use with amplifiers with a minimum 25-watt rms power capacity. The floor-standing Stonehenge I features a columnar bass-reflex enclosure, a 12" high-compliance woofer with a 9-pound magnet structure, a front-mounted dividing network with continuously-variable, high-frequency attenuation control, and a newly-designed direct-radiator tweeter. Stonehenge I is handcrafted of African Afrosian Teak veneers and complemented with a raw cocoa fabric snap-on grille, and is finished on all four sides. The system at \$329, requires 1.4 square feet of floor space, and 16" × 37½" × 14½". Weight is 75 lbs.

CIRCLE NO. 73 ON READER SERVICE CARD

CLARION AM/FM MPX/8-TRACK CAR PLAYER

Clarion's new Model 608 8-track car stereo system incorporates an AM/FM multiplex radio. Among the Model 608's features are integrated circuits, vertical-head tracking to minimize cross-talk, stereo indicator light, stereo/mono switch, 4-watts rms per



channel output, and a removable faceplate for in-dash installation. According to the company, the tape player has a frequency response of 50 to 10,000 Hz, S/N of 45 dB min. and wow and flutter below 0.3%.

CIRCLE NO. 74 ON READER SERVICE CARD

WHITE'S LIGHTWEIGHT METAL DETECTOR

White's Electronics announces its new lightweight, solid-state metal detector, the Coinmaster IV-4B Series II. This refined version of its earlier models boasts added sensitivity, which is governed by a variable control, a greater tuning range (both of which aid searches over highly mineralized

areas), and longer battery life. A meter is included for visual as well as audible indication. Address: White's Electronics, 1012 Pleasant Valley Road, Sweet Home, Oregon 97386.

CIRCLE NO. 75 ON READER SERVICE CARD

PIONEER FRONT-LOADING CASSETTE DECK

Pioneer Electronics' Dolbyized Cassette Deck, Model CT-F7171, features front-panel access for tape loading and all necessary controls. This allows the unit to



be stacked above or below other components. Its transport system is powered by a dc servo motor, for high starting torque and immunity to voltage fluctuations. Other features include separate bias and equalization for ferric oxide and CrO₂ tapes, Dolby noise reduction, ferrite tape head, LED peak-level indicators, memory rewind, switchable level limiter and built-in monitoring amplifier and headphone jack. Frequency response: 40 to 13,000 Hz ± 3 dB (CrO₂ tape); wow and flutter: less than 0.1% (WRMS); S/N: 58 dB (Dolbyized).

CIRCLE NO. 76 ON READER SERVICE CARD

KOSS PHASE 2 STEREO PHONES

The new Koss "Phase 2" stereo headphones allow the listener to control the ambience of the program he is listening to. According to the manufacturer, the listener can either "move himself into the center of the orchestra" or "expand the musical sphere around himself." In either "location" he can accentuate selected portions of the orchestra, as if he moved toward some of the artists. The Koss Phase 2 employs Panoramic Source controls, which are thumbwheels at the lower edge of each earcup, and a two-position Ambience Expander. It can also be used in the conventional stereo mode. The medium-brown earphones are equipped with a 10-ft coiled cord and, price is \$75.

CIRCLE NO. 77 ON READER SERVICE CARD

JOHNSON MINI-SCAN™ POCKET MONITOR

The new Johnson "Mini-Scan" vhf scanning monitor weighs only 9 ounces, (255g), while measuring 5.9"×2.6"×1.4". CMOS scanning circuitry and a newly designed low-drain audio section provide extended battery life. The unit has a four-channel capacity and a built-in ferrite bar antenna. Dual conversion and ceramic filters enhance sensitivity, adjacent-channel rejection, and good overall selectivity. The Mini-Scan is used on the 146-174-MHz band. Other features are a squelch control,


POPULAR ELECTRONICS

built-in speaker, jacks for earphone or external speaker, and optional flexible antenna. The unit uses four AA cells and costs \$119.95.

CIRCLE NO. 78 ON READER SERVICE CARD

HEATH HOME WEATHER STATION

A professional-type weather station, in kit form, is available from the Heath Company. The ID-1290 Weather Station features a solid-state thermometer that displays either indoor or outdoor temperature at the flick of a switch, a solid-state anemometer




with switchable ranges for 0-30 and 0-90 mph, and an electronic wind-direction indicator with individual glowing indicators to give 16-point resolution around the compass. Sensing devices are mounted on a single horizontal mast that may be attached to a TV mast. All connecting wires are contained in one cable. The ID1290, housed in a simulated walnut panel, may be mounted vertically or horizontally and is \$89.95, less cable.

CIRCLE NO. 5 ON READER SERVICE CARD

TURNER "ULTRA-KICKER" CB ANTENNA

The Turner Division of the Conrac Corp., long a leading manufacturer of microphones for two-way radios, has introduced a line of "Signal Kicker" antennas. The "Ultra Kicker" model shows an interesting combination of beam and omnidirectional configurations. It has five elements. A center folded dipole receives power from the transmission line, and is surrounded by four outer vertical dipoles, which are loaded through electronically switched stubs. The antenna can be switched to provide 8 different radiation patterns in 45-degree steps, but it remains fixed and no rotator is needed. Gain is 6.2 dB over a half-wave dipole. VSWR is 1.5:1, and the front-to-side ratio is 20 dB or better. Crossover is 0.6 dB. Two other models, an omnidirectional unit and a rotatable beam, are available at \$79.95 and \$119.95 respectively. Price of the "Ultra Kicker" is \$239.95.

CIRCLE NO. 80 ON READER SERVICE CARD



available. Rise time of the vertical amplifier is 35 nanoseconds, overshoot is 3% or less, and the input impedance is 1 megohm shunted by 35 pF. The 1431 is supplied with a handle/tilt stand, Mylar vector overlay (so the unit can be used as a vectorscope), but less probe. It is \$399.00.

CIRCLE NO. 81 ON READER SERVICE CARD

B & K 3" TRIGGERED SWEEP SCOPE


Dynascan's new B&K oscilloscope, Model 1431, has a bandwidth from dc to 10 MHz, and a sensitivity of 10 mV per division. In addition to the triggered sweep, sync is fully automatic. A three-step vertical attenuator is included, and sweep time is variable from 0.5 μ s to 0.5 s per division, in 19 calibrated regions, and 5X magnification is

FANON TRANSISTORIZED MEGAPHONE

The Fanon Model MV-5S is a combination megaphone and warning signal in high-impact plastic bell and housing. Rated output of the amplifier is 5 W with a 300-yd range. Unit has a built-in weatherproof, dynamic mike, pistol-grip talk/signal switch, adjustable volume, and horn alarm. Power is furnished by six "C" cells. \$69.95.

CIRCLE NO. 82 ON READER SERVICE CARD

**the price for
moving up to a
sweep/function
generator
just came down
to \$149.50**



Exact now offers a laboratory-quality sweep/function generator at a price you'd pay for less-useful sine-square oscillators. And you'll get so much more out of the new Model 195 than traditional audio test equipment, such as sine, square, triangle and swept waveforms . . . even pulses.

This new 2 Hz to 200 kHz instrument is the practical answer to many of your signal source needs, whether you're checking audio equipment, testing bread-boarded circuits or teaching at the high school or college level.

An internal sweep generator lets you sweep, either linearly or logarithmically, the entire audio range of amplifiers or speakers without changing ranges or even touching a knob. The Model 195 has three 1000:1 sweep ranges for frequency sweeping plus high and low level sine outputs with amplitude control. Or you can control the frequency by an external voltage (VCF).



The Model 195 is completely portable, operated by a 9-volt transistor battery, so you can forget 60-Hertz hum problems altogether. An optional rechargeable power supply and charger permits continuous operation from Ni-Cad battery power.

This is a true instrument . . . developed by by one of the world's leading designers and manufacturers of laboratory function generators and frequency synthesizers. Find out what the Model 195 can do on your bench, and move up to a better source of signals.

Price: Model 195 \$149.50

Optional rechargeable power supply, complete with battery and charger \$25.00 f.o.b. Hillsboro, Oregon. Instruments stocked in 36 locations across the United States.

CIRCLE NO. 8 ON READER SERVICE CARD



**We accept BankAmericard
and Master Charge.**

DANA EXACT
electronics, inc.

(A subsidiary of DanaLab, Inc.)
BOX 160, HILLSBORO, OREGON 97123
(503) 648-6661 TWX 910-460-8811



Read what the experts say about Heathkit Digital-Design Color TV

“The picture on the GR-2000 can only be described as superb. The Black (Negative) Matrix CRT, the tuner and i-f strip, and the video amplifier provide a picture equal to that of many studio color monitors.”

(Popular Electronics, April, 1974)

“The picture quality of the GR-2000 is flawless, natural tints, excellent definition, and pictures are steady as a rock. It's better than any this writer has ever seen.”

(Family Handyman, June, 1974)

“The plain truth is, with service and repair costs soaring even for the most insignificant in-home repair, the GR-2000 is the way all color TV sets will have to be made in the near future....”

(Elementary Electronics, May-June, 1974)


25" (diagonal) Heathkit GR-2000

Widely reviewed and acclaimed for its outstanding picture and years-ahead engineering. At the touch of a button, the channel number appears on the screen. The optional clock module displays the time right under the channel readout. The totally solid-state varactor tuner eliminates noisy “clunkers” with contacts that can wear out. Instead, pressing a button silently selects any of the 16 pre-programmed UHF or VHF stations. The unique fixed-filter IF never needs instrument alignment, so pictures retain unmatched clarity and brilliance year after year. And for the ultimate in convenience, add the optional wireless remote control. The GR-2000 can be custom mounted and optional cabinets start at \$119.95*.


Kit GR-2000, less cabinet, 147 lbs., Exp./frt. 669.95*
 Kit GRA-2000-1, Digital clock module, 1 lb., mailable 29.95*




Now—a new generation of Heathkit small-screen color TV with digital readout



GR-500
19" (diagonal)



GR-400
17" (diagonal)



GR-300
15" (diagonal)

Simulated TV pictures

Famous Heathkit quality in your choice of screen sizes — 15, 17 or 19" (diagonal). They all have GR-2000-inspired digital channel readout and optional plug-in clock modules. And in the tradition of the GR-2000, these TV's feature dozens of design innovations. Each uses a precision in-line gun in the picture tube and a slotted shadow mask for a bright picture. The GR-400 and 500's negative-matrix screen provides superior contrast while luminance and video circuits with black level clamps maintain the true brightness of televised scenes.

A factory-sealed static toroid yoke and magnet assembly completely eliminates convergence and purity adjustments — and the picture is superior to sets requiring manual adjustments.

The list of significant advances goes on and on — dual gate FET mixer, FET RF amplifier, 4 tuned circuits (instead of the 3 most sets have), automatic fine tuning and preset picture control, hi-fi output jack, slide out chassis. The GR-300 and 400 come complete with walnut veneer cabinets, cabinets for the GR-500 start at \$39.95.


Kit GR-500, less cabinet, 88 lbs., Exp./frt. 499.95*
 Kit GR-400, with cabinet, 104 lbs., Exp./frt. 489.95*
 Kit GR-300, with cabinet, 90 lbs., Exp./frt. 449.95*
 GRA-2000-1, clock module for GR-300, 400 & 500,
 1 lb., mailable 29.95*

POPULAR ELECTRONICS

6 unique new Heathkit products you can build yourself

Heathkit AM/FM Digital Clock Radio—

The GR-1075 is no ordinary clock radio. Big, bright Beckman planar gas discharge tubes display the time. The readouts adjust their brightness automatically as room lighting changes.



A standby battery power supply keeps the clock on time (without the display) if the electricity is interrupted. When the power is restored, the 24-hour alarm will be on time—and so will you. You can wake to your favorite station or a gentle electronic “beep” with adjustable volume. And the radio section uses the same design philosophy as our famous AR-1214

stereo receiver including fixed ceramic filters in the AM and FM circuits and a factory-assembled and aligned FM front-end with 5 μ V sensitivity. With 4 IC's, 41 transistors and 35 diodes, the GR-1075's design is years ahead of ordinary clock radios.

Kit GR-1075, less batteries, 10 lbs., mailable, 129.95*

Digital Electronic Car Clock/Timer

The GC-1093 is an accurate timepiece for your car, boat or plane. It's an electronic clock and a 20-hour rally timer, both with quartz-crystal accuracy. Bright 1/2"-tall digits dim automatically at night. 12 VDC, mounts on or under the dash.

Kit GC-1093
2 lbs., mailable
62.95*



Desktop Electronic/Sliderule Calculator

At last, a sliderule calculator that's big enough to use. The IC-2100 has finger-sized keys and a bright, 1/2"-tall 8-digit display. Cumulative memory and register exchanges virtually eliminate scratchpad work. Performs arithmetic plus trig and arc trig in degrees or radians, common and natural logs, powers of e, square roots, inverses, pi and exponential functions.


Kit IC-2100
4 lbs., mailable
119.95*



Dual-Trace Oscilloscope

A professional scope at kit-form savings. DC-15 MHz frequency response, post-deflection accelerated CRT, vertical amplifier delay lines, time base up to 100 nsec/cm, guaranteed to trigger up to 30 MHz (typically up to 45 MHz), 1 mV/cm vertical sensitivity, true X-Y capability.


Kit IO-4510
34 lbs., mailable
549.95*




Digital Electronic Clocks with standby power

The GC-1092A is a digital clock with a snooze alarm; the GC-1092D reads the time in 6 digits, the month and date in 4 digits. Both have standby power supplies to keep the clock on time (without the display) even during power interruptions.

GC-1092 A & D,
less batteries, 5 lbs., mailable each 82.95*



GC-1092A Time/Alarm



GC-1092D Time/Date

HEATHKIT ELECTRONIC CENTERS—
Units of Schlumberger Products Corporation
Retail prices slightly higher.

ARIZ.: Phoenix; CALIF.: Anaheim, El Cerrito, Los Angeles, Pomona, Redwood City, San Diego (La Mesa), Woodland Hills; COLO.: Denver; CONN.: Hartford (Avon); FLA.: Miami (Hialeah), Tampa; GA.: Atlanta; ILL.: Chicago, Downers Grove; IND.: Indianapolis; KANSAS: Kansas City (Mission); KY.: Louisville; LA.: New Orleans (Kenner); MD.: Baltimore, Rockville; MASS.: Boston (Wellesley); MICH.: Detroit; MINN.: Minneapolis (Hopkins); MO.: St. Louis (Bridgeton); NEB.: Omaha; N.J.: Fair Lawn; N.Y.: Buffalo (Amherst), New York City, Jericho (L.I.), Rochester, White Plains; OHIO: Cincinnati (Woodlawn), Cleveland, Columbus, Toledo; PA.: Philadelphia, Pittsburgh; R.I.: Providence (Warwick); TEXAS: Dallas, Houston; VA.: Norfolk (Va. Beach); WASH.: Seattle; WIS.: Milwaukee.

Send for your
FREE 1975
Heathkit Catalog—
the world's
largest
selection of
electronic kits!




Heath Company
Dept. 10-1
Benton Harbor, Michigan 49022

Please send my free 1975 Heathkit Catalog.
 Enclosed is \$_____, plus shipping.

Please send model(s) _____
Name _____
Address _____
City _____ State _____ Zip _____

PRICES & SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

CL-551



New Literature

METHODE ELECTRONICS PC BROCHURE

"Printed Circuits," a new brochure from Methode Electronics is a 16-page description of various types of printed circuitry including single-sided etched and coated boards, double-sided etched and plated-through types, additive plated-through-hole circuits, and multi-layer and flexible boards. The brochure is well-illustrated with explanatory diagrams and photographs. Methode's several multi-paneling concepts are described: "crackerboard," "scored-array," "nested-array," and web-matrix panels among them. Address: Methode Electronics, 7447 W. Wilson Ave. Chicago, IL. 60656.

1974 NATIONAL MOS CATALOG

The new edition of National Semiconductors Corp.'s MOS IC catalog is now available. This latest book contains over 500

pages of design and applications information on the broad National line of standard MOS products, including clocks, calculators, and memories. Complete information can be found on National's eight- and nine-digit calculator circuits, digital clocks for desk-top, alarm and automobile applications, shift registers—both static and dynamic, semiconductor memories, including ROM's, PROM's, and RAM's, character generators, code converters, and microprocessor elements. Address: National Semiconductor Corp., Marketing Services Dept., Santa Clara, CA 95051.

LAFAYETTE 1975 CATALOG

The latest edition of the Lafayette Radio Electronics catalog is now available free upon request. It contains over 18,000 items in the consumer electronics field including stereo and 4-channel components and music systems, CB, ham, and PA gear, test equipment, antennas and security devices, musical instruments, cameras and optics, calculators, and many types of parts required in electronic projects. The format of the publication has been changed—page size has been increased 45%; larger type and more color have been used; audio equipment has ratings in full compliance with the latest FTC regulations; and major brand lines have been given expanded coverage. The catalog may be obtained at

Lafayette stores or write to: Lafayette Radio Electronics, Dept. PR, Box 10, Syosset, NY 11791.

AUTHORITATIVE TIME AND FREQUENCY TEXTS

A comprehensive collection of information, theory, and data on time and frequency (T/F) standards has been released by the National Bureau of Standards. Monograph 140, (\$8.65), "Time and Frequency, Theory and Fundamentals," describes the field of T/F research, from basic concepts of the measurement of time to the latest developments in precision timekeeping based on atomic and molecular resonances.

Technical notes supplement the monograph. NBS Technical Note 649 (\$1.00), "The Standards of Time and Frequency in the USA" is also one chapter in the monograph. It describes the activities of the two agencies chiefly involved in the T/F field—the NBS and the Naval Observatory. Technical Notes 616 (Revised) (\$5.70) and 656 (\$.35) deal with "Frequency Standards and Clocks: A Tutorial Introduction" and "Standard Time and Frequency: Its Generation, Control, and Dissemination by the NBS," respectively. A discussion of the broadcasts of radio stations WWV, WWVH, WWVB, and WWVL can be found in the latter Technical Note. The publications are available from the Government Printing Office, Washington, DC 20402.

RCA LINEAR IC WALL CHART

Available from RCA is a quick-reference wall chart giving data on their linear IC's for communications, control, instrumentation, and information systems applications. Included on the chart (Form No. LIC-247A) are op amps, arrays, differential amplifiers, broadband (video) amplifiers, voltage regulators and thyristor control devices, AM/FM communications circuits, comparators, and analog multipliers. It also includes a cross-reference of direct replacement types for the products of 12 other manufacturers. Address: RCA Solid State Division, Box 3200, Somerville, NJ 08876.

1975 RADIO SHACK CATALOG

Radio Shack's 1975 catalog (No. 250) describes the company's complete line of products for home entertainment, hobbyists, and experimenters. The 164-page catalog has 100 full-color pages featuring Radio Shack's own Realistic stereo and four-channel receivers, automatic turntables, tape recorders and players, speakers, headphones, auto stereos and CB equipment. Other products included are Radio Shack electronic calculators, Archer™ antennas, and Archerkit™ and Science Fair™ electronic and hobby kits. Address: Radio Shack, Dept. R-20, 2617 W. Seventh St., Fort Worth, TX. 76107.

"Quick 'n Easy" Channel Scanning with ((P)) Pace Scanning Monitors!


SCAN 10-4 SERIES



New compact design scanner for mobile or base. UHF model covers 450-470 MHz, VHF model covers 144-174 MHz, LF covers 25-50 MHz. Each of the 4 crystal channels is tuneable. Either 110 VAC or 12 VDC. Local/distant function switch, lockout switches for each channel, jack for a remote speaker, power cords, mounting bracket and antenna. All of this in an extremely compact size—4½" x 1¼" x 6".

SCAN 150

Rubber antenna shown is optional.



PACE Engineers introduce the revolutionary "SCANMATE 150." Only 4¾" high, 2" wide and ¾" thick, SCANMATE 150 scans 4 channels in a 10 MHz band spread within the VHF/hi/FM band. The 4 internal AA Nicad batteries can be charged with optional charger. External or rubber antenna jacks provided. Lockout controls are provided for each channel.

((P)) PACE COMMUNICATIONS

Division of PATHCOM INC., 24049 South Frampton Avenue, Harbor City, California 90710
Export: 2200 Shames Drive, Westbury, New York 11590. Available in Canada.

MARK TEN B, THE GAS SAVING, PLUG SAVING, TUNE-UP SAVING, ELECTRONIC IGNITION FROM DELTA. NOW AS LOW AS \$49.95.



Years of testing and use by race car drivers in all categories have proven Delta's Mark Ten B the most advanced ignition system on the market today.

Prove it to yourself. Give your car vroom! With a Mark Ten B Capacitive Discharge Ignition System under the hood of your car great things will happen...like reducing costly tune-ups by as much as 75%. Further, you get better all-weather starts, quicker acceleration and better mileage.

Many operational problems caused by emission control devices, poor manifold or improper fuel mixtures disappear. Delta's Mark Ten B even improves the performance of brand-new factory installed electronic ignitions (Chrysler and Ford). Factory systems merely eliminate points and condenser, but the Delta Mark Ten B combines the advantages of capacitive discharge with solid state

electronics to give real performance and increased energy.

Are you a do-it-yourselfer?

Build your own Mark Ten B... it's available in low-cost

kit form. Or, if you prefer,

get the complete ready-to-install unit. Either way, you can install it yourself in minutes with no rewiring, even over Chrysler and Ford systems.

Mail the coupon today and discover how to enjoy happy motoring with Delta's Mark Ten B. The do-it-yourselfer's dream that really pays off.

 **DELTA PRODUCTS, INC.**
P.O. Box 1147, Dept. PE Grand Junction, Colo. 81501
303-242-9000

Please send me free literature.

Enclosed is \$ _____ Ship ppd. Ship C.O.D. Please send: _____ Mark Ten B assembled @ \$64.95 ppd. _____ Mark Ten B Kit @ \$49.95 ppd. (12 volt negative ground only) _____ Standard Mark Ten assembled, @ \$49.95 ppd. _____ 6 Volt: Neg. Ground Only _____ 12 Volt: Specify _____ Pos. Ground _____ Neg. Ground _____ Standard Mark Ten Deltakit® @ \$34.95 ppd. (12 Volt Positive or Negative Ground Only)

Car Year _____ Make _____

Name _____

Address _____

City/State _____ Zip _____

If you've ever said...

"There must be a better

Send for a free Career Guidance Booklet that could start you on the road to success in a rewarding new career.

It happens to all of us, sooner or later. No matter what kind of job we have.

One day, it suddenly strikes home that we're going to have to work for a living, the rest of our lives. And most of us are horrified at the thought of forever being locked into the jobs we now hold.

"Surely," we tell ourselves, "there

must be a way to earn enough extra dollars each month to balance the family budget. Surely, there must be a way to get the kind of position where you don't have to worry about job security."

"Surely," in other words, "there must be a better way to earn a living!"

If you, too, have been thinking these same thoughts, you'll find one



POPULAR ELECTRONICS

way to earn a living..”

of our free Career Guidance Booklets very helpful at this time. We invite you to send for one.

Your free booklet will describe the opportunities for higher income and greater job security you might expect in one of the career fields listed on the coupon and card. It will also explain why ICS can prepare you for this new career field...right in your own home...in your spare time... *regardless of your education or past experience.*

In addition, you will receive a free “Demonstration Lesson” that lets you see for yourself why preparing for a more rewarding career—the ICS way—may be a lot easier than you think.

Please bear in mind, as you check off your career choice on the coupon or card, that ICS has a long and distinguished record of success. In fact, since 1890, more than 8,500,000 men and women have turned to ICS for career training.

Major corporations use ICS Career Training

ICS has provided training programs for various divisions and branches of companies like Ford; U.S. Steel; Chrysler; Mobil; DuPont; etc.

ICS Career Training is approved for Veterans and Servicemen under the new G.I. Bill, and is accredited by the Accrediting Commission of the National Home Study Council.

Now it's your turn to discover how ICS training can start *you* in a rewarding new profession. Just fill in the coupon or the attached postpaid card and mail it today for your free Career Guidance Booklet and free “Demonstration Lesson.”

Mail attached postage-free card today. If card is missing, use coupon.

ICS International Correspondence Schools
Scranton, Pennsylvania 18515

XA702Q

Please send me a free Career Guidance Booklet, and a free “Demonstration Lesson” for the field I have checked below. I understand that I am under no obligation.

Engineering

- Civil
- Mechanical
- Electrical
- Chemical
- Industrial
- Surveying & Mapping

Automotive

- Automotive Mechanic
- Air Conditioning Specialist
- Transmission Specialist
- Body Rebuilding
- Diesel/Truck Mechanic

Business Management

- Executive Mgt.
- Industrial/Production Mgt.
- Data Processing Mgt.
- Marketing/Advertising Mgt.

T.V. Servicing

- Color T.V. Technician
- Stereo-Hi-Fi Specialist
- CATV-MATV Specialist

Electronics

- Electronics Technician
- FCC Licensing
- Computer Servicing
- Communications/Broadcasting

Electrician

- Check here for special information, if age 16 or under

Accounting

- Business Accountant
- CPA Training
- Income Tax Specialist
- Bookkeeping

Air Conditioning/ Refrigeration/Heating

- Air Conditioning
- Refrigeration
- Heating Specialist

Interior Decorating and Design

- High School
- ICS H.S. Diploma Program
- H.S. Equivalency Program

Drafting

- General
- Mechanical
- Architectural

Motel/Hotel Management

- Motel Management
- Hotel Executive
- Restaurant/Club Mgt.
- Resort Management

Airline/Travel

- Reservations Specialist
- Travel Agent
- Passenger Service
- Cargo Agent

Name _____ Age _____


Address _____ Apt. _____

City _____ State _____ Zip _____

Telephone _____

Approved for Veterans' Training. Eligible Institution under the Guaranteed Student Loan Program. Accredited Member National Home Study Council. Canadian residents use Scranton, Pa. address for service from ICS Canadian, Ltd. In Hawaii: 931 University Ave., Honolulu, Hawaii 96814.

©1974 ICS



Stereo Scene

By Ralph Hodges

MIKES AND MIKING

ALL RIGHT, you want to buy a good microphone so you go for advice to the experts—the recording engineers. And a fat lot of good that does you! Recording engineers today use not one but *many* microphones, all of which they consider “good” for a particular application.

For example, John Woram, a highly experienced studio man and professional consultant on recording matters, frequently rhapsodizes on the various characteristics of mikes in professional sound recording magazines. As John tells it, an engineer might want to use a moving-coil mike with a rather undistinguished high-frequency response to capture a firm, slightly juicy splat from the kick drum (the pedal-operated bass drum in a drum set), while employing a dead-flat condenser pickup to bring out the dry rustle, sting, and snap of the snare drum. In fact, a drum set, which really constitutes only one instrument in a pop ensemble, may have as many as three to six different microphones hovering above, around, or *in* it.

And we can go on. An electric guitar or electric bass consists of the instrument itself as well as the inductive pickups below each string and the amplifier/speaker conglomeration from which the sound emerges. The engineer has the choice of miking acoustically through its speaker (which is, after all, part of the “sound” of the instrument), or running a direct feed from the guitar’s pickups or amplifier to the recording console. On occasion he’s been known to do both, either mixing the two signals on the spot or laying them down in separate tracks on the tape for subsequent mixing. And perhaps he wants to mike the guitar in stereo to give a greater sense of the acoustic field. (Many engineers do not, preferring to make a mono recording of the instrument and then control its position in the stereo “spread” by feeding more or less of it to the left or right channel of the final

record.) Thus the engineer may use a minimum of *three* microphones,—if you count the guitar’s pickups—to get the sound he wants from *one* musician. And today he also has the option of using nonacoustic devices that fasten on the instrument and pick up mechanical vibrations.

All of these implements can be brought to bear selectively, according to the way his *taste* tells him an instrument should sound for a particular recording. Ultimately, recording studios acquire reputations for the special noises they seem to be able to get, or even for the sympathetic touch they give certain instruments.

Recording studios frequently use microphones in an unorthodox fashion. For example, now and again they put a mike *inside* the bass drum. You wouldn’t want to do this with one of the excellent, but generally fragile ribbon microphones of years past, because the first thud hitting the diaphragm would simply blow it away. Few, if any, condenser mikes available could stand the punishment without distorting severely. So you take the overload factor very seriously in professional recording work.

Many of these considerations are of no importance for the amateur recordist. You and I do not and never will have on hand the collection of Neumann’s, RCA’s, AKG’s, Sennheiser’s and now Sony’s that the big studios can inventory. We work with two or three mikes at maximum, hanging them out in space where they’re not likely to get overloaded by any one instrument, and we record the performance as an ensemble effort, not as individual instruments.

For these purposes, I favor the flattest frequency response possible in a microphone. This is not the obvious choice that it first appears to be, and it’s possible that many amateur recordists (and certainly many pros) would disagree. For example, a mike intended for close-up work, especially


for voice, might have a gradually descending low-frequency response, and perhaps a bump in the upper mid-range. These characteristics, compensate for an emphasis of lows that most directional mikes exhibit at close range (“proximity effect”), and also improve articulation. Fine, but I’m usually out in the boondocks worrying about anything but proximity effects.

Now and again, I do feel a need for the mid-range bump (often called “presence boost”) and wish I had it. But under my normal working conditions (frequently my first hearing of the music comes when the tape starts rolling and the performance begins), I have neither the time nor inclination to mess with such esoterica. (I should mention that proximity-effect compensation and even presence boost can be cut in or out by switching on the cases of some microphones.) So I prefer flat frequency response, for the kind of recording I do.

Frequency Response. Frequency-response data for a microphone can be obtained by measuring its simple electronic output with a meter. You don’t have to mike a complex acoustic field as you do with a speaker. But microphone and speaker testing share a common problem: like speakers, microphones are directional, sometimes by accident (diffraction effects of the case on sound trying to reach the diaphragm, for example) and often by design. The two most common microphone directional types in the amateur’s inventory are the *omnidirectional*, meaning a mike that responds equally to sounds impinging from all directions (or tries to, anyway); and the *cardioid*, which describes a microphone that attempts to respond fully to sounds in front of it (wherever its front happens to be) and not at all to sounds approaching from behind it. The polar graphs in Figure 1 illustrate these pickup patterns; imagine the circle of the omni to be a full sphere, and the cardioid’s pattern as a ripe tomato viewed from the side.

Why would you use a directional microphone like a cardioid? Obviously, you’d use it if you didn’t like something coming from behind. This could be audience noise or room/concert-hall reverberation, particularly if it echoes, sounds otherwise nasty, or is just excessive.

There are other directional types, too, such as the *bidirectional*, exhibiting a figure-eight polar re-



Incredible.

Sorry, but when it comes to our new Phase Linear 4000, modesty fails us. How else would you describe a preamplifier that actually:

- *Puts back in* what recording studios take out.
- *Restores dynamics* lost in recording to closely approximate the original.
- *Vanishes into virtual inaudibility* all hum, noise and hiss inherent in most tapes, records, and FM broadcasts.
- Lets your music (at last) reach a *life-like level* where cymbals sound like cymbals, kettle drums like kettle drums.
- Lets you . . . for the first time . . . hear your music from a *silent background*.

Since its introduction follows the Phase Linear 700 and 400 power amps, the 4000 pre-amp *had* to be good. Consider these features:

The Peak Unlimiter

To prevent overload in recording equipment, studios today "peak limit" high-level explosive transients of the source material. Incorporated in the Phase Linear 4000 is a highly-advanced circuit that reads peak limiting, immediately routes the signal through a lead network, and restores dynamics lost in recording to closely approximate the original.

The Downward Expander

Gain riding, a recording technique used to improve low level signal to noise on phonograph discs, unfortunately compresses dynamic range that would otherwise be available. The 4000 senses when gain riding has been used and immediately expands the dynamics reciprocally downward to precisely the intended level.

The AutoCorrelator

The advanced *Autocorrelation Noise Reduction System* in the 4000 makes record/tape hiss and FM broadcast noise virtually vanish . . . without effecting musical content of the source material. Over-all noise reduction is -10 dB from 20 Hz to 20 kHz. Your music comes from a background that is silent.

Plus . . .

. . . the 4000 is an advanced stereo preamp with SQ* and Phase Linear differential logic . . . its *Active Equalizer* gives you a truly flat energy distribution over the full audio spectrum . . . completely passive, independent, *Step-Tone Controls* allow precise tailoring of the music to your listening environment. It is, in a word, incredible. Ask your dealer for an audition.

PHASE LINEAR 4000 SPECIFICATIONS

Total Distortion: Less than .25%. Typically .02%.

Total Noise: High level: 83 dB below 2 volts. Phono: 72 dB below a 10 millivolt reference.

Tone Controls: Bass: Monotonically increasing and decreasing, dual hinge points, ± 8 dB @ 20 Hz. Hinge points switch selectable beginning at 40 Hz or 150 Hz. Treble: Monotonically increasing and decreasing, dual hinge points, ± 8 dB @ 20 kHz. Hinge points switch selectable beginning at 2 kHz and 8 kHz.

Active Equalizer: 6 dB/octave boost below 50 Hz.

Peak Unlimiter: (Nominal peak unlimit rate attack threshold, front panel variable) .5 dB/micro second for + 6 dB peak unlimited operation.

Downward Expander: Downward expansion commences at -35 dB. Ultimate limit is -41 dB. Unlimiter window is 35 dB wide, upper and lower thresholds are simultaneously variable.

Auto Correlator (Noise Reduction Systems): High frequency noise reduction commences at 2 kHz and is 3 dB, reaching 10 dB from 4 kHz to 20 kHz. Weighted overall noise reduction is -10 dB from 20 Hz to 20 kHz.

Size: 19" x 7" x 10" — **Weight:** 18 lbs.

Warranty: Three years, parts and labor.

Phase Linear 4000
THE POWERFUL DIFFERENCE



Fig. 1. Mike pickup patterns: (left) omnidirectional; (right) cardioid.

sponse (or, to continue the three-dimensional analogies, a crudely formed dumbbell with no place to grab onto), and the *supercardioid* and *hypercardioid* varieties, which narrow the cardioid's tomato down into a pepper (sometimes even a chili pepper) shape, usually with some leafy growth at the stem indicating less than total success in eliminating rearward sounds. Some of these are beloved by professionals, either for their pickup patterns or for other special qualities. But they are rarely part of the amateur's equipage.

Back to frequency response. The sound-output pattern of a loudspeaker can also be shown by polar plots. But as any casual audiophile knows, the polar pattern will not be the same at all frequencies. Lows tend to become omnidirectional, while highs may begin to "beam" in a tight super-




Fig. 2. Cardioid pickup patterns at four different frequencies.

cardioid fashion. So it is with microphones, although their directional aberrations are not always the same. Figure 2 shows the polar plots for a cardioid mike at several different frequencies, while Fig. 3 gives its various frequency responses for sounds originating at zero degrees (right in front, or "on axis"), and at several angles off axis. If the polar plot of Fig. 2 showed the pickup patterns for all fre-

quencies, you could draw Fig. 3 directly from it.

What does all this mean? Well, as you may know, the frequency response you hear from a speaker in a room is a combination of its numerous frequency responses at various angles, since reflections from room boundaries ultimately bring to your ears the speaker's output at 60 degrees, 90 degrees, 180 degrees, etc. And the frequency response of a microphone (i.e., what it "hears") is also a composite of its various responses at all angles, since it's picking up the same sort of room reflections.

It follows (or so it seems to me) that the *real* frequency response of a microphone is not the simple on-axis curve, but some kind of summation of the curves in Fig. 3 and many others besides, all adjusted for the reflectivity of the particular recording environment. But since you can't predict the nature of the recording environment, you're ultimately best off, I'd imagine, with a mike whose response changes little with incident angle. The microphone of Figs. 2 and 3 is not too bad in this respect. Others will be better still, and some will be worse. And for some microphones you may be interested in, the relevant data of this kind will prove difficult to get, I'm afraid, even from the manufacturer. But we all do our best.

Microphone Types. There are only three microphone types that interest the serious recordist: moving coil, ribbon, and condenser. The moving coil closely resembles a speaker (and especially a dome-type tweeter) in construction. In operation its cone (or dome) is shuttled to and fro by impinging sound, and the magnet assembly induces an output voltage in the coil that moves with it. The ribbon type employs a low-mass diaphragm of corrugated metal foil that is also the inductor as it moves within a magnetic field. Condenser microphones consist of a light diaphragm in close proximity to a conductive plate. The diaphragm is polarized—either by an external dc voltage source or with a built-in (electret) electrostatic charge—and as it moves relative to the stationary plate in response to air-pressure changes, the varying capacitance modulates the output voltage.

The time was when the high-frequency responses of these three types were a function of their diaphragms' inherent moving masses,

and ranged from dismal to marginal (moving coil), better (ribbon), and best (condenser). Improved materials and construction have made remarkable strides in narrowing the gap, so that on a dollar-for-dollar basis you can get perfectly acceptable—if not identical—results from any. Of course, ribbon mikes are complex in construction and not really available below \$100 apiece. But at around \$150 you might well pick a ribbon over moving coil or a condenser.

Then there is the question of ruggedness and resistance to acoustic overload. To my knowledge I've never had a mike physically overload, but then I don't work close up as a rule. If you plan to, then you should know that moving-coil types are considered best at shrugging off the very high sound-pressure levels that come from brass, drums, electronic instruments, etc.




Fig. 3. Cardioid frequency response on axis and at two angles off-axis.

Some condenser jobs come fairly close, but few condensers can always be trusted in these applications. Ribbons used to have a terrible reputation for going mechanically to pieces at the slightest provocation, and sometimes suffering permanent injury. Many of the breed are still quite delicate, but Beyer claims that its ribbons can tolerate sound-pressure levels in excess of 130 dB—well into the moving-coil class; and the Group 128 condenser mikes are said to be equally rugged.

As for directional properties, moving-coil and condenser mikes can be made to exhibit practically any pickup pattern. The same is theoretically true for ribbons, but I don't know of any omnidirectional ribbon mikes.

Incidentally, lest I have frightened anyone away with my brief reference to prices above, let me say that fine moving-coil and electret-condenser mikes can be had for \$50 and less.

Impedance, Sensitivity, Etc.

These topics frequently form the bulk of microphone how-to-buy articles. I plan to give them very short shrift.

It is imperative, when using longish microphone cables, to set yourself up with low-impedance mikes, which avoids certain noise and high-frequency loss problems. Recognizing this, every modern tape-recorder manufacturer I can think of has designed his microphone inputs for low-impedance mikes ("suitable for microphone impedances from 150 to 600 ohms" is a typical "specification"). Almost any microphone with true audiophile appeal is going to be available within that range. Some can be switched to higher impedance.

Sensitivity (which is voltage out, for such-and-such a sound-pressure level, into such-and-such an impedance) is trickier. I like a high-output mike because, again, I prefer to keep my microphones somewhat away from the instruments, and sound-pressure levels are lower out there. Therefore I'm often happiest with a condenser, which has and needs its own amplifier (often built into the microphone case these days, and powered by an integral penlight dry cell). Thus, a condenser can have just about any output it pleases, and it may not care a lot about load impedance either. (But there is an additional noise specification—the noise contributed by the microphone's amplifier—to consider.) Mikes with excessively low output would get me into signal-to-noise trouble with my recorder's preamps, however. And excessively high outputs might get the close miker into trouble, since the microphone inputs of most audiophile recorders have electronics *before* the record-level controls, and these can overload. But a passive attenuator consisting of a simple resistor network—available from Shure, Electro-Voice, and others, installed in a case for easy microphone line insertion—will take care of that.

Few desirable microphones in realistic (for us) price ranges vary so much in output from the norm that a way couldn't be found to make a decent recording of, say, voice and acoustic guitar. But when you try to discover the *optimum* mike for your machine, you find you need noise and overload data for your microphone inputs, comparable sensitivity specs for different brands of microphone (and they're not really comparable at present), and some very difficult-to-get (or believe) data about live-music levels. (Argh!) Instead, I recommend you consult your tape machine's manufac-

urer. In many cases he'll have had a chance to use the mike that interests you, and has some insights.

Contacting the manufacturer could be particularly helpful if you plan a major purchase. But don't just write and say, "Which microphone should I buy?" Familiarize yourself with what's available, narrow your choices down to a few, and let him suggest a final decision in the light of your expressed (in your letter, concisely) recording intentions.

As I've said, I prefer to mike a little distantly. This is because I get a good dose of hall reverberation mixed into the final result, and since being well back in the hall is the perspective from which I'm used to hearing performances, it sounds truer to me. (By the way, when I say "mike distantly," it means that the microphones are usually at stage edge or a little beyond, and from seven to twelve feet up.)

I get all kinds of arguments about my technique, and I pay them no attention whatever. True, my tapes would be too dim and muddy for AM radio play (although I absolutely insist they sound fine through good speakers); and for most commercial purposes, they would probably be considered

hopeless. Who cares? I'm in business to please myself, not the mass millions. I get the kind of sound I wish I could get on more commercial recordings, and that is the reason I willingly lug tape machine, mikes, headphones, mike stands, cables, and miles of tape through dark Manhattan nights in quest of musical events.

For like-minded souls wishing to learn about microphones, I can recommend Lou Burroughs' *Microphones: Design and Application*, from which I've freely borrowed for this column and its illustrations. It costs an outrageous \$20 (plus tax and postage, I'm sure) from Sagamore Publishing Co., 980 Old Country Road, Plainview, N.Y. 11803, but it is a truly fine and comprehensive text, with revelatory advice on maintenance.

Correction. An error appeared in my November 1974 column on speaker failure. In the discussion of woofer-cone offset, the text referred to dc amplifier voltages that "may appear at the output capacitors." The sentence should have read, "may appear at the outputs of direct-coupled amplifiers using *no* capacitors." ♦

Model AT15S cartridge shown in Model AT1009 tone arm.



THE HOT TIP IS SHIBATA ...and audio-technical!

The only phono stylus tip designed for lower record wear while improving high frequency tracing.

It's the stylus we include on our AT12S, AT14S, AT15S & AT20SL Audio-Technica Dual Magnet*

audio-technical.

cartridges. To give you better sound from any matrix record or present stereo disc, as well as correct, long-lasting performance from discrete 4-channel (CD-4) records.

Audio-Technica Dual Magnet cartridges are brand new and loaded with features. Like a separate, independent magnetic system for each side of the stereo groove. And smooth response to 45,000 Hz and beyond. Plus very low moving mass for superior tracing ability.

Get a tip from leading audio showrooms throughout the country who are now stocking and recommending the Audio-Technica Dual Magnet cartridges. For every modern record you own.

*U.S. Patent Nos. 3,720,796; 3,761,647

AUDIO-TECHNICA U.S., INC., Dept. 15P, 33 Shiawassee Ave., Fairlawn, Ohio 44313
In Canada: Superior Electronics, Inc.

CIRCLE NO. 6 ON READER SERVICE CARD

NEWS HIGHLIGHTS

Philips & MCA Market Video Disc

N. V. Philips, based in the Netherlands, and MCA, Inc., Los Angeles, have reached an agreement for marketing a Philips/MCA video-disc player and compatible discs for consumer use. An official of MCA states that this development will result in the interchangeability of their video discs. The companies will establish a licensing organization to negotiate with others for related patents. It is expected that a liberal licensing policy will enable many companies to participate in the video player technologies of both concerns. The Philips/MCA video-disc player will be manufactured and marketed by Philips, while MCA, whose resources include the Universal Pictures film library, will produce and market video disc programs.

Blank Tape Sales Skyrocketing

Nearly 200 million blank cassette tapes and 30 million blank 8-track cartridges will be purchased this year, according to the Longines Symphonette Company, a major producer of such tapes. The company also states that cassettes, though now considered a hi-fi medium, are being used for speech recording as well as music. Students are recording their lectures, and businessmen are taping their conferences on cassettes. These new demands, according to a Longines sales projection, will push the total cassette purchases in 1976 to top 340 million. This represents an increase in sales at the rate of 50 million more new cassettes per year.

RCA Introduces Hybrid OP Amps

RCA's Solid State division has introduced a family of hybrid op amps that combine the advantages of MOS/FET's, bipolar transistors, and COS/MOS on a monolithic chip. Gate-protected PMOS transistors are used in the input circuits of the CA3130 family, to provide very high input impedance, low input current, and high-speed performance. The common-mode input-voltage range goes to 0.5 volts below the negative-supply terminal. A bipolar driver provides voltage gain. A COS/MOS drain-loaded inverting amplifier comprises the output stage operating in the Class A mode. The output can be swung within millivolts of either supply rail when used with highly resistive loads, and the gain of this stage depends on the load impedance. Open loop gain of the op amp is 110 dB and bandwidth is 15 MHz. The CA3130 series can be used as comparators (COS/MOS interface), wideband amplifiers, voltage regulators and followers, and in timing applications.

Data Transmission on Real-Time TV

A new system of encoding information on broadcast TV signals has been introduced by the Atlantic Research Corp., Alexandria, Va. The Data-Dot™ system modifies the video signals to cause a small dot to appear in a corner of the receiver's screen, which carries one or more channels of information. A peanut-sized optical

sensor is placed over the dot, and decodes the information which can be printed, displayed, or recorded by a variety of terminal devices. The manufacturer says that modules can be used without any modification of the TV receiver. This system has many possible uses. It can provide data to accompany any televised event—performance records of a player involved in a sports competition, historical information on dramatic characters, even stock market and news reports!

"Under New Proprietorship"

GTE Sylvania and Philco-Ford jointly announced an agreement under which the former would acquire the Philco name and distribution rights for home entertainment products manufactured by Philco-Ford's Home Products Division, and sold in the U.S. and Canada. The agreement does not involve Philco-Ford's line of home refrigerators and freezers, its Telesound operations, or its automotive products. In another development, North American Philips Corp. acquired about 85 percent, or 15 million shares, of the outstanding stock in the Magnavox Company.

Trends in the Microwave Industry

The microwave products industry represents 8 percent of the total electronics industry, and generates \$2.2 billion annually in economic activity. This figure is expected to grow to \$2.8 billion by 1983, according to a report assembled by the Business Communications Company, Stamford, Conn. A large (7.5 percent) annual growth is predicted for the microwave oven field.

Private-Use TV Station

A new television station, available for private use, has opened in New York City. It is part of a new service authorized by the FCC, called Multipoint Distribution Service. The new medium, named "Private Television," is to be utilized by business, government, and entertainment users to deliver their programs at lower cost than is possible via other available means. . . . Owned and operated by the Microband Corp. of America, the station has its control center located in the Empire State Building and will provide its full-color private TV transmission facilities to various locations throughout the tri-state area. . . . The station comes under FCC common-carrier regulations, which restrict its activity to program distribution only. Customers select the transmission time, as well as the individual receiving points, and control the program content. Multiple Distribution Service (MDS) uses microwave frequencies (2150 MHz) and a system of address-encoding to assure program privacy. . . . Microband is affiliated with MDS stations in other cities through a national system that plans to use domestic communication satellites to interconnect them in a national private TV network. Stations are presently in Washington, D.C., Chicago, Houston, Baltimore, and Philadelphia. Coverage for Miami is expected soon.

mitScope

Our 25 lb., \$2000.⁰⁰ four channel scope is handheld, digital, weights 10 ozs. and costs \$189.⁵⁰*



SIZE: 5 3/4" x 3 1/4" x 1 1/4"

The mitScope MS-416 is a valuable tool in analyzing circuits. With the increasing use of digital circuitry in home entertainment equipment (stereo receivers, television sets, etc.), the MS-416 will be indispensable for every electronic service department. Digital circuitry is becoming more and more commonplace, and the mitScope is designed to handle this requirement. The MS-416 can be extremely useful in digital circuit design in electronic research and development situations. With its memory capability the mitScope can outperform oscilloscopes many times its price.

A few of the areas where the mitScope is an excellent tool for diagnosing problems are: electronic calculators; digital clocks and timers; digital automotive electronics; and many more.

DISPLAY: LED Matrix: 4x16 LED Matrix. 4 channels: with 16 divisions per channel useful for determining extensive time relationships.

TIME BASE: Range: from .5 u sec. to .2 sec. Triggering: from channel one input signal; positive or negative edge selection using SYNC switch; also an automatic sweep for checking DC steady-state signals.

Range Selection: using three controls—a potentiometer for initial sweep rate and two switches for X1000 and X20 selection.

* **OR, IF YOU REALLY WANT TO SAVE, BUILD YOUR OWN MS-416 FOR JUST \$127.⁵⁰**

MODES: Normal: for most troubleshooting and testing applications. Storage: on all 4 channels stores the information in a 16x4 bit high speed RAM and displays the signal continuously.

PULSE CATCHING: Single-shot storage capability: can catch and store a one-time occurring pulse in the memory and display it for as long as desired.

POWER: Battery: operation using rechargeable NiCads. AC: operation using an AC-(Adapter/Charger) for use with normal 110 v.a.c.

PRICE: MS-416 (fully assembled) \$189.50
MS-416 (kit with easy-to-follow manual) \$127.50

Warranty: One year on parts and labor on assembled units. 90 days on parts for kits.

Prices, specifications and delivery subject to change without notice.

MITS INC.


"Creative Electronics"

Enclosed is a Check for \$ _____
or BankAmericard # _____
or Master Charge # _____
Credit Card Expiration Date _____ Kit
Include \$3.00 for Postage and Handling Assembled
 MS-416
 Please send information on Entire MITS Line.
NAME _____
ADDRESS _____
CITY _____
STATE & ZIP _____
MITS / 6328 Linn, N.E., Albuquerque, New Mexico 87108 505/265-7553 PE-1-75


Sylvania goes



18" Color



12" Black & White



one better.

We train you on two TV's instead of one (You keep both)

With Sylvania's Master TV Career Program, you get not just one but two TV sets. Color and Black & White. Both solid-state. Both designed to give you the solid, practical experience you need. Both yours to build, learn with and keep.

With all Sylvania Career Programs you get our exclusive Autotext method of instruction, a modern, step-by-step approach to learning, which gets you through the basics of electronics quickly and easily.

An optional Cassette System, a technique that adds an extra dimension to learning. It's almost like having an instructor right in your own home. As you play the tapes, he'll guide you through your lessons, explaining as you read, going over schematics and reinforcing everything you learn!

Plus a choice of Programs that can lead to any number of career goals. In TV, communications, automation, digital and solid-state electronics. And in fields you haven't even dreamed of.

Plus specialized advanced training and carefully-engineered Project Kits for that "hands-on" training you

need to make it in the world of electronics.

Throughout your training, Sylvania makes that extra effort to go one better.

Send the card or mail in coupon today for our FREE Catalog. And go with Sylvania.

SYLVANIA Technical Schools

Home Study Division 694-501-0
Sylvania Technical Systems, Inc.
909 Third Avenue
New York, N.Y. 10022

Please send me FREE illustrated career catalog. I understand that I am under no obligation.

Name _____

Address _____

City _____


State _____ Zip _____

Age _____

Veterans: Check here


GTE SYLVANIA Color cabinet optional





IS PROUD TO ANNOUNCE: THE CT-1024 TERMINAL SYSTEM

- * DISPLAYS UP TO 16 LINES (of 32 Characters) AT ONE TIME.
- * 1,024 Character — Two Page Memory Capacity — STANDARD.
- * Plug-In Circuits to adapt the terminal to any requirement at lowest possible cost.
- * Requires +5 Volts DC @ 2.5 Amps, -5 and -12 Volts @ 20 Ma.
- * Use with any TV set



- * Up to date, low power consumption STATIC type MOS Memory.
- * No complicated refresh or power-down circuits needed.

At last we can tell you about the most versatile, video-display terminal kit available anywhere; the Southwest Technical CT-1024. Our terminal is designed around a basic mother board and a 6,144 bit memory that will display two pages of data on any standard television set, or monitor. The two pages consist of 16 lines with 32 characters on each line. Input may be any source of parallel ASCII code; keyboard, computer, etc. If the system is to be used for a display, teaching aid, deaf communicator, or other similar purpose; this is all you will need.

Other applications of a terminal system such as remote time share, RTTY, etc require an interface having a serial output. For these applications you add our # CT-S plug-in UART card to the mother board. This allows you to transmit and receive ACSCII coded data in serial form at a rate of 110 baud. (300 and 600 baud options are available). The standard RS-232 type interface connects directly to your transmitter FSK modulator, modem system, or what have you.

If you are going to use the CT-1024 directly with a computer I/O port that requires a parallel ACSCII input, then you will want our parallel interface card, #CT-P which

allows either the keyboard, or the computer to access the terminals memory and display data on the screen.

For those applications where it is useful, we also have an "off line edit", or "screen read" plug-in circuit #CT-E. This allows you to compose a program, or message on the terminals display screen and transmit it out a line at a time when you are finished and satisfied that everything is correct.

If you would like the convenience of complete cursor control, we have our #CT-CM plug-in board. This gives you Move Right, Move Left, Move Up, Move Down, Home Up, Erase to end of line and Erase to end of frame functions. These are operated by keyswitches, or any other type switches you may wish to use, giving you complete manual control of the cursor.

If the terminal is to be part of a computer system, you might prefer our automatic cursor control circuit #CT-CA. This plug-in not only allows you to control the cursor and to perform the functions listed above, but makes possible computer control of these same functions through the machines software.

# CT-1024 Terminal System Kit with 1024 Memory Card—less cabinet or power supply	\$175.00 PPd
# CT-E Screen Read Plug-in Card Kit	\$ 17.50 PPd
# CT-M Manual Cursor Control Plug-in Card Kit	\$ 11.50 PPd
# CT-P Power Supply for CT-1024—115-230 Volt Primaries.	\$ 15.50 PPd
# KBD-2.Keyboard Kit — 53 Keys	\$ 39.95 PPd

FREE—1975 Catalog—Circle our number on the "Bingo" card.

SOUTHWEST TECHNICAL PRODUCTS CORPORATION


219 W. RHAPSODY

SAN ANTONIO, TEXAS 78216
CIRCLE NO. 34 ON READER SERVICE CARD

EXCLUSIVE!

ALTAIR 8800

The most powerful minicomputer project ever presented—can be built for under \$400



BY H. EDWARD ROBERTS AND WILLIAM YATES

THE era of the computer in every home—a favorite topic among science-fiction writers—has arrived! It's made possible by the POPULAR ELECTRONICS/MITS Altair 8800, a full-blown computer that can hold its own against sophisticated minicomputers now on the market. And it doesn't cost several thousand dollars. In fact, it's in a color TV-receiver's price class—under \$400 for a complete kit.

The Altair 8800 is not a "demonstrator" or souped-up calculator. It is the most powerful computer ever presented as a construction project in any electronics magazine. In many ways, it represents a revolutionary development in electronic design and thinking.

The Altair 8800 is a parallel 8-bit word/16-bit address computer with an instruction cycle time of 2 μ s. Its cen-

tral processing unit is a new LSI chip that is many times more powerful than previous IC processors. It can accommodate 256 inputs and 256 outputs, all directly addressable, and has 78 basic machine instructions (as compared with 40 in the usual minicomputer). This means that you can write an extensive and detailed program. The basic computer has 256 words of memory, but it can be economically expanded for 65,000 words. Thus, with full expansion, up to 65,000 subroutines can all be going at the same time.

The basic computer is a complete system. The program can be entered via switches located on the front panel, providing a LED readout in binary format. The very-low-cost terminal presented in POPULAR ELECTRONICS last month can also be used.

PROCESSOR DESCRIPTION

Processor: 8 bit parallel
 Max. memory: 65,000 words (all directly addressable)
 Instruction cycle time: 2 μ s (min.)
 Inputs and outputs: 256 (all directly addressable)
 Number of basic machine instructions: 78 (181 with variants)
 Add/subtract time: 2 μ s
 Number of subroutine levels: 65,000
 Interrupt structure: 8 hardwire vectored levels plus software levels
 Number of auxiliary registers: 8 plus stack pointer, program counter and accumulator
 Memory type: semiconductor (dynamic or static RAM, ROM, PROM)
 Memory access time: 850 ns static RAM; 420 or 150 ns dynamic Ram




Fig. 1. Basic block diagram of computer parts and operation.

In an upcoming issue, we will describe how to build a low-cost CRT-type terminal that can be used with the computer and can also be mated with any time-sharing computer by telephone.

About the Computer. A computer is basically a piece of variable hardware. By changing the bit pattern stored in the memory, the hardware (electronic circuitry) can be altered from one type of device to another. When the bit pattern, and thus the hardware, is changed, we have what is referred to as "software." Any type of variable instruction (programming)—such as Basic, Fortran, Cobol, Algol—is generally classified as software.

To cause it to vary the hardware, you must communicate with the computer. In the case of the 8800, this is done by setting the bit pattern on the front-panel switches in accordance with a set of instructions (provided with the Intel 8080 LSI chip). For example, the 8800 computer will automatically add when a specific bit pattern (10000010) is received. By setting address and data switches, a complete program of up to 78 steps in the basic computer can be inserted into the processor. If extensive programming is to be performed, an assembler or higher language is used. With an assembler, the person doing the program simply types the word "add" on the device. (In Basic and Fortran, a + is used instead.)

Fundamental programming concepts are simple enough to master in a relatively short time. However, to become an efficient programmer requires a lot of experience and a large amount of creativity.

The block diagram of the basic 8800 computer (or any computer, for that

matter) is shown in Fig. 1. It consists of the following subsystems:

CPU. The heart of the computer is the CPU, or central processor unit. See fig. 2. The CPU performs all the calculations, generates system timing, and makes all decisions. Of particular importance are the decisions the CPU makes concerning what device should have access to the data buss. It makes these decisions by sending status information at the beginning of each computer cycle, telling the memory and the input/output what to expect for the rest of the cycle.

The CPU contains the program timer, sometimes called the P counter. This device keeps track of the current location in the memory that the processor is using. Also located in the CPU is the arithmetic unit.

The CPU used in the 8800 computer, the Intel 8080 LSI chip, is relatively expensive in quantities of one. It was selected, however, because it serves to create a minicomputer whose performance competes with current commercial minicomputers. In practice, a lower-performance processor would have been adequate for the majority of the tasks the user might wish to initially define. But the problem with the lesser-power approach is that relatively little money would be saved, and it would be doomed to near-future obsolescence for practical purposes. Our intent here was to produce a processor with more than enough power to handle any job.

Still another consideration was programming. The larger the instruction set, the easier the computer is to program. The 8080 chip has 78 instructions, which is almost twice that of the next power level CPU available (Intel's 8008), which is really designed for use as a buffer.

The CPU contains eight general-purpose registers, P counter, arithmetic unit, accumulator, stack pointer, instruction decoder, and miscellaneous timing and control circuits. The arithmetic unit is of special interest because it contains the circuitry required to perform arithmetic in both decimal and binary formats.

The stack pointer is the register that keeps track of the subroutine addresses. The 8800 computer is capable of performing an almost unlimited number of subroutines, a feature not available with other microprocessors and absent in many minicomputers.

The instruction decoder is the core of the variable-hardware concept. It

PARTS LIST

- C1, C5 to C13—0.1- μ F disc capacitor
- C2—0.01- μ F disc capacitor
- C3, C4—100-pF disc capacitor
- C14 to C20—0.001- μ F disc capacitor
- IC1—8080 central processing unit IC (Intel)
- IC2 to IC5—74L74 IC
- IC6 to IC14—8T97 IC
- IC15, IC17—7402 IC
- IC16, IC32, IC33—7404 IC
- IC18 to IC20, IC51—74123 IC
- IC21—7473 IC
- IC22 to IC24, IC50—7400 IC
- IC25—7430 IC
- IC26—7410 IC
- IC27 to IC31, IC39 to IC41—7405 IC
- IC34, IC35—8111 IC
- IC36—74L30 IC
- IC42 to IC49—74L00 IC
- IC52—7406 IC
- IC53 to IC58—8111 IC (optional)
- LED1 to LED36—Panel-type, red light-emitting diode
- (Note: Following are resistors 1/2-watt, 10% tolerance)
- R1, R3, R9 to R31, R56—1000 ohm
- R2, R4, R7, R8—330 ohm
- R5, R33 to R37—2200 ohm
- R6—7500 ohm
- R32—100 ohm
- R38, R48 to R55—10,000 ohm
- R39—200,000 ohm
- R40 to R47—470 ohm
- R57 to R92—220 ohm
- S1 to S16, S25—Spst miniature toggle switch
- S17 to S24—Spdt spring-loaded, momentary-action miniature toggle switch
- XTAL—2-MHz crystal
- Misc.—Metal case; power supply (see text); line cord; multiconductor ribbon cable; mounting hardware; solder; etc.
- Note: The following items are available from MITS, Inc., 6328 Linn N.E., Albuquerque, NM 87108 (Tel.: 505-265-7553): partial kit No. 8800PK (includes pc boards and all electronic components (but not case, switches, or power supply), \$298; complete kit No. 8800K (contains all parts, including ready-to-use case, switches, and power supply), \$397; Completely assembled and tested Model 8800A computer (includes 90-day warranty), \$498. Prices do not include postage or delivery charge. Both kits include detailed assembly and operating manual. A FREE set of etching and drilling guides, component-placement diagrams and miscellaneous information is available from the kit supplier (send self-addressed 8 1/2" x 11" envelope with 40c postage). Check supplier or manufacturer for latest ICI price, available separately.




Fig. 2. These are logic functions on the 8080 processor chip (ICI). This n-channel CPU permits 78 basic instructions and has 8-bit parallel processing.





Fig. 3. The logic associated with the CPU (ICI) is shown at left. All of the buffers and latches are on a single pc board. Connecting wiring is through a 100-line buss.

decodes the instructions and sets up the various registers, gates, etc., in the CPU for proper functioning. All system timing comes from the CPU. (The logic associated with the CPU is shown in Fig. 3, while the system clock is shown in Fig. 4.)

Memory. A computer memory stores the various binary 0's and 1's that make up its language. These 0's and 1's are known as *bits*. Some memories are organized to store 4, 16, 24, or 32 bits to a *word*, while others—specifically those in the 8800 computer—are organized to store eight bits to a word. Each time the CPU requests data from the memory, a complete word is transmitted. The term *byte* is interchangeable with the

Printed circuit boards are designed so that the various mating pads are aligned. Multi-conductor ribbon cable interconnects the boards.



term word in an 8-bit processor. (The basic 8800 memory is shown in Fig 5.)

The time required from when the address first appears until the data is stable is called "access time." In most modern semiconductor-memory minicomputers, it ranges from 15 ns to 30 μ s. With proper adjustments, any memory speed can be used in the 8800 computer, although standard memory time is 850 ns for a static random-access memory (RAM) and 420 ns for a dynamic RAM. Higher-speed memories will not appreciably affect the performance of the computer, while slower-speed memories will result in an overall reduction in system speed.

In addition to semiconductor RAM's, the processor will also service ROM's (read-only-memories) and PROM's (programmable read-only memories). Access time should be reinforced for the particular memory used.

Any conventional memory can be used in the computer if the input loading on the buss does not exceed 50 TTL loads and if the buss is driven by standard TTL loads. Normal expansion loads to the buss would be one




Fig. 4. Computer operation is controlled by signals from this 2-MHz clock circuit.

standard low-power load per expansion card.

Front Panel. The front-panel logic permits the following functions:

1. STOP: Stops the processor immediately after it completes the cur-

rent instruction. An automatic stop occurs when power is turned on (interrupts are disabled).

2. RUN: Starts the processor at the current address.

3. EXAMINE: Causes the data stored at the location (set by the switches) to




Fig. 5. The basic memory contains up to eight 256 x 4 RAM's.

be displayed in binary by LED's.

4. **EXAMINE NEXT:** Steps the P counter once and displays the word stored at the next location.

5. **DEPOSIT:** Causes the information preset by the switches to be stored in the memory.

6. **DEPOSIT NEXT:** Stops the P counter and loads the memory.

7. **SINGLE STEP:** Steps the program one instruction.

8. **RESET:** Clears the CPU and sets up a starting address of 0.

9. **CLEAR EXT:** Clears all input/output devices; occurs automatically when power is turned on.

10. **PROTECT/UNPROTECT:** Allows selective protection/unprotection of blocks of memory. When a block of memory is protected, it is impossible to write over that block, but its contents can be read out.

There are 36 LED status indicators on the front panel, 16 of which are used for the address buss, 8 for the system status latches, and 8 for the data buss. The four remaining LED's are used for indicating memory-protect, interrupt, system-wait, and hold status.

Power Supply. Four power sources are required to operate the computer: +5 volts at 2 amperes, -5 volts at 500 mA, -12 volts at 500 mA, and +8 volts at 6 amperes. The first three are regulated, while the last is unregulated. The three regulated lines power the processor. The unregulated line powers the peripheral cards that can be used to expand the system, each of which has its own 5-volt regulator on board. This reduces electrical noise and obviates the possibility of total system failure due to the failure of only one regulator.

Expansion. The basic computer is designed for almost unlimited peripheral and memory expansion, using a buss system where all input/output connections merge into a common line. Hence, an external card can be plugged into any slot and it will function properly. The only qualification is that each card have an address decoder to allow the specific card to take what data it needs from the common buss and put data on the buss as required. The processor buffers are designed to drive 300 external cards, which should be adequate for most applications. Bear in mind that only 17 cards will yield 65,000 words of memory.

[Editor's Note: At this writing, a number of different peripheral devices

are in various stages of design or undergoing tests]

Assembly Details. The basic computer employs four printed circuit board assemblies, each of which contains one functional element of the basic system. Because the boards are large and very complex, we are not publishing etching and drilling guides or component-placement diagrams. Instead, you can obtain a set of guides, diagrams, an instruction set, buss points, and miscellaneous information by sending a stamped self-addressed 8½" × 11" manila envelope with 40c postage to MITS, Inc. (See note below Parts List for address.) Request the PE8800 package.

The front panel display board accommodates the 36 LED indicators and their associated drivers. Address line inputs A0 through A16, data lines D0 through D7, and the various status lines originate on the CPU board. The boards have been designed so that the

various mating pads on both are aligned. Multi-conductor flexible ribbon cable interconnects the boards.

The front panel control board contains the circuitry for the interfacing between the control switches located on the front panel and the CPU. In addition to the interconnections to the actual processor, this board accepts memory address switches A0 through A15 (also on the front panel). The first eight of these switches (D0 to D7) are used to put data into the CPU. The EXAMINE/EXAMINE NEXT, DEPOSIT/DEPOSIT NEXT, SINGLE STEP, and RUN/STOP switches are also wired directly to the front panel control board.

The third board contains the Intel 8080 central processing unit LSI chip, two-phase clock and buffers, and the various lines going to the buss. (The buffers are tri-state, high-input-impedance, high-output-level devices.) This board also has four dual-D flip-flops wired as latches for the eight bits of status information. All input and output wiring to and from the CPU board is via a 100-line buss.

The basic memory board contains 256 eight-bit words of random access memory (RAM). It is directly expandable to 1000 words. This board also contains the input/output data-gating, address-decoding, memory-wait, and memory-protect circuits. The memory-wait circuit allows the memory time to stabilize the output data to the processor, while the memory-protect circuit prevents accidental overwriting of the memory. All connections between the CPU and the memory board are via the 100-line buss.

The four boards, along with the power supply, mount in an 18-in. deep by 17-in. wide by 7-in. high (45.7 × 43.2 × 17.7-cm) metal cabinet. The various operating switches and LED indicators go on the front panel. When all this is done, the computer cabinet's interior will appear to be almost empty. However, the internal cabling system is arranged with connectors to accommodate 17 more boards within the case, all connected to the main buss lines. The added boards can be used for memory, input/output devices, control devices, etc. All you have to do is plug the boards into the connectors and the computer does the rest.

Part 2 of this article, next month, will describe the operation of the computer and present some sample programs. ♦

SOME APPLICATIONS FOR THE ALTAIR 8800 COMPUTER

Listed below is only a small sampling of the thousands of possible applications for the computer. The Altair 8800 is so powerful, in fact, that many of these applications can be performed simultaneously. It can be used as a:

- Programmable scientific calculator
- Multichannel data acquisition system
- Automatic control for ham station
- Sophisticated intrusion alarm system with multiple combination locks
- Automatic IC tester
- Machine controller
- Digital clock with all time-zone conversion
- High-speed I/O device for large computer
- Digital signal generator
- Automated automobile test analyzer
- On-board mobile controller
- Autopilot for planes, boats, etc.
- Navigation computer
- Time-share computer system
- "Smart" computer terminal
- Brain for a robot
- Pattern-recognition device
- Printed matter-to-Braille converter for the blind
- Automatic drafting machine
- Automatic controller for heat, air conditioning, dehumidifying
- Controller for sound systems
- Digital filter
- Signal analyzer


THE ELECTRONIC flash system brought "stop action" photo opportunities to camera enthusiasts. It also eliminated the need for changing spent flashbulbs thanks to the storage properties of the electrolytic capacitor and the use of long-life gaseous lamps. The next major advance in electronic flash technology can be pinpointed to 1965 when Honeywell Photographic introduced an automatic electronic flash, freeing photobuffers from having to set f-stops for each shot that was at a different distance.


Now electronics has created another plateau in automatic flash technology by adding thyristor control—an SCR that both triggers the flash and stops capacitor discharge when the subject receives sufficient light. The result? More flashes per battery charge, faster recycling time for the next shot, and short recharge time.

A Flash of Light. For background, here are the various steps that go into producing the electronic flash of light. First, voltage from a battery, the usual power source in an electronic flash, is converted to ac by means of an oscillator circuit. (This oscillator, by the way, is what causes the characteristic "whine" you hear in the electronic flash unit.) Once the ac is generated, it is stepped up to a higher voltage by a transformer. Then the ac is converted back to dc by a rectifier, after which it is stored in the flash unit's main electrolytic capacitor. (Capacitors in modern flash units are capable of storing potentials of about 350 volts.) The flash capacitor is connected to a gas-filled tube. Xenon is the usual gas used, although some other types are available.

Thyristor Circuitry for ELECTRONIC Photoflashers

*How a
simple SCR trigger
provides faster recycling,
more flashes per charge
and quick recharge
for the latest breed of
automatic electronic
flashers*






Three greatly simplified block diagrams show the major components of the various types of electronic flashers. At (A), a manual unit is the least complex. Diagram (B) shows how a photocell is added with control circuit and quench tube to dump surplus energy. At (C), a thyristor unit adds an SCR to trap voltage from the main flash capacitor.

At this stage, everything is set for triggering the flash. What is now needed is a high-voltage pulse to ionize the gas in the flashtube to make it conductive so that energy can flow through the tube, where it will be converted to light. This high-voltage pulse is created as the camera's shutter contacts close, causing a small trigger capacitor to release its charge into a spark coil connected to the wall of the flashtube. After the charge on the flash capacitor has been exhausted, the gas becomes de-ionized and no longer conductive. The recharging cycle can then begin. Once the cycle is complete, as indicated by the ready lamp on the flash unit, the flash can again be fired.


Automatic Flash. Film exposure is based on two factors: time and intensity. With the pre-1965 photoflashers, the time factor (flash duration) was fixed at about 1/1000 of a second for most units. Hence, intensity had to be controlled by changing the camera's lens opening (f-stop).

The Honeywell 660 automatic flash employed the first "quench circuit" and operated on the variable of time. Now, instead of just one flash duration of perhaps 1/1000 second, the flash unit would give a burst of light with a duration of anywhere between,




Energy used by three electronic flash units shooting the same scene. At (A), the manual unit uses all the voltage stored in flash capacitor to illuminate the scene. Proper exposure is obtained by setting the f-stop on the camera. In unit (B), a quench-tube type, exposure was controlled by the flash unit. Only 45 percent of the energy was used to expose the film. Flash unit (C) used the same amount of time and energy as (B) to illuminate the subject properly but unused energy remained in the flash capacitor, resulting in less battery drain as well as a faster recycling time between shots.

TRACES FROM AN ENERGY-SAVING FLASH UNIT



Oscilloscope traces show results of synthesizing various working distances by regulating a set of baffles in front of a Braun 2000 flash unit, then measuring the resulting flash waveform with a photomultiplier and scope set to 0.2 ms per division. Effective flash duration varies from maximum of 1/1000 s (equivalent to using unit on manual or at its maximum working distance) to minimum of 1/32,000 s (using unit at closest working distance). Peak in the waveform on middle four traces is from firing of the flash tube. This is a characteristic of some, but not all, of latest energy-saving flash units using thyristors.



We used a high-speed oscilloscope to check flash duration of the Braun 2000, set to give briefest flash of 1/32,000 s. Measurement from pulse width at half height.

1/1000 and 1/30,000 second. The exposure control was taken from the camera, and the photographer put in the flash unit. The photographer had only to set an f-stop on his camera, following the recommendations of the manufacturer based on the light intensity from the flash unit and the ASA of the film. The flash unit would then control the duration of the light.

Here's how it works. Light emanating from the flash tube is reflected from the subject back to the flash unit, where it is detected by a photocell. The photocell is connected to a small timing capacitor whose value has been carefully selected based on known criteria (f-stop to be used with a given ASA of film, light intensity, and distance) that add up to an exposure analog. The amount of light falling on the photocell can be biased either by using small apertures or neutral-density filters placed before it. By so doing, the photocell can be fooled into believing that it takes two, three, or four times as long to illuminate the scene. Responding to the amount of light falling on it, the photocell regulates the charging of the timing capacitor. Once the timing capacitor has reached its full charge in a quench-tube circuit, it closes another switch that allows the current flowing from the flash capacitor to be shunted to another tube, with a lower series resistance. Here, the energy is expended in the form of light and heat.

This second tube is never seen by the photographer, and its light never plays a part in the photographic process. It is just a convenient way of dumping the unneeded energy flowing from the flash capacitor. With this approach, flash durations of up to 1/70,000 second have been obtained with small electronic flash units, permitting us to record such things as bullets piercing wood, balloons breaking, etc.

All of this was enough to send most photographers into fits of ecstasy, but it still left one problem. Even though the quench-tube idea brought enormous flexibility to electronic flash units, they were still energy wasters. There was no feasible way to dam up the energy flowing from the flash capacitor to the flash tube. The result was that a photographer could obtain only a limited number of flashes per battery or charge. In the case of the rechargeable nickel-

cadmium battery, this was usually about 40 to 60 flashes.

Enter Thyristor Control. In the fall of 1972, Braun introduced the first series-circuit, thyristor-controlled flash units. The much-sought-after breakthrough came in the form of a small silicon controlled rectifier (SCR) called a "thyristor." Operating as an electronic switch, this little solid-state wonder can handle the load flowing from the flash capacitor and stop it at the precise moment that the exposure control circuit says the subject has received enough light. Instead of having a parallel circuit that simply reroutes the energy from the flash capacitor, we now have a series circuit that allows the leftover energy to remain in the flash capacitor.

The thyristor has many advantages, among them: It can switch on and remain on until the current flowing through a dc circuit drops to zero (or near zero). It can be made to open if it receives a very brief low-energy pulse from the opposite direction. The pulse to shut down, of course, comes from the timing circuit with its small capacitor connected to the photocell.

Used in an electronic flash unit, the thyristor performs two jobs. First, it stops the current flowing from the main flash capacitor, thus regulating the duration of the flash in the same manner the parallel quench circuit did. And it allows the unused energy to remain in the flash capacitor, rather than being wasted. This, in turn, provides another advantage. Recycling times can be shortened because the battery can very quickly

supply the small amount of energy necessary to recharge the capacitor. Battery power can be conserved—meaning more flashes per charge.

One series-type thyristor flash unit known to us recycles in about 2.5 seconds after illuminating a scene 10 ft (3.05 m) away. In doing so, it uses only 22 percent of the energy in the flash capacitor. However, if this same unit is fired at a subject 20 ft (6.1 m) away, it will have used up 90 percent of the stored energy and will require 6 seconds to recharge. At distances of 2.5 ft (0.76 m), the recycling time would be only about 0.25 to 0.33 second. In the manual mode (with the photocell covered), or at distances at the very end of the electronic flash's ability to properly illuminate the scene, the thyristor does not receive the reversing pulse from the timing circuit. Instead, it opens after the voltage in the flash capacitor has dropped to near zero (usually about 1.5 volts).

Battery conservation goes hand in hand with the storage of energy in the flash capacitor. Before the thyristor made its appearance in flash units, it was necessary each time to supply enough power to bring a fully depleted capacitor up to full charge. Now, the thyristor has reduced the requirement so that only fractions of the earlier power are required to recharge a partially discharged capacitor. In some cases, if the flash unit is used exclusively at the closest working distances (where the duration of the flash is briefest), it is not uncommon to obtain 700 to 1000 flashes per nickel-cadmium battery

charge. (On manual, these same batteries would deliver only about 60 flashes per charge. Since no one shoots exclusively at distances of 2.5 ft (0.76 m), the more usual number of flashes per charge is about 100 to 200.

Thyristor-controlled electronic flashes are not likely to glut the market in the near future. This type of flash makes sense only with the more high-powered flash units. The low-powered flash units generally require the entire flash charge on the capacitor to illuminate scenes greater than 10 ft (3.05 m) away; so, there would be no energy savings by building into them a thyristor circuit. Only flash units where a small amount of energy would be used in a shot would make the thyristor circuit practical and necessary.

Another thing barring the universal use of the thyristor in electronic photoflash units is that this type of SCR is expensive and can be tricky to make. Quality control must be very tight, which reduces the number of devices available. This means that thyristor suppliers are having a rough time trying to keep up with the demand. Manufacturers tell us that they are having troubles trying to get enough thyristors just to meet the demand for flash units now in production.

When you do see a thyristor-controlled flash unit, you can bet you will have to pay more for it than you are accustomed to do for "conventional" flash units. The type of sophistication built into these flash units does not come cheap. Perhaps when semiconductor manufacturers can crank out this type of SCR the way other manufacturers crank out resistors, a price reduction can be anticipated—but not before then.

Who Makes Them. If you want to look for one of the new thyristor-controlled flash units, ask for any of the following in your local photo store: Argus Model 1272 or Model 1275; Auto Spiralite Thy 1000; Bell & Howell Model 880; Braun Vario Computer 2000 F022 or F027; Honeywell Auto Strobolar 470; Metz Mecablitz 402 or 217; Rollei Model 36 RE or Model 140 RES; or the Vivitar Auto Thyristor Model 292 or Model 352. Canon, Minolta, and Nikon also market this type of electronic photo flash unit outside the U.S. ♦



A
state-of-the-art
report
on charge-coupled
devices
and scanned
photodiode
arrays.

BY HARRY GARLAND
AND ROGER MELEN

Solid-State Image Sensors— TV Camera Tube Successor?

AN EXPERIMENTAL TV camera has been developed that is no larger than a pack of cigarettes. Equipment is being installed at supermarket checkout counters that can automatically read price tags. There is even a machine that enables blind people to read ordinary printed material. All of these developments are made possible by the use of solid-state image sensors—a special type of integrated circuit.

An image sensor can contain hundreds, even thousands, of individual photosensitive elements on a single chip of silicon. It is normally mounted in a standard IC package that is covered with a transparent top. When a scene strikes the image sensor, usually through a lens as shown in Fig. 1, the individual elements of the sensor can be scanned electronically and their outputs displayed.

Area vs. Image Array. The photosensitive elements of an image sensor can be in either a linear or an area array. In a linear array the elements are in a single line; in an area array, they are in a two-dimensional matrix.




Fig. 1. An image-sensor system.

A linear array can be used to produce a two-dimensional picture, but only one line at a time as the image

moves across the sensor. The number of elements in an array determines the resolution of the picture. The effect of resolution on picture quality is shown in Fig. 2. Here, the same picture is scanned by five different linear arrays. The array with the lowest resolution (32 elements) produced the picture on the left, while the picture on the right was produced by an array with 512




Fig. 2. Photos of displays show how resolution affects picture quality. Number of elements in array increases from right to left.

elements. The improvement in quality from right to left is obvious.

The advantage of an area array over a linear array is that the image doesn't have to be scanned from top to bottom to produce a two-dimensional picture. An example of an imaging system using a lens to image a picture onto a

2500-element area array is shown in Fig. 3. The sensor is electronically scanned and its video output is displayed on a CRT. The array used is a Reticon Model RA50X50 (Fig. 4).

The reading aid shown in Fig. 5 was developed at Stanford University and has a 144-element (6 X 24) image sensor.

A small camera containing the image sensor is used to scan a printed page. The outputs of the sensor control a 144-element tactile display that a blind person can feel by fingertip. This reading aid, known as the Optacon (Optical to Tactile Converter) is being produced by Telesensory Systems Inc.




Fig. 3. Solid-state imaging system using a 50 by 50 sensor array. The image can be seen on CRT in front.




Fig. 4. Close-up of the Reticon RA 50x50 sensor. The background is photo of the array magnified many times.




Fig. 5. Reading aid for blind is used by scanning letters with sensor in right hand and feeling them with left hand on tactile display.




Fig. 6. With normal light on piece of silicon (A), resistance is high. More light lowers resistance (B).

Types of Image Sensors. Integrated circuit image sensors can be built in a number of different ways. The two most common types are the charge-coupled device (CCD) and the MOS scanned photodiode array. Both types make use of the inherent light sensitivity of silicon.

The light sensitivity of silicon can be observed by performing the simple experiment shown in Fig. 6. When a strong light is shining on the silicon device, the resistance of the silicon is seen to decrease. What is being observed is the process of *photogeneration*. When light interacts with silicon, current carriers (both holes and electrons) are generated, reducing the resistance. In fact, each photon that interacts produces one hole and one electron (sometimes called a hole-electron pair).

Silicon is not uniformly sensitive to all wavelengths of light. In fact, silicon image sensors are generally much more sensitive to red light and the




Fig. 7. Spectral response of silicon to various colors of light.




Fig. 8. Charges in CCD array are transferred from left to right to produce a video output.

Fig. 9. Photodiode array is scanned by switching sequentially from one to another





Fig. 10. Self-scanned photodiode array is scanned by transistors on the IC chip.

near infrared than they are to shorter-wavelength blue light. The sensitivity of an image sensor to different colors is summarized in the spectral response curve shown in Fig. 7.

CCD Arrays. Charge-coupled device image sensors enjoy one major advantage over MOS scanned photodiode arrays: they can be built more densely and with larger numbers of elements. The basic photosensitive element in a CCD is an MOS capacitor. An entire array of these capacitors makes up the CCD image sensor. The key feature of the CCD is that charges can be transferred sideways, from one MOS capacitor to another.

The operation of the CCD image sensor is shown diagrammatically in Fig. 8. Each of the capacitors can be

considered as a small "bucket" that holds a charge. When light shines on the sensor, a charge is produced in the bucket through photogeneration. The more light that shines on a particular bucket, the more charge produced. The video information is read out by quickly transferring the charge from one bucket to the other and measuring the charge at the output. All of the charges are emptied from the buckets in this process and the cycle can then be repeated.

The image sensor with the largest array that is commercially available today is a 100 X 100 (10,000-element) CCD array produced by Fairchild Semiconductor. This image sensor produces excellent pictures, but falls short of providing full television resolution. Before that can be achieved

with an IC, a 512 X 320 (163,840-element) image sensor must be developed. This would be a very large sensor indeed, and its development presents a real challenge to the electronics industry. RCA has recently announced an experimental CCD that comes close to providing this resolution, but it is not being produced commercially at this time.

Scanned Photodiode Arrays.

In the MOS photodiode image sensor, the photosensitive element is a silicon diode. When reverse-biased and in the dark, a very small leakage current flows through a photodiode. This is called "dark current." When light shines on the diode, current carriers are generated and more current flows; and the current increases as the light intensity is increased.

The operation of a scanned photodiode array is shown in Fig. 9. The four diodes are sequentially scanned by a rotating switch. Notice that a small capacitor is shown across each diode. The capacitors are not separate components; they represent the inherent capacitances of the diodes. When a diode is selected by the switch, its inherent capacitor charges up through the resistor to the level of the 5-volt supply. As the switch moves on to another diode, the first capacitor discharges through its photodiode. If no light is hitting the diode, the small dark current will only partially discharge the capacitor. With more light on the diode, the capacitor is more fully discharged by the higher current. Now, when that diode is again selected by the switch, an output signal is produced as the capacitor recharges to 5 volts. This video output signal is caused by the voltage drop across the resistor. The more the capacitor is discharged, the greater will be the video signal. Image sensors that operate in this manner are operating in the charge-storage mode.

Scanned photodiode sensors use MOS transistors as switches to scan the diode array. The photodiodes are actually the source-to-substrate diodes of the MOS transistors. As shown in Fig. 10, the MOS transistors are sequentially "closed" by pulses from a shift register which is indexed by a clock input. Image sensors that include shift register circuitry right on the IC are said to be self-scanned. The Reticon image sensor mentioned earlier is an example of a self-scanned MOS photodiode array. ♦

IF YOU ARE READY FOR SERIOUS CAREER

Learn College-Level



ADVANCEMENT NOW—

Electronics at Home

With CREI's unique Electronic Design Laboratory Program

There is only one way to a career in advanced electronics—through advanced training. You can get such training through a resident engineering college or you can take a CREI specialized college level electronics program at home.

Wide Choice of Programs. CREI offers you program arrangements with *fourteen* areas of specialization in advanced electronics. You can select exactly the area of specialization for the career you want.

CREI also offers program arrangements *both* for those with extensive experience in electronics *and* for those with only limited experience. All programs are college-level, except for a brief introductory level course, which is optional.

Unique Laboratory Program. CREI now offers a unique *Electronic Design Laboratory Program* to train you in the actual design of electronic circuits. You also get extensive experience in tests and measurements, breadboarding, prototype building and in other areas important to your career. The Lab Program makes it easier for you to understand the principles of advanced electronics. Only CREI offers this complete college type laboratory program.

The Lab Program includes professional equipment which becomes yours to keep. You will especially appreciate the Electronic Circuit Designer, which is available only through this program and which you will find extremely valuable throughout your professional career.

College Credit. You can actually earn college credit through CREI programs, which you can use at recognized colleges for an engineering degree. CREI maintains specific credit transfer arrangements with selected colleges in the U. S.

Industry Recognized Training. For nearly 50 years CREI programs have been recognized throughout the field of electronics. CREI students and graduates hold responsible positions in every area of electronics and are employed by more than 1,700 leading organizations in industry and government.

Qualifications to Enroll. To qualify for enrollment, you should be employed in electronics or have previous experience or practical training in the use of electronic equipment. You must also be a high school graduate or true equivalent.

All CREI Programs are available under the G.I. Bill

Send for FREE Book. If you are qualified, send for CREI's full color catalog describing these college-level programs and your career opportunities in advanced electronics. Mail card or write for your copy of this book.




CREI CAPITOL
RADIO
ENGINEERING
INSTITUTE

McGraw-Hill Continuing Education Center
3939 Wisconsin Avenue Northwest
Washington, D. C. 20016



Accredited Member, National Home Study Council

AN IGNITION TIMING LIGHT FOR IMPROVING GAS ECONOMY



BY ANTHONY CARISTI

NOWADAYS, everyone knows how important it is to get the best gas economy possible from an automobile. One of the more important factors that affect economy is engine timing. In addition, proper timing is required on all automobile engines so that exhaust emissions do not exceed allowable limits.

Timing changes for a variety of reasons. As the parts of an engine wear, the timing tends to become retarded. If ignition points are replaced, timing is also disturbed. Furthermore, it is virtually impossible to set the point gap exactly the same as it was when the timing was last set.

Using a dwell meter is a far more accurate method of setting point gap than using a feeler gauge, but even this will not guarantee proper ignition timing. The fact is, the best way to check ignition timing is with a timing light.

The timing light described here can be built for only a few dollars. Yet, it is designed to perform as well as a commercial unit costing \$25 or more. Its light output is bright enough to use

under conditions of bright daylight, and it is battery-powered (from the car's battery) to make it independent of the ac line.

About the Circuit. The heart of the timing light's circuit (Fig. 1) is dc-to-dc converter transformer *T1*. It alternately switches current between transistors *Q1* and *Q2*, while stepping up the battery potential to about 125 volts. A ferrite pot core was chosen for this circuit to keep down project size and cost.


The primary winding of *T1* (wound around the pot core) is done by the "bifilar" method that gives tight coupling and accurately locates the center tap. The tight coupling is essential to keeping the voltage spikes across the transistors to an absolute minimum. (In this type of circuit, the spikes can easily exceed ten times the supply voltage if a poorly designed transformer is used causing transistor failure.) By using a bifilar winding for the primary, the voltage spikes across *Q1* and *Q2* are well below the 60-volt rating of the transistors.

The stepped-up voltage from the secondary of *T1* is again stepped up by the voltage-doubler circuit consisting of *D1* and *D2*. It is then passed into flashtube *FT1*.

Construction. Perhaps the most demanding part of the construction process is the winding of *T1*. Even so, the job is not difficult, only time-consuming. The transformer should be wound in the following manner:

Start by winding the feedback loop (its leads are labelled 1 through 3 in Fig. 1) on the bobbin supplied with the ferrite core. Use No. 30 enameled wire. This winding consists of 10 turns of wire, interrupted at the 5th turn for a center-tap connection. Connect and solder 5-in. (12.7-cm) lengths of stranded hookup wire to the ends and center-tap of the winding. Label the leads 1 at the first turn, 2 at the center-tap, and 3 at the final turn. Then wrap the winding with a layer of thin Mylar or plastic tape.

Next comes the bifilar-wound primary winding. This consists of 27 double turns of No. 30 enameled wire.



PARTS LIST

- C1—0.005- μ f, 500-volt disc capacitor
- C2—22- μ f, 25-volt tantalum electrolytic capacitor
- C3, C4—20- μ f, 150-volt electrolytic capacitor
- D1, D2—500-volt, 1/2-ampere silicon rectifier (1N2070, HEP R0053 or equivalent)
- FT1—250-volt, 50-watt-second flash-tube (Radio Shack No. 272-1145 or similar)
- Q1, Q2—60-volt, 1-ampere npn silicon transistor (2N5296 or equivalent)
- R1—68-ohm, 1/4-watt resistor
- R2—560-ohm, 1-watt resistor
- R3—470-ohm, 2-watt resistor
- R4—220,000-ohm, 1/2-watt resistor
- T1—Transformer wound on TDK Type

- H5A P2213 Z52H ferrite core and TDK Type BP 2213-612 bobbin (See text)*
- Misc.—Flashlight body (see text); colored-coded test lead cables; alligator or crocodile clips with insulated boots (2); rubber grommet; printed circuit board; Dow Corning Silastic® cement; machine hardware; stranded hookup wire; No. 30 and No. 36 enameled wire; spring-type spark plug cable connector (available from most automotive supply outlets); stranded hookup wire; solder; etc.
- *The TDK ferrite-core/bobbin assembly is available for \$3 from: Anthony Caristi, 69 White Pond Rd., Waldwick, NJ 07473.

Fig. 1. The dc-to-dc converter (TI) steps up the battery voltage.

Label one end of a 4-ft (1.22-m) strand of the enameled wire with a 4. Label one end of a similar strand 5. Starting with these two ends together, wind 27 turns of both wires on the bobbin. Using an ohmmeter, determine the unmarked end of the wire that started with 4 and connect it to the end

marked 5. This is the center tap. The other unmarked end is terminal 6. Cover the winding with tape to hold it in place and insulate it from the secondary.

The secondary winding consists of 240 turns of No. 36 enameled wire. This is the most tedious part of as-

sembly. Be sure to accurately count the number of turns as you go. How many turns you wind will determine the dc potential applied to the flash-tube. When you are finished winding, attach 5-in. lengths of stranded hookup wire to the winding ends and label them 7 and 8. Then wrap the turns with tape.

Now you can begin assembling the circuit proper. A printed circuit board is recommended for component mounting (see Fig. 2 for actual-size etching and drilling guide and components placement diagram).

Transformer T1 is mounted on the board with the aid of a 6-32 \times 1-in. machine screw, fiber washer, (at the top of the transformer), and a 6-32 nut. Do not overtighten the hardware or you will crack the core, rendering it useless. (Note: Capacitor C4 mounts on the board atop C3 as shown in Fig. 3)

When the circuit board assembly is completely wired, temporarily connect to the appropriate points on it red and black hookup wires for the positive and negative battery leads. Connect the leads, properly polarized, to a 12-volt battery or other dc source. If the board and transformer are properly assembled, you should hear a high-pitched tone when power is applied. This is the vibration of the transformer core as the circuit oscillates. A VOM connected across R4 should provide a 250-volt reading if the input potential to the circuit is set to 14.5 volts. If the circuit does not oscillate, the phasing of the feedback winding of T1 may be incorrect, in which case, you can transpose leads 1 and 3 and try again. Remove the temporary leads.

The type of flashlight body best suited for your timing light is shown in the lead photo. You will have to drill two mounting holes for the circuit board assembly. A third hole that permits color-coded battery and plug leads to exit the flashlight body should be lined with a rubber grommet. Pass the leads through this hole and connect and solder them to the appropriate points on the board. Terminate the positive and negative battery leads with insulation-booted alligator or crocodile clips and the plug lead with a spring-type plug-to-cable adapter.

Turn over the circuit board and carefully solder a 4-40 machine nut to the copper pads surrounding the mounting holes. Make certain that the nuts are centered over the holes and that no solder flows into the threads.





Fig. 2. Foil pattern is above, component placement, left.

The flashtube mounts in the flashlight's reflector. You can enlarge the standard lamp hole in the reflector with a rat-tail file, working carefully to avoid damaging the reflector or scratching its reflective coating. The flashtube's fit should be reasonably close without binding. Place the reflector assembly face down on a flat surface and insert the flashtube in the enlarged hole, positioning it with its point against the glass lens and vertical to the plane of the lens. Run a bead of epoxy or Dow Corning Silastic® cement between flashtube and reflector and allow the cement to set overnight. Be sure to maintain the flashtube vertical to the lens as the cement sets (Fig. 4).

Once the cement has set, you can complete final assembly. Locate the negative (woven) electrode lead of the flashtube and connect it to the hole marked FT1(-) in the component-placement guide in Fig. 2. Then connect the positive electrode lead (it exits the end of the flashtube opposite the negative electrode lead) to the FT1(+) point on the board. The only connection left to be made is the spark-plug test lead. Locate this lead and connect and solder it to the high-voltage terminal on the flashtube. (Note: The high-voltage terminal is the metal band affixed to the outside of the flashtube.) Pack the connection with Silastic cement to insulate it and set the assembly aside to harden.

When the cement has set, slide the circuit board assembly into the flashlight case and anchor it in place with




Fig. 3. Wired pc board assembly shows T1 mounted with hardware fiber washer. C4 is on top of C3.

two 4-40 × ½-in. machine screws. Screw on the reflector assembly but under no circumstances permit the reflector itself to rotate. If you allow the reflector to rotate, the flashtube will be damaged or a short circuit will develop.

How to Use. Before making any timing adjustment on your car, set the dwell time of the ignition points according to the recommendation of the manufacturer of your car. This can be accomplished by using a dwell meter on most General Motors cars and adjusting the points with an Allen wrench while the engine is running. On other car makes, the dwell angle must be set by adjusting the point gap opening. Bear in mind that the dwell angle must always be properly set *before* the timing is adjusted as changes in the dwell angle will change ignition timing.

Locate the number one cylinder of your car's engine. (On 4- and 6-cylinder engines, it will be the one

nearest the front of the engine. The number-one cylinder on a V8 engine is also nearest the front, but it could be either on the left or the right.) With the engine shut off, remove the ignition lead to the number-one cylinder and connect the timing light's plug lead to the plug. Replace the ignition wire.

Before starting the engine, it is advisable to clean the flywheel and paint a thin white line over the timing mark so that it is readily visible. Then refer to the decal, located in the front of the engine compartment of late model cars, to determine the calibration of the timing scale and proper ignition timing specifications.

Remove the rubber hose connected to the vacuum diaphragm of the distributor and plug the hose opening with a pencil. This disables the automatic vacuum advance built into the distributor. Timing of an engine is always adjusted with the vacuum advance disabled. If you neglect to do this, you will set the timing incorrectly and the engine will not operate properly.

Connect the remaining two timing light cables to the car's battery, observing the proper polarity. Start the engine. The light should now be flashing at a rate of 4 to 5 times per second. Aim the timing light at the flywheel to locate the timing mark. The mark should appear to be stationary. If timing is not correct, loosen the bolt that clamps the distributor assembly to the engine and rotate the distributor in the direction that yields the proper indication. Tighten the bolt and recheck the timing to make sure it has not changed.

Stop the engine. Remove the timing light and replace the hose to the distributor's vacuum-advance diaphragm. The timing of the engine is now correctly set. It need not be checked again until the points are replaced. ♦






Fig. 4. Flashtube mounts in enlarged hole in light reflector.



BY
MARTIN
MEYER



BUILD

An Under-\$90 Scientific Calculator

Ten digits of mantissa with 2-digit exponent and a full range of scientific operations, including double-nested parentheses.

THE inexpensive four-function calculator is an eminently practical tool for everyday home and primary-school use; however, high-school students, engineering and science majors in college, and practicing engineers and scientists require more sophisticated equipment. Fortunately, there is a new breed of calculators that is rapidly gaining popularity in professional and advanced-student circles. Going by such names as "scientific" and "slide-rule" calculators, they expand by several magnitudes the number of functions and the information-handling capacities of "ordinary" calculators for limited uses.

Scientific calculators may be capable of obtaining n th roots and n th powers; trigonometric functions (sine, cosine, tangent, etc.); natural and common logarithms; degrees-to-radians conversions; and many other functions. As a general rule, these calculators also feature at least one level of store/retrieve memory, a 10-digit mantissa with two-digit exponent, and separate displays to indicate negative quantities (in both mantissa and exponent) and overflow and disallowed functions.

Most scientific calculators with the capabilities described above sell for \$150 or more at this writing. But the POPULAR ELECTRONICS full-function,

200-decade scientific calculator costs only \$89.95 in kit form. It is 3 $\frac{3}{8}$ " wide, 6" long, and 1 $\frac{1}{2}$ " thick.

What It Does. What can you, as an electronics experimenter, do with such a calculator? The answer is, just about anything you want to do in problem solving. For example, suppose you wanted to know the equivalent resistance of a network of three resistors (560 ohms, 390 ohms, and 670 ohms) in parallel. By hand, this problem might take you 10 minutes or more. With the calculator, less than 30 seconds is needed to get the answer (171.1638788.).

Approaching a more difficult prob-




Fig. 1. IC1 and IC2 are special MOS IC's that accept the keyboard commands, perform the required operations, and deliver a signal for the 14-digit LED display. The other IC's form the interface between the MOS and LED's. The two-way transistor power supply generates the negative voltage needed by IC1 and IC2.

PARTS LIST

B1,B2—3.5-volt rechargeable batteries
 C1—50- μ F, 6-volt electrolytic capacitor
 C2,C3—4.7- μ F, 10-volt electrolytic capacitor
 D1 to D3—1N4148 diode
 D4—1N4001 rectifier diode
 D5—1N4739 zener diode
 DIS1—14-digit light-emitting diode scientific display
 IC1,IC2—MOS scientific calculator integrated circuits (see note)
 IC3 to IC5—SN75492 hex inverter integrated circuit (Texas Instruments)
 IC6,IC7—SN75491 7-segment driver integrated circuit (Texas Instruments)
 J1—Subminiature phone jack
 Q1 to Q3—2N5232 transistor
 R1—Optional charging resistor (value contingent on charging current desired)
 R2—2.2-megohm, 1/4-watt resistor
 R3—22,000-ohm miniature printed circuit potentiometer
 R4—3900-ohm, 1/4-watt resistor
 R5—1500-ohm, 1/4-watt resistor
 R6—4.7-ohm, 1/4-watt resistor
 R7 to R14—220-ohm, 1/4-watt resistor
 T1—Special converter transformer
 Misc.—Calculator case; keyboard assembly; recharger; mounting nuts (2); thin insulating washer; Molex Soldercon® printed circuit connectors; fine solder; etc.

Note: The following are available from Network Research Corp., 27 Eagle St., Spring Valley, NY 10977: complete kit of parts including manual, batteries, and ac adapter/recharger for \$89.95 (New York residents add sales tax); #N1003 keyboard assembly for \$12.00; #N1002 display assembly for \$19.50; #N1001 etched and drilled pc board for \$5.50; #N1000 MOS scientific calculator IC's for \$60 the set; #N1005 transformer for \$3; #N1004 interface IC's (5) for \$9.50 the set.

lem, suppose you wanted to know the equivalent impedance of a 560-ohm resistor and a 25.5-mH choke at 2500 Hz. The solution, 687.5569736, takes about a minute with the calculator, considerably more time with paper and pencil.

To give you a better idea of how practical the calculator is, you can throw away your logarithm and trigonometry tables. You won't need them again because they are only a few keystrokes away in your calculator—all figured out to an accuracy of nine decimal places. And that goes for π as well. (A more detailed list of the capabilities of this calculator is given in the box.)

The POPULAR ELECTRONICS calculator has built into it two levels of nested parentheses, each of which defines a variable before executing a function command. This permits the problem to be "written" into the calculator exactly as it is written down on paper. When a new parenthetical statement is opened, the previous results and functions are stored in the calculator until that level of parentheses is closed later in the problem. So, a complex problem like

$$x = \sin \left[\frac{1}{1 + \sqrt{(a+b)^2 - (c+d)^2}} \right]^3$$

where $a = 4$, $b = 5$, $c = 2$, and $d = 3$ can be solved quickly with the aid of the parentheses. The keystroke sequence would be: 1, +, (, (, 4, +, 5,), x^2 , -, (, 2, +, 3,), x^2 , $\sqrt{\quad}$, =, 1/x, sin, x^y , 3, =. When the last keystroke is executed, the display will read the answer, 8.70831579 -09, which means that the mantissa is the number shown raised to the negative ninth power of 10 (10^{-9}), which means further that the calculator employed another built-in feature—automatic scientific notation. (The calculator goes automatically to scientific notation whenever the solution is an excessively large or an excessively small number.)

Note that in the above sample problem no memory or external scratchpad was required to find the solution.

About the Circuit. The schematic diagram of the complete scientific calculator is shown in Fig. 1. Special MOS integrated circuits IC1 and IC2 are the heart of the circuit. They accept keyboard entries, perform all mathematical operations demanded, and deliver a multiplexed output to the driver circuitry for the 14-digit LED display. (The display consists of 10 mantissa digits, two exponent digits, one negative-sign digit for the exponent, and a final digit that combines the disallowed-function, minus-sign, and radian-function notation to the left of the mantissa.)

Buffers IC3 through IC5 drive the 14 digit-enable lines, while IC6 and IC7 are the segment drivers for the display. Note that all similar segments are driven simultaneously, with the digit selector choosing the correct digit of the moment.

Because the MOS chips require both positive and negative 7 volts dc referenced to common to operate and

only a 7-volt battery is used in the calculator, a two-transistor (Q1/Q2) dc-to-dc voltage converter is required. In conjunction with T1, R4, and C2, the Q1/Q2 circuit forms a push-pull power oscillator. The output of T1 is rectified by D1 and D2. It is then filtered by C3 to deliver the -7 volts required. Transistor Q3 is the power-saver switching regulator, while potentiometer R3 permits adjustment of the battery's low-voltage cutoff point.

Rectifier diode D4 converts the ac from the plug-in charger to pulsating dc for charging the two batteries. Zener diode D5 keeps the voltage from exceeding the approximately 8 volts required for recharging. An optional resistor (R7) is used to limit the charging current to a safe level.

Construction. There is no practical way of assembling the calculator without the aid of a printed circuit board. Unfortunately, since the board must have conductors on both sides

FEATURES OF THE POPULAR ELECTRONICS FULL-FUNCTION SCIENTIFIC CALCULATOR

Basic arithmetic: add, subtract, multiply, divide

Any positive or negative number between 1.99×10^{-99} and 1.99×10^{99} can be entered and displayed

Entry can be in either floating point or scientific notation, with automatic conversion to scientific notation in very large and very small numerical results

Algebraic problem entry with two levels of parentheses

10-digit mantissa with 2-digit exponent numeric display, plus battery-low, minus-sign, radians, disallowed-function, battery saver display.

Positive/negative sign selection for mantissa and exponent

Transcendental functions: sin, cos, tan, \sin^{-1} , \cos^{-1} , \tan^{-1} , common log, natural log, e^x , x^y

Convenience functions: \sqrt{x} , $1/x$, x^2

Separate memory register for storage of constants or intermediate results

Chain calculations with any sequence of functions desired

Independent system and entry clear

Trigonometric functions can be performed in either degrees or radians

Separate \leftarrow key with 9 decimal place accuracy

Automatic display cutoff to conserve battery power

Rechargeable batteries

Battery charger that doubles as ac-operated battery eliminator

and the components must be mounted as close to the board's surface as possible, there is no practical way of making this board at home. While you might be able to make the required double-sided board at home with all points properly registered, there is no known method that can be used at home to plate-through the holes. Hence, you will have to purchase the pc board from the supplier listed in the Parts List.

Shown in Fig. 2 is the component-placement guide for the main board assembly. The view is from the component side of the board. (The two sides of the board are readily identifiable because the bottom side on which no components are mounted bears the legend BOTTOM.)

Start assembly by installing and soldering into place the fixed resistors. Then proceed to installing the three electrolytic capacitors, the diodes, and the transistors, taking care to observe proper polarity and basing. Mount the transistors close to the board's surface. Use a fine-pointed soldering tip, thin-strand solder, and a minimum of heat. Frequently clean the soldering tip with a damp rag to remove excessive buildup of solder. This will minimize the possibility of solder bridges between the closely spaced foil conductors. *Do not touch or remove the MOS IC's (IC1 and IC2) from their carriers until instructed to do so.*

If you inspect T1, you will note that there are three pins in one of its corners. These pins serve as the installation "key." Install and solder into place the transformer. Potentiometer R3 mounts in the upper-right corner of the board. Then install IC3 through IC7 in their respective locations, carefully observing the notch code. As you proceed, carefully inspect the board for the presence of solder bridges. If you locate a solder bridge, reflow the solder and remove the excess.

Install the two flat (negative) battery contacts as shown. Solder them at both ends and on both sides to the copper conductors. (Note: There are small holes in the board and the battery contacts are dimpled. When properly installed, the contacts are positioned with their dimples engaging the holes.) Install and solder into place the spring-type battery contacts, making sure that the pin-connector side is vertical to the plane of the board. Mount and solder into place jack J1.




Fig. 2. Component placement on the component side of the pc board.

Straighten a strip of 24 Molex Soldercon® connectors but do not remove the connector strip. Force the end pins of the strip through a 2½-in. by ⅛-in. (16- × 3.2-mm) piece of masking tape from the non-adhesive side. Mount the connector strip in the holes just below the five IC's at the top of the board, pressing down to seat the tape firmly against the board's surface. Flip over the board and solder the protruding pins to the copper foil. Be very careful to avoid solder bridges. Flip over the board again and, using long-nose pliers, bend the connector strip back and forth until it parts from the connectors. Be careful to align the connectors properly.

In the same fashion as described above, mount a strip of 20 Soldercon connectors along the lower edge of

the board. This time, use a 2-in. (51-mm) length of masking tape. (The upper strip of connectors is for the display interconnect, while the lower is for the keyboard interconnect.)

Straighten four Soldercon strips, each consisting of 14 connectors. Install these in the holes for IC1 and IC2. Then, before breaking away the connector strips, make sure the connectors are straight and that the IC pairs are parallel to each other. Now, before you even consider opening the carrier in which IC1 and IC2 are packed, carefully read and become familiar with the procedures for handling MOS devices by reading the instructions given in the box on page 57.

With yourself properly grounded and all conditions for good MOS-device handling met, open the carrier.

With the IC's still in the carrier, determine which is which and the locations of pins 1. Pin 1 is near the small bump on each IC. To be absolutely certain of pin 1 on each IC you can use a small magnifying glass to check the IC leads near where they enter the packages. Only pin 1 in each case has a tiny hole drilled through it.

With the forefinger of the hand you have grounded pressed against the metal plate on top of IC1 remove the IC from its carrier. Check to make sure its leads are in straight lines. Then carefully install the IC in its appropriate connectors on the board. First engage the pins along one side of the IC in the connectors. Once this is accomplished, work the leads along the other side into their connectors. Apply firm, even pressure to the IC to seat it in its connectors. Do not force the IC into the connectors or subject it to torsional forces or you might misalign or even break off pins. If insertion is difficult, replace the IC in its carrier. Then, insert and remove an old IC in the connectors several times to "form" them. Any DIP IC will do; just make sure to cover all connectors. Now, install the IC from the carrier.

Repeat the above procedure for IC2.

The display comes as a completely wired assembly, with its 24 connector pins already mounted in place. Just make sure that the pins are in a straight line. Carefully fit the display-board pins into their respective connectors on the main board. Press the display board into place so that it rests on the five upper IC's with a slight tilt.

The keyboard also comes as a complete assembly, including connector pins. Straighten any out-of-line pins and engage them in the connectors along the lower edge of the main board. Gently seat the keyboard assembly in place until the narrower portions of the upper two plastic posts on the keyboard assembly engage the smaller of the holes above the negative-terminal battery contacts on the main board.

Slide the entire assembly into the top half of the calculator case until the two small plastic tabs on the bottom end of the keyboard engage the molded slots in the case top. At this time, two threaded plastic posts should appear through the holes immediately above the negative battery contacts on the main board, and J1 should slightly protrude through its slot in the case.

Holding the board assembly in place

in the case, secure the two together with small nuts over the threaded posts. (Note: Because of possible interference between nut and close-by foil conductor near the left post, precede the nut here with a thin insulating washer.)

Place the power switch in the OFF position, and tape it in place until the batteries have been installed. The batteries are marked with + and - signs. The + sides are protected by sleeveings that extend beyond the bodies of the batteries. The sleeveings are notched in such a manner that the batteries will fit into their respective locations in only one way. Slip the batteries into place. This completes construction.

SAFE HANDLING OF MOS IC'S

Prior to any construction and before removing MOS IC's from their protective carriers, it's imperative that certain precautions be understood and followed:

All insulated-gate MOS devices can be permanently damaged by excessively high electronic fields. Random electrostatic charges *must* be kept away from MOS devices. Anyone who handles the devices should wear anti-static clothing (preferably cotton) and, if possible, cotton gloves. Do *not* wear synthetic fabrics, particularly nylon; they readily build up static charges.

All working surfaces where MOS devices are handled should be conductive and at ground potential. Before handling, you should also be grounded. And avoid dropping MOS devices because of possible contact with charged surfaces or objects.

All apparatus that is to come into contact with MOS devices must be grounded, including your soldering iron's tip. Never insert or remove a MOS device in a powered circuit. When inserting or removing a MOS device, touch the grounded surface only after you have grounded yourself. If possible, ground the conductor pattern around the area where the device is to be installed with conductive tape or aluminum foil during installation and removal. When a good MOS device is removed from a circuit, immediately install it in a protective carrier.

You can ground the tip of your soldering iron by wrapping around its thick portion a copper strap and fastening the strap to a length of meshed cable. The free end of the cable then goes to a good ground. To ground yourself, use a similar procedure. Wrap a length of meshed cable snugly around your working-hand wrist and connect the free end of the cable to a good ground.

Checkout and Adjustment. Plug the recharger into J1 and let the batteries charge for a few hours. Then disconnect the charger. Remove the tape from the power switch and set it to ON. The right-hand mantissa digit and its decimal point should come on, displaying 0. Leave the power applied and, after about a 30-second delay, the 0 and decimal point will blank out, being replaced by a minus sign in the exponent display. This indicates that the battery-saver feature is working.


Press the clear (C) key to restore 0 to the display. Feed in the numbers 1 through 0; operate the +/- and EE (enter exponent) keys; feed in 88; and press the +/- key. The display should now read -1234567890-88. Press the degrees-to-radians key; a small diagonal bar segment should come on to the extreme left of the display. Operate this key again, and the bar should extinguish. Press the C key.

Press the π key. The display should now read 3.141592654. Depress C. Now, with 0 displayed in each case, press log (common logarithm), 1n (natural logarithm), and 1/x (reciprocal). In each case, before depressing C, the disallowed function indicator, an inverted L, should show at the far left of the display.

To adjust battery-low indicator potentiometer R3, it is necessary to first fully charge the batteries. Plug the battery charger into J1 and the ac outlet. With the power switch set to OFF, charge the batteries for about 8 hours. Then use the calculator for about 4 hours. Then, with the power ON, adjust R3 with a thin-bladed screwdriver through the hole in the bottom of the main board, until the battery-low indicator (an L at the left of the display) comes on.

Install the back of the calculator case by inserting the two bottom "hooks" into their respective slots at the bottom end of the calculator. The top end simply snaps into place. A narrow slot at the top of the case is provided to permit the case to be reopened as desired with a coin or screwdriver blade. Simply twist.

The calculator can be operated from fully charged batteries for about 4 to 5 hours. When the charge runs down, simply plug in the recharger. Recharging takes 8 to 10 hours. The battery charger can also be used as a convenient battery eliminator. However, *under no circumstances should the recharger be used if there are no batteries in the calculator.* ♦



IC Speed Controller for HO Model Railroads

*Precision low-cost device provides
full control flexibility and simple
speed indication option*

BY ROBERT D. PASCOE


WITH A PAIR of integrated-circuit operational amplifiers and a handful of parts, you can build a precision speed controller for HO-gauge model railroads at minimal cost. The solid-state controller features forward/reverse, stop, increase-speed, and decrease-speed switches for full control flexibility. In addition, optional lighted pushbutton switches can be used to provide a vis-

ual indication of how fast the train is moving on its tracks. The faster the train moves, the brighter the light from the lamps.

About the Circuit. Operational amplifier *IC1*, in conjunction with transistors *Q1* and *Q2* (see schematic diagram), forms a voltage regulator circuit. The output voltage from this circuit is determined by the voltage at the

wiper at potentiometer *R2* and the dc voltage across capacitor *C3*. Op amp *IC2* is connected in a voltage-follower configuration. The dc voltage across *C3*, the reference for the regulator, is a product of the time a constant current is "pumped" into the capacitor. The two current "pumps" in this system are made up of the *Q3* and *Q4* circuits, with *Q3* the negative and *Q4* the positive pump.

BY DON LANCASTER



PART I

*The keyer
combines pitch
and envelope
information in
an amplifier to shape
a realistic mode.*

KEYING & VCA CIRCUITS FOR ELECTRONIC MUSIC INSTRUMENTS

KEYING circuits go by many names. In organs, they are called simply keyers; in traditional electronic synthesizers, they are often called voltage-controlled amplifiers (vca's), envelope shapers, or modulators. Functionally, they are electronic multipliers. All of them do the same job—they combine pitch information with the envelope information to produce a realistic note or note sequence.

Done properly, this sets the attack, sustain, fallback, decay, and snubbing of any note on an individual basis. Envelope control can also introduce such special effects as percussion, the "bite" on the leading edge of a horn sound, echos, tremelo, and noise modulation.

A very few older organs did not employ keyers. They simply applied and removed the supply voltage to and from oscillators or used the keys themselves as off/on note controllers. Envelope shaping ability is very limited by this means. At the other extreme, some true computer composing circuits and programs completely specify the amplitude and frequency instantaneously. With these exceptions, virtually every other electronic music system generates tones and envelope information separately. These two signals are then routed into a circuit that provides a combination of the desired loudness and frequency.

The keyer or vca might work on any note in a monophonic instrument, or

one individual keyer can be supplied with each note in a polyphonic system. We can use much more sophisticated keying circuitry if we need only a few, rather than one for each note. Keying or envelope shaping can take place either before or after the timbre or tone-quality circuitry, working either with the raw frequencies as generated or the final highly structured harmonic tone. Organs usually employ fixed formant filters; and a polyphonic instrument is usually keyed first and voiced later. In synthesizers, the note will more often be colored by a patchwork of voltage-controlled oscillators (vco's) and filters (vcf's), and then envelope shaping takes place.




Fig. 1. In a good keyer, pitch and envelope waveforms (above A) are combined to produce a note which is their mathematical product (below A). Output of poor keyer (B) has excessive transients; (C) has envelope in output; (D) has unequal positive and negative swings.

of the tone or waveshape without behaving like a low-pass filter.

To be useful in a circuit, the keyer should have a medium-to-high tone input impedance and a low output impedance so that it can drive output and timbre circuitry without difficulty and does not load down the tone source too heavily. The impedance at the envelope input would ideally be infinite so that large-value resistors and economical small capacitors could be used for attack-sustain-decay shaping. This is particularly important on polyphonic instruments where a hundred or more keyer circuits might be needed.

Keyer design is no simple task, since it shares all the woes of any faithful electronic analog or digital multiplication problem. Let us look at some popular approaches to keyer design. In this first part of our two-part article on keyers, we will discuss diode, differential-amplifier, four-quadrant multiplier, and gain block keyers. Next month, JFET, MOSFET, Transconductance-amplifier and CMOS keyers.

Diode Keyer. The diode keyer is by now, fairly obsolete. An ordinary silicon diode has its small-signal (50 mV or less) ac impedance set by

the direct current through the diode. If there is no current, the diode is an open circuit. For small direct currents, the impedance presented to ac signals is given by the ratio $26/I$, where I is the current in milliamperes. So, a diode carrying a 0.5-mA current "looks" like 52 ohms to a low-level ac signal routed through it.

In Fig. 2A, one capacitor is used to couple a tone into the diode and use the envelope information to set the direct current through the diode. The disadvantage of this circuit is that it will thump as the envelope appears in the output. A second diode and equal positive and negative signal swings (Fig. 2B) from the envelope circuitry overcome this disadvantage. The two diodes are in series across the envelope circuit but in parallel with the tone input. Two more diodes (Fig. 2C) eliminate the extra coupling capacitor.

Input impedance is low, output impedance is high, and a wide voltage swing into a medium resistive load is needed for the envelope input. But if the diodes are identical and if the control voltages are also identical, and if the ac signal level is low enough, the diode keyer can operate without introducing intolerable distortion, and it

What a Keyer Does. Any keying circuit must simply control the gain of the tones fed through it. In Fig. 1 are shown some good and some bad things keyers do. The keyer must behave as a linear, electrically bilateral variable resistor. Ideally, it must introduce no coloration or significant distortion of its own (Fig. 1A).

A keyer must be transient-free. This means that no ringing or overshoot can be permitted as in Fig. 1B. It also means that no feedthrough of the envelope information to the output can be permitted (Fig. 1C). The result of feedthrough is a loud thump and other response-recovery problems later on in the circuit. Any keyer circuit in which the dc output level changes as a function of the envelope command is bound to be a bad design and will thump badly.

A keyer must treat positive and negative signal swings equally, amplifying or attenuating them with equal gain (Fig. 1D). And the keyer system must have a wide enough frequency response to follow faithfully the envelope and pass all frequencies




Fig. 2. Simple diode keyer (A) thumps as envelope appears in output. Two diodes (B) eliminate most of output thumping. Four-diode version (C) saves one capacitor and has lower distortion.

will not cost much to make. (A diode keyer will always add some distortion.)

Various transistor schemes have been used in keying setups. They are basically diode keyers that use the base-emitter junctions of transistors as the multiplier elements. They ease the loading and impedance problems, but they can introduce thumping if they are not properly designed. Today, we have much better methods.

Differential Amplifier. In Fig. 3A is shown a differential amplifier. It is the most commonly used amplifying circuit at this time and is found in almost all linear integrated circuits. A differential amplifier normally amplifies the difference between two input signals. In Fig. 3A, one input is tied to ground to provide single-ended-input operation. This circuit can be used as a keyer by routing the tone signal into input X and the envelope into input Y.

If a fixed voltage is applied to input Y, some emitter current will appear in Q1 and Q3. Input A goes to Q1 and comes out of the transistor's emitter. The emitter signal drives Q3, which is operated as a grounded-base stage, and an amplified version of the input signal appears at Q3's collector.

The gain of the circuit in Fig. 3A is obtained from the formula $IR/104$ where R is the Q3 collector load resistance in kilohms and I is the emitter current in Q3, the 104 comes about because Q3 receives only half the

available current and because Q1's output impedance is equal to the input impedance of Q3, which yields a second 2:1 attenuation.

It is important to note that the gain is directly proportional to the emitter current. Change the voltage on input Y, and the gain changes, and the product of the envelope and tone input signals is obtained. This type of circuit is called a vca. It bilaterally and at high speed gives the product of the two input signals.

One obvious problem with this circuit is that the dc drop across Q3's collector load resistor follows the envelope, resulting in two output terms—the desired shaped tone and an undesirable thumping from envelope feedthrough. In Fig. 3B, a second load resistor, in the collector circuit of Q1, has been added. This circuit has two outputs, one of which is in-phase and the other out-of-phase with the input. Both outputs bounce up and down together.

A good differential amplifier ignores the common-mode up-and-down bouncing of the input signals. It is only the difference between the two signals that matters. So, by simply adding still another differential amplifier stage to the one shown in Fig. 3B, the output stays at a fixed dc level regardless of the envelope and is a thump-free replica of the desired signal.

Differential amplifiers are widely used in synthesizer vca's. While many

similar devices exist, the RCA CA3000 series linear IC's offer many differential-amplifier possibilities. An ordinary 741 or 5558 operational amplifier can be used to eliminate the common-mode thumping on the last stage. The differential-amplifier vca offers good input and output impedances, controllable gain, and large signal swing. The envelope signal must be referenced to a negative supply, and the input impedance might be a bit lower than we would like it to be. Dynamic range is good and distortion is low, but the system becomes a bit complex if a separate circuit is used for each polyphonic note. The differential-amplifier vca is a very good choice for monophonic synthesizer circuits.

Four-Quadrant Multiplier. A four-quadrant multiplier is a true electronic multiplier that provides the product of the envelope and pitch inputs directly. No offsets are needed on the envelope input, and the output is normally referenced to ground.

A typical four-quadrant multiplier circuit is shown schematically in Fig. 4. The multiple paths through all the differentially-arranged transistors provide for automatic cancelling of common-mode feedthrough and thumping. As a sometimes handy gimmick in some advanced synthesizers the phase of the tone signal is reversed by inverting the envelope.




Fig. 3. In basic differential amplifier (A), envelope causes thump in the output. An additional amplifier, can be added (B) to eliminate thump. Second stage can be an ordinary 741 operational amplifier.





Fig. 4 (A) are typical connections for 4-quadrant multiplier. Key internal circuitry is shown at (B).

Typical four-quadrant multiplier IC's include Motorola's MC1595 and Analog Devices' AD532. Alternatively, you can use the much lower priced Signetics 5596 as the key component

in a multiplier of your own design. The only real disadvantage with the four-quadrant multiplier is its cost. None of these IC's is inexpensive. Some exceed \$20 each and obviously

are too costly if you are considering using one for each note in a polyphonic system. Aside from this, the four-quadrant multiplier is just about the best you could hope for.

Gain Block. Several linear IC's offer remote-controlled gain capability that can be used as a keyer circuit. Motorola's MFC6040 is a typical example of such a circuit (Fig. 5). It costs about \$1. Its circuit is one more variant on the differential-amplifier theme




Fig. 5. Gain block envelope shaper.

with common-mode bucking. Typical voltage gain, wide open, is 3:1 or 10 dB; attenuation can go as low as 70 dB below full output.

The output swing of the MFC6040 can be up to 6 volts peak-to-peak. One potential disadvantage of the circuit is that the attenuation is somewhat nonlinear. ♦

SBE

Sentinel


SCANNING MONITOR RECEIVERS

HF/FM • VHF/FM • UHF/FM

Now—the "Sentinels", a series of fine monitor receivers joins the big, world-wide-accepted line of SBE communications equipment. Single or dual band models of these versatile, application-oriented SBE scanners provide coverage of the most widely used VHF/UHF bands. For example, the six different receivers available give FM reception and positive scanning operation for business, industrial (including RCC and other mobile telephone), law enforcement, fire, highway emergency, traffic advisory, marine—including intership / Ship-to-shore / Coast Guard/Weather — many other services.

SIX MODELS:

- Sentinel I: Hi-144-171MHz, Lo, 30-51MHz.
- Sentinel II: 144-171MHz.
- Sentinel III: 30-51MHz.
- Sentinel V: 450-470MHz.
- Sentinel VI: Hi-450-470MHz, Lo-144-171 MHz.
- Sentinel VII: Marine, 156-164MHz.



8 channels—continuous "scanning". Receiver locks on first channel on which signal appears.

Priority channel feature: Receiver shifts instantly to designated channel whenever carrier appears on it regardless of existing channel status.

Channel lock-out buttons: Unwanted channels can be locked out.

Manual advance button allows channels to be scanned manually.

Base or mobile (AC or DC). Use in car or home/office. Operates both on 12VDC for mobile and 115VAC for home station.

Big audio volume—3 to 4 watts.




- Fractional microvolt sensitivity
 - Squelch • Built-in speaker • Jack for external speaker • Crystals used are readily available types (not included).
- Complete w/ plug-in telescoping antenna, mobile mounting bracket and cord, plug sets for 12VAC and 115VAC.

Write for Brochure

SBE LINEAR SYSTEMS, INC.
220 Airport Blvd., Watsonville, CA 95076.

The better the the better you

Compare
what we
offer in kits
and lessons.
Compare
our
tuition



DIGITAL
MULTIMETER



ELECTRO - LAB

NTS DIGITAL GR-2000 SOLID STATE
COLOR TV WITH 315 SQ. IN. PICTURE
AND VARACTOR DIGITAL TUNING

TROUBLESHOOTER
VOM

As an NTS student you'll acquire the know-how that comes with first-hand training on NTS professional equipment. Equipment you'll build and keep. Our courses include equipment like the 5" solid-state oscilloscope, transistor and tube-tester, vector monitor scope, 74 sq. in. B&W TV, and solid state stereo AM-FM receiver. The unique NTS **Digital GR-2000 color TV** with first ever features like silent varactor diode tuning; digital channel selection, (with optional digital clock,) and big 315 sq. in. ultra rectangular screen. This is just a sampling of the kind of

better equipment that gets you better equipped for the electronics industry.

This electronic gear is not only designed for training; it's field type — like you'll meet on the job, or when you're making service calls. And with NTS easy-to-read, profusely illustrated lessons you learn the theory behind these tools of the trade.

Choose from 12 NTS courses covering a wide range of fields in electronics, each complete with equipment, lessons, and manuals to make your training more practical and interesting.

Simulated TV reception

equipment will be equipped.



Compare our training; compare our tuition. We employ no middlemen because we need no salesmen. We believe you have the right to make your own decisions based on the facts, and you'll find these all spelled out in our catalog mailing. Lessons, kits, and experiments are described in full color. Most liberal refund policy and cancellation privileges — it's all in writing. And our low tuition is another big advantage. No frills, no commissions to pay. This means lower tuition for you. You receive solid training value. NTS puts more into your training, so you get more out of

it. Make your own decision. Mail the card, or write if card is missing. There's no obligation, ever, and no salesman will call.

Approved for Veteran Training. Get facts on new 2-year extension.

NATIONAL TECHNICAL SCHOOLS

TECHNICAL-TRADE TRAINING SINCE 1905
Resident & Home Study Schools
4000 South Figueroa St., Los Angeles, Calif. 90037

THE tuner is the "radio" portion of your music system. Although most tuners cover both the AM and FM broadcast bands (and proposed government legislation will make this mandatory), the following comments apply specifically to FM tuners.

The tuner's function is to separate one desired signal from the many intercepted by the antenna, amplify it millions of times, convert its frequency modulation to an exact facsimile of the original program, and (if it is a stereo program) subject the detected signal to a complex process which separates it into left and right stereo channels.

Like amplifiers, most tuners tend to sound pretty much alike on ordinary program material. Many people place great store in numerical specifications for such characteristics as sensitivity and selectivity. Actually, neither of these is easy to reduce to a single convenient number that defines that aspect of the tuner's performance. Numbers are used, of course; but they are frequently misunderstood or misinterpreted.

Sensitivity. This refers to the ability of a tuner to receive a weak signal with acceptably low noise and distortion. The IHF Usable Sensitivity rating is most often quoted, although it does not correspond to a really listenable signal. Most good tuners have an IHF sensitivity of less than $3 \mu\text{V}$, and some are as low as $1.5 \mu\text{V}$. Although in practice it would not be possible to detect any real difference between two tuners whose sensitivities differed by a factor of two (all else being equal), there is a tendency to make much of differences of a few tenths of a microvolt, a quite insignificant amount. More meaningful is the 50-dB Quiet-ing Sensitivity rating included in a proposed IHF tuner standard, but not yet in wide use. Our test reports in POPULAR ELECTRONICS do include it, however. This is usually in the range of 3 to $7 \mu\text{V}$ and represents the weakest mono signal that can be received without excessive background hiss. For stereo reception, all these sensitivity figures should be multiplied by a factor of ten, which may explain why stereo sensitivity ratings are not widely publicized!

Of course, these sensitivity numbers have no absolute meaning to the consumer who cannot know the actual received signal strengths in his area. In rural locations, one can indeed find

HOW TO "READ" FM TUNER SPECS

BY JULIAN D. HIRSCH

signals of a few microvolts, and sometimes the highest possible tuner sensitivity is needed in such locations. In most urban and suburban locations, the tuner receives from its antenna hundreds or even thousands of microvolts from dozens of stations.

Selectivity. Clearly, high sensitivity is not likely to be an important tuner rating for the city dweller. What about selectivity? FM stations in any given area are assigned to channels at 400-kHz intervals (alternate channel spacing). If you are located close to a powerful FM station and wish to receive a far-off station only 400 kHz removed, you will need high alternate-channel selectivity. Most FM tuners have selectivity ratings between 45 and 60 dB, which is generally adequate for interference-free reception. If you have a "problem," there are some tuners whose alternate-channel selectivity is 90 dB or more. They are expensive, but well worth it if you need their special qualities.

In strong-signal areas, some tuners are subject to spurious responses—signals appearing on the dial in unexpected places and sometimes interfering with a desired signal. The relevant ratings—image rejection, spurious rejection, i-f rejection—are also expressed in decibels, with the higher numbers being better.

Capture Ratio. A major cause of distorted FM sound is multipath recep-

tion, caused by a signal reflecting from various structures and reaching the antenna from different directions and at slightly different times. The tuner specifications related to low multipath distortion are capture ratio (the lower the better, with most good tuners under 3 dB and the best reaching 1 dB or less), and AM rejection (ratings in excess of 50 dB are good, and a few are as high as 70 dB). You should be aware that no tuner can be completely immune to multipath distortion and that the best cure for this and most other FM reception problems is a good directional antenna which can be rotated to obtain best results.

The tuner distortion rating should be well under 1%, and most good tuners are rated between 0.2% and 0.5% in mono, and about twice as much in stereo. Stereo channel separation varies with modulating frequency, but is often specified at 400 Hz or 1000 Hz, where it is greatest. Comprehensive ratings include a definition of separation over a range of frequencies, such as 100 to 10,000 Hz. If the separation exceeds 20 dB over most of the audio range, you can be assured of a satisfactory stereo effect. Many tuners in all price ranges have 30 to 40 dB of separation over most of the audio band.

Operating Ease. Many important tuner differences relate to their ease of operation, rather than their electrical performance. The tuning dial should be legible and well calibrated. (Some tuners, even high-priced units, are difficult to set accurately to a known frequency because of inadequate dial calibration.) The tuning "feel" should be smooth and positive. Tuning indicators, whether meters or lights, should give an accurate indication of correct tuning. Interstation-noise muting circuits should be free from bursts of noise as one tunes through a station (although many are not). All of these characteristics are easy to judge for yourself and require no technical knowledge.

There are several tuners with digital frequency readouts instead of the usual slide-rule dial. This eliminates any problems of dial calibration but adds appreciably to the cost of the tuner. Compensating for their higher prices is the fact that most digital tuners also have above-average performance in most other respects relating to high fidelity. ♦

Identifies leads on unknown transistors, indicates PNP or NPN polarity, and shows up bad devices

BUILD THE TRANSISTOR IDENTOMETER

BY JOHN T. BAILEY


MOST experimenters have a drawer full of unidentified transistors which are of little use unless the leads and type (pnp or npn) can be determined. Actually, that's the only really important information needed to apply a transistor in a circuit—assuming it is “good” to begin with. Of course, it's nice to

know what the transistor's beta is, but this is not essential in many applications.

The Identometer was designed to provide a quick check of a transistor's leads and type. It operates on the basis that bipolar transistors will operate, but poorly, if the emitter and collector leads are interchanged without also reversing the power supply. Since a transistor has three leads, it is possible to connect them in six different ways. With a transistor plugged into the test circuit, the Identometer has a switch to make the six different connections. When the right one is selected, an indicator light comes on. The light also tells whether the unit is npn or pnp.

Circuit Operation. A schematic of the circuit is shown in Fig. 1. Note that T_1 has two secondaries, one serving as the power supply for the Q_1 -LED1 and Q_2 -LED2 circuits and the other for the unknown transistor. Transistor Q_1 saturates when the upper secondary voltage is in the positive half cycle and its base is positive. Transistor Q_2 saturates when its collector has a negative voltage and its base is negative. The two transformer secondaries must be in phase as shown by the small dots at terminals 1 and 3.


The circuit is equivalent to an exclusive OR logic device, which has an output only when the two inputs are at different levels. The high or low signal requirements are provided by the transistor being tested and the instantaneous polarity of the ac line at the moment. The combination is one polarity for npn transistors and the opposite polarity for pnp types.



PARTS LISTS

- D1, D2—1N4001 diode
- D3, D4—1N914 diode
- LED1, LED2—Light-emitting diode (Calec-tro K4-559 or similar)
- Q1—HEP736 transistor
- Q2—HEP715 transistor
- R1-R3—1000-ohm, ½-watt resistor
- R4—18,000-ohm, ½-watt resistor
- S1—Spst switch
- S2—3-pole, 6-position rotary switch (Mal-lory 3236J or similar)
- SO1—Molded transistor socket
- T1—12-volt, 300-mA filament transformer (Radio Shack 273-1385, modified per text)
- Misc.—Plastic case (Radio Shack 270-231), Insulated miniature alligator clips (red, green, and yellow; Radio Shack 270-378), knob with pointer, line cord, mounting hardware, press-on type, etc.

Fig. 1. Transistor being tested is plugged into SO1 or connected to color-coded alligator clips.



This distinction provides the type identification.

With the correct phasing of the 3-4 secondary of *T1*, the exclusive OR signals are accepted by the LED driver that can react to a compatible signal during its half cycle of the ac. Diodes *D3* and *D4* prevent slight differences in the voltage levels from turning on the drivers.

Construction. To duplicate the pro-

TOTYPE and use the pc boards shown in Fig. 2, certain mechanical modifications must be made to two of the components. Transformer *T1* must have its four terminals cut to a size that can fit into the pc board. As shown in Fig. 3, two more tabs must be added to terminate a new winding. The molded plastic form of this transformer allows adding the two new terminals (3 and 4 on the schematic). The six terminals will

then be spaced three on each side, on ⅜-in. centers.

Wind 46 turns of #34 enamelled wire around the original core. There is enough room to do this, although it will take a little patience. Be sure that the new winding is wound in the same direction as the 12-volt winding already on the transformer to ensure correct phasing. (Don't scrape the enamel off the wire.) If you should wind the new secondary the wrong






Fig. 2. Foil pattern for main pc board is at left, with component layout at right. Foil pattern above is for rotary switch.



way, it is easier to route the ends to the correct terminals than to start over or modify the pc board.

The terminals of S2 must be modified as shown in Fig. 3 so that the switch will fit the pc board as shown in Fig. 2.

Now you are ready to assemble the circuit on the main board as shown in Fig. 2. The front panel is marked as shown in the photograph with the six switch positions identified. Install SO1 and mount the LED's in small rubber grommets, properly identified.




Fig. 3. Add a winding and terminals to the transformer and alter switch lugs as shown.

Then mount the switch on the front panel. Connect the larger board to it with spacers. Note that the large board has a small spacer supporting it from the hole drilled near the center of the rotary switch board.

Drill three small holes for the colored test leads and put grommets in the holes. The leads are terminated with color-coded insulated alligator clips. From the top of the panel, the lowest test lead (green) is on a line from the emitter terminal on SO1; the center lead (yellow) is the base; and the upper lead (red) is the collector.

Operation. Connect the three color-coded test leads to the unknown transistor in any order, turn on the power, and rotate S1 until one of the LED's illuminates. Make sure that this only occurs at one position. The position of the switch will then identify the leads and the LED will indicate the type.

If the transistor being tested is not good (either open, shorted or leaky), neither indicator may come on or one or both may light at more than one switch setting.

The Identometer will not check FET's, nor will it work "in circuit." When checking power transistors, particularly germanium types, there may be some unpredictable results due to the high leakage current associated with these transistors. ♦

Simple Squelching Circuit for Stereo FM Tuners

BY LAWRENCE N. DWORSKY

MANY inexpensive stereo FM tuners have no automatic "squelch" to eliminate between-station hiss. However, they invariably have a stereo indicator lamp that can be used to trigger a very simple squelching circuit like that shown in the schematic.


The add-on squelch circuit shown employs an inexpensive photo Darlington amplifier (HEP1001), operating with its base connection "floating". The Darlington amplifier switches from a very high resistance in darkness to a very low resistance when illuminated by relatively low light levels. When the photo transistor is switched to low resistance, essentially the supply voltage from the battery is applied across the gate-source terminals of both HEP 802 FET's. This pinches off the FET's and causes them to present a very high source-drain resistance across the outputs of the tuner, effectively doing nothing.

When there is no light present, the photo transistor presents a high resistance to the gates of the FET's. The source-drain resistance of the FET's therefore drops to about 200 ohms, effectively short-circuiting the outputs of the tuner.

If the tuner being used has an exceptionally low output impedance—less than 600 ohms or so—the between-station muting may be insufficient with this setup. In this case, a 100-ohm resistor placed in each output line of the tuner (see phantomed portion of schematic) should remedy the problem. Since most amplifiers have a relatively high input impedance, these resistors should have no effect on system performance.

No power switch is needed with the add-on squelch circuit because battery drain is very low. Even when operating at full capacity, the drain is less than 10 μ A. So, the battery will last just about its shelf life with power continuously on, which eliminates the bother of having to remember to turn on an extra power switch.

When installing the squelch circuit, use only shielded audio cable to make the hookups between tuner, squelcher, and amplifier. Also, mount the Darlington amplifier as close as possible to the stereo indicator lamp in the tuner. This transistor is very sensitive; so, care must be taken to insure that it "sees" light from only the stereo indicator lamp and not from any other light sources. ♦





LIGHTNING DAMAGE INSURANCE JOBS

By John T. Frye, W9EGV

"IT'S TIME we furthered your education by discussing lightning-damage insurance jobs that come into the shop," Mac announced to Barney his assistant, during their afternoon Coke-break.

"A man can't even enjoy a Coke around here without having it laced with knowledge," the red-headed youth grumbled, "but go ahead—if you must."

"That's what I like: an enthusiastic listener," Mac said, lighting his pipe. "There are three entities involved in this kind of a job, and each must be considered: the owner of the damaged electronic equipment, his insurance company, and the service shop called upon to assess the nature and extent of the damage and possibly to repair it. Let's run quickly through the chronology of such a job; then we'll go back and discuss interesting features."

"First, an insured who thinks lightning has damaged his radio, TV, hi-fi, amateur station, CB transceiver, etc., should promptly report this to his insurance agent, who will instruct him to get an estimate of the damage from an established service shop. (That doesn't mean the insured's brother-in-law who tinkers around with electronics in his spare time!) At the shop, a technician carefully examines the equipment to see if the set failure was caused by lightning, the extent of the damage, and the probable cost of repairing the set. This information is relayed to the insurance agent, directly or through the owner, and the agent calls an adjuster to look at the set. It may be a few days before the adjuster calls at the shop; but when he does, he will want the technician to show him hard evidence that lightning did the damage; so all such evidence should be carefully preserved for his inspection.

"The adjuster reports to the insurance company, which, based on his recommendation, either (1) denies all responsibility due to a lack of evi-

dence that the failure was caused by lightning, (2) authorizes a repair of the set, or (3) because the cost of repair is prohibitive, makes some cash or replacement arrangement with the insured. The company pays for the estimate in the last two cases; the customer pays in the first. At any rate, the bill is made out in triplicate: one for the customer, one for the insurance company, and one for our files. The customer pays us, and we give him two receipted copies of the bill. He turns one over to the insurance company, and they send him a check."

"Why might a person think lightning had damaged his equipment?"

"Such circumstantial evidence can vary all the way from a coincidence in which the set would not operate immediately after a heavy thunderstorm to much stronger evidence in which a ball of fire comes out of the TV set at the same time there is a snap of lightning from a nearby stroke, followed by smoke curling out the rear of the cabinet."

"That last reminds me of Thoreau's remark: 'Some circumstantial evidence is pretty strong, like finding a trout in the milk.' How does lightning usually reach the equipment?"

"In the case of a receiver attached to an outside antenna, the stroke or induced voltage surge can come in on the feedline, but more often it enters via the power line. A bolt doesn't have to strike the line for this to occur. All it has to do is strike in the vicinity. After all, the current of lightning strikes has been estimated to be as high as 200,000 amperes, with 15,000 to 20,000 amperes being an average value; and the voltages producing the strike are estimated to be as high as 100,000,000 volts. Lasting only microseconds, such a strike produces a tremendous field that induces a voltage surge on the primary of a power line that can leap across to a transformer secondary and enter the house through the ac wiring. This surge can

easily bridge open switch contacts of a radio or TV receiver. Most people don't understand this.

"What kind of damage does lightning do?"

"Mark Twain remarked that one thing you could lie about and get away with was to tell something you heard a parrot say. Lightning stories are like that. No one can prove you're lying. I've seen lightning strike a horizontal antenna and reduce it to a line of little copper beads in the grass below. When a conductor carries a heavy current, forces are developed by the accompanying magnetic field that tend to crush the conductor. This is called the 'pinch' effect. Another time I saw a rubber-covered copper wire that had been hit by lightning and reduced to a rubber tube with no wire inside at all. Stranger still, the rubber insulation seemed to be intact and hardly scorched. More common effects include the fragmentation of line bypass capacitors, melted power switch contacts, fused conductors on pc boards, vacuum tube envelopes shattered,




Fig. 1. A spark gap arrester to protect ham antenna is easily made.

ruptured filter capacitors, shorted windings in power transformers, antenna input coils of radios and TV sets badly charred, flash burns on the chassis in the vicinity of line cord tie-points or the power switch, and tubes with burned out filaments. These are some of the things the adjuster will expect to see."

"I imagine the action the insurance company takes depends a lot on the policy the owner has."

"Right. The usual home owner's policy comes in a variety of types, including various deductible amounts with matching premiums. Naturally, the higher the deductible the lower the premium. TV, amateur, and CB antennas, rotators, and towers are not ordinarily covered by policies that are written to cover the house, garage, and household goods. Even then, with

such a policy, TV sets, radios, and hi-fi's are only covered for their actual cash value. The guy who has never read his policy carefully may be very chagrined to discover the total loss of his beloved but ten-year-old hi-fi does not entitle him to a brand-new stereo system at the expense of the insurance company. He may do well to recover the cost of a new stereo cartridge.




Fig. 2. In power-line arrester, current is reduced by resistor.

"But there's another way to go. If he has ham, CB, or hi-fi equipment worth \$500 or more, he can insure it for full replacement value with a separate policy usually labeled a 'personal line floater' or an 'inland marine floater.' Then, if his equipment is destroyed, the company will pay enough to buy a new system comparable to the one he had before. Such policies cost from 80¢ to better than \$2 per \$100 of declared value per year, depending on the individual company and the item insured. Jewelry, cameras, tools, service instruments, and similar equipment in the home can be insured with these policies."

"Seems to me the technician is pretty important in this operation."

That he is. Actually I do many insurance jobs here without ever seeing an adjuster. Local agents know me, and they also know the average adjuster is unqualified to assess damage to sophisticated electronic equipment. They're content to use my report as the basis for settling the claim. I'm sure this arrangement prevails in many other communities, and it puts a lot of responsibility on the technician, especially when the equipment belongs to a long-standing customer who feels 'taking' an insurance company isn't really stealing. When one of these starts hinting he wants me to declare his equipment a total loss when it isn't, or to say the damage was caused by lightning when there's no evidence to support this, I suggest that he take his set to another shop be-

cause I intend to call things exactly as I see them. Invariably, he then backs off."

"What do you think is the best insurance policy?"

"That's easy: prevention. You rarely recover your entire loss through insurance; so the best thing to do is try to protect your equipment from lightning damage. You could, of course, follow the practice observed in the old French provinces and keep some wood from a lightning-struck tree under your bed, secure in the belief you're fully protected because 'lightning never strikes twice in the same place'; but I'd suggest you employ more scientific methods. Start by making sure your house wiring is properly grounded and protected against overloads with fuses or circuit breakers. Install U.L.-approved arrestors on all TV lead-ins, antenna rotator control wires, and coax feed lines. Ground metal towers or metal masts mounted on poles or other wooden supports. Make a *good* common ground. If you don't know how—most people don't—order "Lightning Protection Code 1968," NFPA No. 78, from the National Fire Protection Association, 470 Atlantic Avenue, Boston, MA 02210, for a postpaid price of \$1.37."

"How do lightning arrestors work?"

"There are many types, but all are intended to do one job: carry a heavy surge of lightning-induced current in a conductor safely to ground, while leaving that conductor virtually disconnected from ground at all other times. Let me sketch a couple of common types. Shown in Fig. 1 is a homemade spark gap arrester for use on the open-wire feeders of a ham antenna. Gaps are spaced just wide enough not to arc with full power from the transmitter, but voltage from a nearby discharge will start the arc that carries the heavy current safely to ground. When the surge subsides, the arc stops.

"Things are different when the conductor normally carries heavy current and high voltage, as does a power line primary. Once the arc is started by lightning, the follow-current from the generator would keep it going until the arc electrodes were melted. The arrangement in Fig. 2 prevents this. The nonlinear thyrite resistor has a resistance which decreases exponentially with increasing current. When carrying the heavy discharge current, it is a virtual shortcircuit; but with the lower follow-current, the re-

sistance increases until the voltage drop across it is sufficient to stop the arc. Various resistance and gap types of lightning arrestors are manufactured for use with telephone lines, coaxial cable, twin-lead, etc.

"But remember I said most damage from lightning occurs when a surge comes in on the house wiring. That's why I think it is an excellent idea to install a secondary service lightning arrestor, such as G.E. Model 9L15CCB007, called a Home Lightning Protector, right at the service entrance. Otherwise, pull the plugs on all electronic equipment when you're going to be gone for several days or when you're home and a thunderstorm is building."

"Do you think a high antenna tower invites lightning damage to the home?"




Fig. 3. A metal antenna tower, properly grounded, provides a cone of protection for the house.

"Quite to the contrary, if the tower is metal and properly grounded or has the metal mast properly grounded, it actually provides a cone of protection as shown in Fig. 3. Note that the apex of the cone is at the top of the grounded antenna, and the radius of the base is equal to the height of the tower. A direct strike of lightning to any object inside this cone is very unlikely."

"All right, let's recapitulate: quiz your insurance agent and read your policy carefully to see exactly what kind of protection you have for your electronic equipment. To protect that equipment, use lightning arrestors on all leads entering the house, including the power leads. Make good grounds and bond them together. Pull plugs during storms or when you're going to be away from home, and don't try to con the service technician into helping you defraud the insurance company. If he goes along with that, he'll cheat you, too!"

It takes more learn about

Bell & Howell Schools introduces three fascinating learn-at-home programs featuring some of the finest equipment available as your "teachers". Choose the program you prefer—then mail card for free details today!

Experience is the best teacher, without a doubt. And when it comes to learning electronics, we feel it's hands-on experience with state-of-the-art equipment that counts the most. That's why with Bell & Howell Schools' learn-at-home programs you work with some of the most up-to-date equipment. Equipment that's being used today—and will be used tomorrow. So the skills and knowledge you acquire will be useful for years to come.

Of course, with all our learn-at-home programs you'll have plenty of lab manuals and basic principles to work with. And you'll also get exciting "teachers" to help make electronics come alive ...

Lab Starter Kit gives you hands-on experience with the very first lesson.

We get you started with the basics in an exciting way! At the very beginning you get a fully-assembled volt-ohm meter as well as design panels, modular connectors, experimental parts and battery. So you don't just read about electronics principles, you actually see them at work!

You build your own Electro-Lab® electronics training system.

Whatever program you choose, you get your own home laboratory including oscilloscope, digital multimeter and design console to give you actual experience in wiring, soldering, assembling, testing, trouble-shooting and circuit analyzing.

I. Learn new skills in the field of Home Entertainment Electronics including building the new generation color TV.

What better or more exciting way to learn digital electronics! Once you have the basics under your belt and get into color theory and service, you'll build a 25" diagonal color TV and probe into the digital technology behind digital channel numbers that flash on the screen ... a digital clock that flashes the time to the second and an automatic channel selector.

As you put the set together, you'll discover how advanced integrated circuitry works, how to trouble-shoot it and much more. Upon completion of the program you'll have gained the specialized occupational skills to service color TV's plus the principles that you can apply to repair a variety of home electronic equipment. And you'll have the foundation to understand and work with new product applications as they're developed, too!

II. Use professional communications equipment as you delve into Communication Electronics .

Here's how to pick up skills in the vital field of two-way radio, widely used in public safety, marine, industrial and transportation areas. Bell & Howell Schools Communication Electronics Program can help prepare you for the FCC licensing exam, right through to 1st class radiotelephone operator. And teach you skills in two-way radio, radar or commercial broadcasting.

For a refundable deposit, you get to use the special two-way radio equipment lab featuring an FM transceiver, frequency meter, and modulation meter. All regular, first-rate commercial grade test equipment.



"Electro-Lab" is a registered trademark of the Bell & Howell Company.
Simulated TV Picture/Test Pattern

than books to electronics.

III. Digital Trainer helps you learn the latest in Industrial Digital Electronics.

Digital technology is setting new standards of accuracy and beginning a revolution in industry. For example, more precise control in refining, manufacturing plants, food processing and transportation. And now you can learn about this technology with Bell & Howell Schools' unique Digital Trainer. You'll analyze and experiment with various types of

integrated circuits so you'll have a solid background in modern digital electronics and its applications to industry.

You study at home in your spare time ... with help as close as the telephone.

Because these are home study programs, you can learn electronics without missing a day of work or a single paycheck.

You study at your convenience—without being a classroom captive. If you ever have any questions, you can call our toll-free number for help.

You can also meet and talk shop with fellow students and instructors at "help sessions" held in 50 cities at various times throughout the year. Bell & Howell Schools tries to give you more personal attention than any other learn-at-home program.

Decide which exciting program you're interested in ... you can check more than one. Then mail postage-paid card today for free information—no obligation!

Taken for vocational purposes, these courses are approved by the state approval agency for Veterans' Benefits. Please check box on card for free information. Naturally, we cannot offer assurance of income opportunities.


1. Power Output Meter
2. Design Console
3. Modulation Meter
4. Digital Multimeter
5. Triggered Sweep Oscilloscope
6. Lab Starter Kit
7. Frequency Meter
8. FM Transceiver
9. 25" Diagonal Color TV
10. Alignment Generator
11. Lesson Tape Player
12. Digital Trainer

724R2

If card has been removed, please write to:

An Electronics Home Study School
DEVRY INSTITUTE OF TECHNOLOGY


ONE OF THE
BELL & HOWELL SCHOOLS
4141 Belmont, Chicago, Illinois 60641



Product Test Reports

TECHNICS BY PANASONIC MODEL T-200 SPEAKER SYSTEM (A Hirsch-Houck Labs Report)

Compact, inexpensive system with room-filling sound.



THE Technics Model T-200 is the least expensive of a new series of loudspeaker systems from Panasonic. It is a compact system that measures 21 3/4 in. by 12 in. by 10 1/2 in. deep (55.2 × 30.5 × 26.7 cm) and weighs slightly less than 30 lb (13.6 kg). The oiled walnut cabinet contrasts with an attractive sculptured, acoustically transparent grille that is available in either blue or brown.

The two-way system contains a 10-in. (25.4-cm) acoustic-suspension woofer that crosses over at 1800 Hz to a 1 3/4-in. (4.45-cm) cone-type tweeter. The rated dispersion angle of the tweeter is 120° in both the horizontal and vertical planes. A switch is provided on the rear of the cabinet to permit the tweeter level to be set for normal or 3 dB attenuation. (Flattest overall response is obtained with maximum tweeter output.) The system has a rated nominal impedance of 8 ohms.

The retail price of the Technics Model T-200 speaker system is \$99.95.

Laboratory Measurements. The response of the speaker system was measured in a "normal" listening room by a method that yields a good

approximation of its total energy output over the frequency range. Averaging and warble-tone measurements were used to minimize the effects of standing waves. At frequencies lower than about 300 Hz, close microphone spacing was used, and the two test curves obtained were joined together to provide a composite frequency-response curve.

The response of the woofer was notably smooth, with a resonant peak of about 3.5 dB at 75 Hz and no sign of irregularity up to several hundred hertz. The tweeter also had a rather flat response curve (although it is normal to find some irregularity at high frequencies with the measurement methods we used). Its output fell off smoothly at frequencies beyond 10,000 Hz, with no sign of a peak throughout its entire range. The overall response was a very good ±4 dB from 45 Hz to 14,000 Hz.



The bass distortion at a constant 1-watt drive level was between 3% and 5% from 100 Hz to 60 Hz. When we

varied the drive level to maintain a constant 90-dB sound-pressure level (SPL) at a distance of 1 meter from the woofer, the distortion was somewhat higher than we have measured on some other speakers of the same size, but it was not audible on program material.


The tone-burst response was fairly good. There were no signs of severe ringing or generation of spurious frequencies throughout the operating range of the system. Efficiency was moderately low, as would be expected of an acoustic-suspension design. An input of 1 watt in the midrange produced a 90-dB SPL at a 1-meter distance. This corresponds to about 80-dB SPL in the normal listening area of a typical room, which is about as loud as most people would care to listen to music in their homes.

The electrical impedance of the system was 5 ohms at 20 Hz and between 100 and 200 Hz. It peaked at 18 ohms at the 62-Hz bass resonance point. At frequencies higher than 1000 Hz, the impedance was typically 15 to 18 ohms.


User Comment. The general shape of the measured response curve for the T-200 was confirmed by our simulated live-versus-recorded listening test in which the T-200 was used to imitate the sound of a specially recorded program played through a reference speaker, our "live" orchestra. The T-200's midrange and highs were virtually perfect, but there was a slightly full quality in the lower midrange and upper bass range. This appeared to correspond with the fact




300 Hz



1800 Hz



7000 Hz



that the average woofer level was a few decibels higher than was the average tweeter level.

When a 3- to 4-dB attenuation (a

“shelf” response cut) was applied at frequencies below 1000 Hz with an octave-band equalizer, the speaker system did a near-perfect job of imita-

ting the original sound in an A-B comparison. The highs were obviously peak-free and very well dispersed.

Listening to this speaker system, one is apt to find it difficult to believe that the sound is coming from an inexpensive compact system. It gives a room-filling sound suggestive of a much larger system and provides exceptionally good musical balance and overall smoothness. The T-200 illustrates most effectively how the proper combination of conventional drivers and crossover components by a knowledgeable designer can produce a total sound character that is greater than the sum of its parts.

CIRCLE NO. 65 ON READER SERVICE CARD

PIONEER MODEL RT-1011L STEREO TAPE RECORDER (A Hirsch-Houck Labs Report)

Logic-controlled recorder handles 10½-inch reels.



THE U.S. Pioneer Electronics Model RT-1011L stereo tape recorder features three motors, three heads, solenoid-operated transport, and 7½ and 3¾ ips (19.05 and 9.53 cm/s) operating speeds. This quarter-track recorder is designed to accommodate tape reels measuring up to 10½ in. (26.7 cm) in diameter. The transport is “logic controlled” so that any operating mode or speed can be selected from any other without having to first press the STOP button. Yet, the tape is fully protected against breakage and spilling.

General Description. The recorder's tape loading procedure is simplified by a guide roller arm that locks out of the way when it is moved to its limit so that the tape takes a straight-line path across the heads, over the capstan, and over a tensioning arm as it goes to the take-up reel. The tensioning arm also serves as an automatic

shut-off switch in the event of tape breakage and when the tape runs out.

Two large illuminated meters indicate both recording and playback levels. The meters monitor the line outputs so that the playback indications vary with the setting of the playback level controls. Located above the meters is a red light that comes on whenever one or both channels is set to the RECORD mode. Below each meter is a standard jack for 600- to 50,000-ohm dynamic microphones.

Locking pushbutton switches control ac power, tape tensioning for 7-in. (17.8-cm) and 10½-in. (26.7-cm) tape reels, and tape speed. Other pushbuttons are labeled REC, PLAY, REWIND, FAST FORWARD, and STOP. For easy identification, the REC button is red, while the STOP button is larger than the others. Although the pushbuttons energize solenoids, they are designed to mechanically lock into position to permit the recorder to be set up in advance for recording. When line power is later applied by an external clock timer, the deck goes directly into its recording mode.

Five lever switches supplement the pushbuttons. Two place the channels individually into the recording mode when the REC button is pressed. This is a safety feature that prevents accidental tape erasure. It also serves as a means of recording on one channel while playing back through the other for echo and sound-on-sound (the latter requiring external patching).

Two more levers provide excep-

tional flexibility in adapting the recorder to any type of tape. They separately control recording bias and equalization. Each has positions for STD (standard) and LH (low noise/high-output) tape formulations. A table in the comprehensive instruction manual provided with the recorder suggests switch setting combinations for many popular tapes. Alternatively, optimum conditions can be determined by recording and listening.

The last lever switch connects the line outputs to either the source (input) signal or to the playback amplifier's outputs.


Concentric control knobs are provided for independently adjusting the recording levels in the two channels. One pair of controls is for the microphone inputs, while the other is for the line inputs. A third pair of concentric controls permits the playback level to be adjusted in each channel.

A stereo headphone jack is located on the recorder's front panel. The line inputs and outputs and a DIN socket that repeats the two are located on the rear of the recorder.

The recorder can be operated vertically or horizontally. It measures 17 in. high by 16 7/8 in. wide by 8 15/16 in. deep (43.2 × 42.9 × 22.9 cm) and weighs 49 lb (22.3 kg). It comes with walnut side panels, a 10½-in. metal reel, and two reel-hub adapters for professional-size reels with large center holes.

The retail price of the Pioneer Model RT-1011L stereo tape recorder is \$599.95.

Laboratory Measurements. Using Ampex test tapes, we found the playback equalization of the tape re-



order to be very accurate at both speeds. It was within ± 0.5 dB from 50 Hz to 15,000 Hz at $7\frac{1}{2}$ ips and within ± 0.8 dB from 50 Hz to 7500 Hz at $3\frac{3}{4}$ ips. (These are the frequency limits of the test tapes.)

We used 3M No. 207 tape for the balance of our tests. We measured the record/playback response with all four combinations of switch settings. Although the differences were slight, we concluded that the LH bias and STD equalization settings yielded the flattest overall frequency response.

Using a -20-dB recording level at $3\frac{3}{4}$ ips, the overall response was within ± 2.5 dB from 20 Hz to 13,500 Hz. At a 0-dB recording level, tape saturation (expected at this speed) caused a sharp drop-off in response beyond 7000 Hz. At $7\frac{1}{2}$ ips, the response at the -20 dB level was a very flat 2.5 dB from 20 Hz to 24,500 Hz. It was within ± 1 dB from 25 Hz to 21,000 Hz. Saturation was less of a problem at higher recording levels at $7\frac{1}{2}$ ips. Hence, the 0-dB response did not begin to fall off appreciably until we reached 12,000 Hz.

The line inputs required 43 mV for a 0-dB recording level. This produced a maximum playback output of 0.5 volt. The microphone sensitivity was 0.18 mV for 0 dB, while the amplifiers over-

loaded at 70 mV. This should be quite adequate for most recording situations.

A standard Dolby level tape played back with a full-scale +3-dB meter indication. The meters were somewhat slower in responding than are true VU meters. They indicated 65% of their steady-state values on 0.3-second tone bursts as compared to 99% for a true VU meter.

At a 0-dB recording level, the playback distortion was 1.0% at $7\frac{1}{2}$ ips and 1.2% at $3\frac{3}{4}$ ips. To reach the standard 3% reference distortion level, it was necessary to record at +12 dB (far off the meter scales) at either tape speed. Referred to this level, the unweighted noise was -62 dB at $7\frac{1}{2}$ ips. With IEC A weighting for better correlation with subjective effects, the noise was -70.5 dB. It is interesting to note that the S/N ratio at $3\frac{3}{4}$ ips was only 0.5 dB lower than at $7\frac{1}{2}$ ips. At maximum gain through the microphone inputs, the noise level increased by a negligible 3 dB.

The tape speeds were 0.4% fast at $7\frac{1}{2}$ ips and 0.4% at $3\frac{3}{4}$ ips. In fast forward and rewind, an 1800-ft (550-m) tape passed in 84 seconds. The unweighted rms flutter was 0.12% at $7\frac{1}{2}$ ips and 0.16% at $3\frac{3}{4}$ ips. To our sur-

prise, the flutter was reduced when the guide roller arm was locked in its loading position. (It normally plays an important part in reducing flutter.) The flutter measurements were then 0.08% and 0.12% respectively. Wow was the residual of the test tapes, measuring 0.01% to 0.02%.

The tape transport operated smoothly and appeared to be fool-proof. When going from either fast speed to PLAY, the tape came to a stop in about a second and paused for 2 or 3 seconds before going into play. The manual explains how the PAUSE control can be used to eliminate even this small delay if desired.

The headphone outputs had very good volume levels, even with 200-ohm high-impedance phones.

User Comment. Despite an ability to accommodate 10½-in. reels, this is very much a home tape recorder—an outstandingly fine one. In ease of loading and handling, it is about as simple and straightforward as any machine we have used. Its frequency response, distortion, and noise levels are among the best we have measured and would do justice in most respects to any professional recorder.


Due to the calibration of the deck's meters, it is eminently practical to maintain average music recording levels near the 0-dB mark. The meter pointers can be permitted to swing to full-scale and beyond on peaks without serious risk of over-recording.

Needless to say, the deck did a flawless job of recording from phonograph and tuner sources as well as of playing back commercially recorded tapes. At a surprisingly reasonable price, the Pioneer Model RT-1011L offers an impressive combination of high performance and operating versatility.

CIRCLE NO. 66 ON READER SERVICE CARD

HEWLETT-PACKARD MODEL 5381A FREQUENCY COUNTER

Seven-digit, laboratory-grade instrument operates to 80 MHz



WITH the increasing number of frequency sensitive circuits in

modern electronic systems—filters in stereo receivers and speaker cross-overs; SSB, RTTY, and SSTV filters in ham gear; digital systems in frequency synthesizers and calculators—a good frequency counter is an important item to have on the electronics workbench. A frequency counter is essential for checking the accuracy of dials on r-f and a-f signal generators. Though they are usually “within the ball park,” dial accuracy and resetabil-

ity are more critical when complex filters are involved since they don't work properly unless they are tuned “on the head.”

Although there are many reliable frequency counters, it is nice to see that one more big name (Hewlett-Packard) has entered the relatively low-cost market with their Model 5381A Frequency Counter (\$249).

This 7-digit (LED) laboratory-grade instrument has a frequency range of 10 Hz to 80 MHz (which means it can be used in the CB and ham ranges).

POPULAR ELECTRONICS

Sensitivity is 25 mV up to 20 MHz and 50 mV to 80 MHz. Accuracy is ± 1 count plus or minus the time-base accuracy. The time base uses a 1-MHz crystal that ages less than 0.3 ppm/month, ± 10 ppm from 0° to 40°C, and ± 1 ppm for a 10% line voltage variation.

Gate times can be selected manually and the resolution is 10 Hz at the 0.1-second gate time, 1 Hz at the 1-second gate time and 0.1 Hz at the 10-second gate time. The input impedance is 1 megohm shunted by 50 pF. Even at the most sensitive settings, the input to the counter will handle up to 200 volts (peaks ac plus dc) without harm.

Physically, the 5381A is quite pleasing in appearance, with a clean, uncluttered look. It is 3.5" high, 6.25"

wide, and 9.75" deep. It weighs 4.75 lb and has a built-in tilt stand.

User Comment. We had the opportunity of using the 5381A for several weeks on a variety of electronic equipment. After aligning a number of SCA traps and half a dozen or so filters in SSB and SSTV rigs, and checking a number of countdown circuits in digital projects, we really got to like the look of the seven-digit, easy-to-read display. In the MHz mode, reading the value down to three decimal places was easy, while in the Hz mode, resolution was 0.1 Hz.

The 5381A was in regular use in the shop even through the so-called "brownout" days when the power line had considerable variations. We did

not have to worry about the accurate settings on the various frequency generators since the excellent accuracy of the 5381A, even with 5% to 8% power reductions, enabled us to make critical adjustments.

A number of CB rigs have been checked and aligned with each other, after which, communication between units was improved due to the closer r-f alignment. The tone-alert accessories were also re-aligned so that the systems worked as they did when brand new.

For use at even higher frequencies, Hewlett-Packard also has a Model 5382A, a 225-MHz version, which costs \$450.

CIRCLE NO. 67 ON READER SERVICE CARD

TRAM DIAMOND 40 AM CB TRANSCEIVER

Has output circuit protection, SWR bridge and noise blanker



THE Tram Diamond 40 is a 23-channel crystal-synthesized mobile transceiver designed for AM operation on the Citizens Band. Among its special features are a microphone-gain control, final-amplifier protection circuitry, built-in SWR bridge, switchable noise blanker (in addition to the usual AM-type noise limiter), and a theft-deterrent mobile mounting bracket. An edgewise meter movement indicates relative signal strength on receive and relative output power or SWR on transmit. Also included are the usual adjustable squelch, Delta tune, public-address facility, and detachable microphone.

The transmitter operates at full legal power when the transceiver is connected to a nominal 13.8-volt dc power source. The power source can be either a positive- or a negative-ground system. Reverse-polarity protection is provided in either case. Stability of critical circuits under varying source voltages is assured by means of a built-in electronic voltage regulator.

The transceiver measures 8 in. by 6 $\frac{3}{4}$ in. by 2 $\frac{1}{2}$ in. (20.3 × 17.1 × 6.4 cm)

and weighs 6 pounds (2.7 kg). It retails for \$209.95.

The Receiver. According to our tests, the double-tuned receiver has excellent sensitivity and selectivity. The sensitivity measured 0.3 μ V for 10 dB (S + N)/N at 30% modulation and 1000 Hz. Adjacent-channel rejection was nominally 60 dB, while good communication quality was maintained with a 6-dB overall bandpass of 450 to 2400 Hz.

The bipolar r-f input amplifier is equipped with shunt diodes that serve as protection against overloads. The first conversion to a 10.0- to 10.04-MHz i-f is accomplished with the aid of a FET mixer. A bipolar-transistor mixer is used for the second conversion to a 455-kHz i-f. Selectivity is obtained by using a ceramic-filter bypass at the emitter of the second mixer and a ceramic filter at the input of the two-stage 455-kHz i-f section.

Application of dual agc voltages to the r-f stage, plus a single loop to the second mixer, provides an exceptionally flat output response level. Only a 4-dB output change occurred with a 20-dB input signal variation (at 1-10 μ V). A 3-dB change occurred with a 60-dB input change (at 10-10,000 μ V), and a 6-dB change with an input excursion of 80 dB (at 10-100,000 μ V). Approximately 50 μ V of input signal was needed to register S9 on the meter.

Other measurements indicated an 80-dB rejection of the primary image

and 70 and 90 dB i-f signal rejection at 10-10.04 MHz and 455 kHz, respectively. Spurious-signal rejection measured 55 dB minimum.

The noise blanker is a parallel-gate setup in which an IC is used at the front end and for gating the output of the second mixer. It can be turned on and off while simultaneously shifting in and out of the circuit a series-gate type a-f automatic noise limiter (anl). This noise-reducing setup proved to be extremely effective. It attenuated noise pulses of 30 to 40 dB above a 0.25 μ V signal down to near inaudibility in the presence of the signal. Its use drops the overall gain on weak signals by 4 to 6 dB, but the sensitivity-versus-S/N ratio is unaffected.

(A noise limiter is simply an audio-frequency signal peak clipper. Usually set to provide 100% modulation, it clips any signal level that exceeds that required for full modulation. The blanker, on the other hand, interrupts the r-f signal path momentarily during high-level noise pulses ahead of the selectivity circuits. A limiter is a simple device that operates well enough, but because of its clipping action can cause a-f signal distortion when clipping takes place. The blanker is more sophisticated, operating only for short noise-signal durations. Because it interrupts the signal path, it is not distortion producing.)

The push-pull class-B output amplifier is driven by an IC. In our tests, it delivered a 3.5-watt output at 5.5% distortion at the onset of clipping with a 1000-Hz test signal. With clipping, the output was 4.5 watts at 10% distortion. A thermistor-compensated squelch

was adjustable for thresholds of from 0.25 to 300 μ V.

Frequency Synthesizer. The crystal frequency synthesizer in the Diamond 40 employs six crystals in the 16.965- to 17.215-MHz range. Four of the crystals are cut for the 9.545- to 9.585-MHz range for the receiver and four are cut for the 10.0- to 10.04-MHz range for the transmitter. During transmit, the frequency tolerance held to within 440 Hz on any channel.

The Delta-tune circuit for the receiver is detuned at its center position, allowing the CB'er to "feel" when it is set to the middle of the channel.

The Transmitter. A triple-tuned bandpass-coupling network minimizes spurious responses from the

synthesizer mixer for the transmitter. The r-f power output amplifier employs a triple-tuned output-matching section. Collector-modulation of the driver stage and power amplifier is accomplished with the receiver's a-f setup plus a speech amplifier for the mike. (The latter is automatically switched in for this mode.)

With operation from a 13.8-volt source the r-f carrier output measured 4.5 watts. The distortion measured 9% at 100% modulation at 1000 Hz, and the frequency response was 270 to 2700 Hz at the 6-dB points. Adjacent-channel splatter, using a 2500-Hz standard EIA test tone, was -50 dB. Advancing the mike gain control for an additional 6-dB input-signal level (a practice the operating manual advises against) caused clipping and in-


creased the adjacent-channel splatter to -40 dB. With speech at normal modulating levels, the splatter was somewhat less. Setting the gain control to the point where the modulation starts to make the transmitter-on lamp blink slightly will usually hold the modulation within acceptably safe limits.

The fail-safe setup in the transmitter functions as follows: If the antenna line is badly mismatched to the transmitter, the resulting SWR will produce a large reflected voltage from the SWR bridge. This voltage is then used to disable the transmitter drive and thus protect the output transistor from damage under improper load conditions. This is a protective scheme we would like to see more of in transmitters.

CIRCLE NO. 68 ON READER SERVICE CARD

EDMUND SCIENTIFIC KIRLIAN ELECTROPHOTOGRAPHY KIT

Experimental photography provides fascinating results.



Electrophotography kit is set up on top of carton in which it is received.

PHOTOGRAPHY with electricity goes back to the 19th century. But it wasn't until Czechoslovakian researchers in 1939 published "electrophotographs" of leaves displaying strong corona patterns that some interest in the field emerged. It was the Russian scientists, the Kirlians, however, who truly developed the method in depth over the years, creating a wide range of patented apparatus for use in various fields.

Kirlian photography permits one to view brilliant emanations from organic or inorganic objects, made visible photographically only when the subject is placed in a field of high-frequency electrical currents. Using color film, the images are spectacular, revealing all colors, shades, patterns

and degrees of brilliance. Some observers describe it as a pulsing energy source. Scientific interest revolves around interpreting the corona or "bio-energy" force, which displays changes as a result of anger, illness, or fear in a human; lack of water in a plant; etc.

The Edmund Scientific Company's "Kirlian" Electrophotography Kit (No. 71,938) at \$49.95 uses the principle described, opening up a new world of photography for experimenters.

What It Is. Edmund's "Kirlian" photography kit consists of a variable low-voltage transformer; a high-voltage, high-frequency induction coil; metal electrode; glass plate; photo changing bag; and all neces-


sary lead wire. Calling it a kit is really a misnomer, as one does not truly "build" it. For example, the variable voltage step-down transformer and the high-frequency induction coil are fully assembled. What one does is set up the system from assembled components.

The high-quality step-down transformer, which is plugged into a 117-V ac source, provides output voltages that can be varied from three to eight volts. It includes an on-off switch. The high-frequency induction coil, which is fed the step-down transformer's low ac voltage, converts the voltage to a high-frequency, high-voltage output. High frequencies are developed by a set of vibrating contacts that interrupt the input at a rapid rate. Though output voltage from the induction coil is very high, the secondary's output current is quite low, being limited by core saturation. Nonetheless, great care should be taken when operating the device to avoid a shock.

Setting up the "Kirlian" kit is simple enough. Assuming a suitable darkened room for photographic developing purposes, here are the assembly steps: The cardboard shipping container is used as a support for setting up, folding one side's flaps inside and poking a pencil-size hole in the closed bottom to pass the high-voltage lead. Placing the high-voltage induction coil inside the carton, the high-voltage lead is pulled through the hole so that it protrudes from the carton. Now the carton is resting on its open side, the closed top acting as a platform with the electrode lead protruding.

The twin power leads of the induc-

tion coil are brought out from the bottom edge of the carton and plugged into the jacks of the variable low-voltage step-down transformer that is positioned outside the carton. Stripping about one inch of insulation from the high-voltage lead protruding from the carton top, the lead is bent 90 de-



Kirlian photograph of a begonia leaf showing the corona around the edge.

grees, with the excess wire pushed back into the carton. The square, metal electrode is then placed on top of the HV electrode lead and the perimeter of the metal is taped to the carton with masking tape. Next, the glass dielectric plate is centered atop the electrode and taped down.

If a suitable darkroom is not available, the photo changing bag should be used. Here, a hole is poked through the bottom to accommodate the high-voltage lead. The lead plus components on top are placed inside the bag, with the bag and its contents resting on the carton.

Completing setup, the following tests should be made before photographing an object. The stepdown transformer control should be set to its maximum, eight volts. Powering the device, you should hear "buzzing" of the interrupter contacts of the high-frequency coil. Next, the user's hand should be placed on the glass dielectric plate. The result should be a slight tingling sensation due to capacitive coupling of the high-frequency current. In the dark, a corona discharge should be seen from your hand; maybe, a crackling sound heard. (**Caution:** Do not operate equipment if the glass dielectric plate is damaged; limit skin area exposures to about one minute per day; use in a well ventilated area to prevent ozone buildup; use a pair of glass-lensed sunglasses when viewing the corona so that shortwave ultraviolet rays

won't cause eye irritation; do not operate in the presence of anyone with implanted devices such as heart pacers or around children or anyone not familiar with normal electrical safety precautions.)

Either 35-mm film or Polaroid 4 x 5 sheet film type 58, may be used. The film is placed directly on the glass dielectric plate, centering it over the metal electrode under the glass. The emulsion side is placed face up. An object to be photographed "Kirlian" style is placed directly on the film. For small objects, such as a coin, one's finger is placed on the object to provide a ground.

Comments. Setting up the Edmund Kirlian Photography Kit was an easy job. But in our haste we did not follow directions to tape down the glass dielectric. After using the system a while, the glass moved, which allowed an associate to be jolted by a discharge. With the glass covering the metal electrode, however, only a mild tingling sensation was felt. Following this, we taped down the hot lead and wiped the glass on both sides to be sure that moisture and dirt would not provide an electrical path.

We used black-and-white sheet film (ASA 32), taping it to the glass. However, 35-mm film, black-and-white or color, can be used. For the latter, the cassette should be taped close to the edge of the glass, securing the leader to a bulk-film reloading 35 mm cassette, which is taped to the opposite end of the glass. Using a 3/8" wood dowel as a handle, tapering the end to fit the bulk-film cassette, five clockwise turns of the spool (done in the dark) will withdraw sufficient unexposed film.

A user must experiment with exposure. Recommendations by the manufacturer are a fair guide, but best exposure varies due to humidity, film dampness, object density, etc. Typical exposures will be 12 to 15 seconds when the voltage control is set at eight. We started at six volts, feeling that there's more control over exposure if time is a bit longer.

There's no doubt that "Kirlian" photography is fun. You'll be amazed at the results, especially with color film. Edmund Scientific also has a \$9.95 starter kit and a more expensive "professional" kit. The former uses a piezoelectric demonstrator.

CIRCLE NO. 69 ON READER SERVICE CARD

FREE EICO CATALOG

346 Ways To Save On Instruments, Burglar Alarms, Automotive & Hobby Electronics!

The more you know about electronics, the more you'll appreciate EICO. We have a wide range of products for you to choose from, each designed to provide you with the most pleasure and quality performance for your money. The fact that more than 3 million EICO products are in use attests to their quality and performance.

"Build-it-Yourself" and save up to 50% with our famous electronic kits.

For latest EICO Catalog on Test Instruments, Automotive and Hobby Electronics, Eicocraft Project kits, Burglar-Fire Alarm Systems and name of nearest EICO Distributor, check reader service card or send 50¢ for fast first class mail service.

**EICO—283 Malta Street,
Brooklyn, N.Y. 11207**

*Leadership in creative electronics
since 1945.*





CIRCLE NO. 14 ON READER SERVICE CARD




learn by doing!

Perform more than 200 exciting experiments with CIE's fascinating **ELECTRONICS LABORATORY PROGRAM!**

Put theory... into practice



You get your own 161-piece electronics laboratory... with authentic electronic components used by industry!



You learn how to construct circuits and connect them with a soldering iron, which is part of your CIE laboratory equipment. This "hands on" experience is extremely valuable in applying what you learn.

Testing and troubleshooting are an important part of your learning experience. Included in your laboratory is a precision "multimeter" to diagnose electrical and electronic troubles quickly and accurately.

Modern space-age components like this IC (integrated circuit) are professional quality and can be used again and again in many of your projects. Lesson by lesson, piece by piece your knowledge grows!

Prepare now for a high income career in Electronics...the Science of the Seventies.

Electronic miracles are changing today's world with breathtaking speed.

And with this growth in electronics technology has come a brand new need... a demand for thousands of electronics technicians, trained in theory and practice to build the products, operate them and service them during the Seventies.

Don't just wait for something to "happen" in your present job. Get ready now for a career you'll really enjoy with a good income and plenty of opportunity for advancement.

Experience with experiments is your best teacher

"Hands on" experience helps to reinforce basic theory. When you learn by doing, you discover the "how" as well as the "why." You'll find out for yourself the right way as well as the wrong way to use electronic components. How to construct your own circuits, to discover trouble spots and learn how to fix them. And with CIE's special Auto-Programmed® Lessons, you learn faster and easier than you'd believe possible.

CIE's fascinating course, Electronics Technology with Laboratory, teaches you Electronics by making it work before your eyes. And you do it yourself, with your own hands.

Importance of FCC License and our Money-Back Warranty

Many important jobs require an FCC License and you must pass a Government licensing exam to get one.

But, a recent survey of 787 CIE graduates reveals that better than 9 out of 10 CIE grads passed the FCC License exam.

That's why we can offer this famous Money-Back Warranty: when

you complete our Laboratory Course, which provides FCC License preparation, you'll be able to pass your FCC exam or be entitled to a full refund of all tuition paid. This warranty is valid during the completion time allowed for your course.

You get your FCC License — or your money back!

You'll have high paying job opportunities

Electronics is still young and growing. In nearly every one of the new exciting fields of the Seventies you find electronics skills and knowledge are in demand. Computers and data processing. Air traffic control. Medical technology. Pollution control. Broadcasting and communications. With a CIE Diploma and an FCC License you can choose the career field you want... work for a big corporation, a small company or even go into business for yourself.

Here's how two outstanding CIE students carved out new careers: After his CIE training, Edward J. Dulaney, President of D & A Manu-

facturing, Inc., Scottsbluff, Nebraska, moved from TV repairman to lab technician to radio station chief engineer to manufacturer of electronic equipment with annual sales of more than \$500,000. Ed Dulaney says, "While studying with CIE, I learned the electronics theories that made my present business possible."

Marvin Hutchens, Woodbridge, Virginia, says: "I was surprised at the relevancy of the CIE course to actual working conditions. I'm now servicing two-way radio systems in the Greater Washington area. My earnings have increased \$3,000. I bought a new home for my family and I feel more financially secure than ever before."

Send now for 2 FREE BOOKS

Mail the reply card or coupon for our school catalog *plus* a special book on how to get your FCC License. For your convenience, we will try to have a representative call. If coupon is missing, write: Cleveland Institute of Electronics, Inc., 1776 E. 17th St., Cleveland, Ohio 44114. Do it now!



Approved
under
G. I. Bill

All CIE career courses are approved for educational benefits under the G. I. Bill. If you are a Veteran or in service now, check box for G. I. Bill information.

CIE Cleveland Institute of Electronics, Inc.
1776 East 17th Street, Cleveland, Ohio 44114
Accredited Member National Home Study Council

Please send me your two FREE books:

1. Your illustrated school catalog, "Succeed in Electronics."
2. Your book, "How to Get a Commercial FCC License."

I am especially interested in: Electronics Technology with Laboratory
 Electronics Technology Industrial Electronics
 Electronic Communications First Class FCC License
 Broadcast Engineering Electronics Engineering


Name _____ Age _____
(PLEASE PRINT)

Address _____

City _____ State _____ Zip _____

Veterans and Servicemen: Check here for G. I. Bill information.

PE-72



Solid State

By Lou Garner

LOOKING INTO THE CRYSTAL BALL

IF YOU'VE been a regular reader of this column, you know that I enjoy playing an annual guessing game with the electronics industry, predicting what new semiconductor products or technological advances will be introduced each year. For nearly two decades, my predictions have proven accurate better than 90% of the time. Because of this record, some have accused me of being an inspired prophet. Not so!

Actually, my annual predictions are based on an extrapolation of known developments in the industry. A "guesstimate" of where present trends are leading and what *could* be done with present technology. The method is similar to that used by science-fiction authors, but extended to the immediate, rather than the distant future.

Sometimes, my predictions have proven early by a year or so—simple examples of over-optimism and expectations that the industry would move faster in some areas than in others. Just as often, however, I've goofed in the opposite direction, predicting a new development which is announced *before* the column appears in print.

Let's see how I fared with the predictions made in January, 1974. As you may recall, I predicted:

- *A substantial drop in the prices of digital electronic watches from the present hundreds of dollars.* Score one for the OM! Surprising just about everyone and catching some manufacturers with their inventories up, National Semiconductor Corporation's Novus Consumer Products Division (1177 Kern Avenue, Sunnyvale, CA 94086) introduced a line of six digital electronic watches in early fall with a list price on one model of only \$125.00
- *Comparable reductions in the prices of digital electronic clocks.* Score another! At the same time that Novus announced its new low-priced electronic watches, it also announced a line of three digital electronic alarm clocks. The lowest priced model in the line lists at \$34.95!
- *LED's at prices comparable to those of miniature incandescent lamps in small quantities.* Another home run (bull's-eye, or whatever)! Recent advertisements in these pages offered type MV50's at six for a dollar, MV5024 equivalents at eight for a dollar, MV5222 equivalent green LED's at five for a buck, and Mini-Red LED's similar to the MV50 at a whopping ten for a dollar.
- *The introduction of control-function IC's as stock items.* Chalk up another score! Space limitations prevent our listing all of the various control IC's now available through major distributors, but two moderately priced types which should be of interest to serious experimenters are the

SGS-ATES L120 and L121 (SGS-ATES Semi-conductor Corp., 435 Newtonville Ave., Newtonville, MA 02160). Both devices are offered in 16-pin DIP's, both are priced at \$6.00 each in unit quantities, and both are intended for control functions in industrial and consumer applications. The L120 is a Triac/SCR phase control and the L121 a Triac/SCR burst control.

- *The development of one or more new solid-state transducers.* WOW! We really hit the jackpot on this one. Several manufacturers introduced new solid-state transducers during 1974, with the National Semiconductor Corporation now offering so many types that it recently published the industry's first catalog/handbook on pressure and temperature transducers. Entitled *Transducers: Pressure and Temperature*, the 160-page volume is much more than a mere listing of device specifications and options. It covers general transduction theory as well as the theory of operation of IC transducers in particular, and includes a number of useful tables plus a lengthy glossary of transduction-related terms. The book's applications section discusses automotive, medical, and audio uses, cable fault location, and even musical instruments, such as an electronic clarinet that comes on like a Sousaphone. Copies of the book are available without charge on letterhead request to the Marketing Services Department, National Semiconductor Corporation, 2900 Semiconductor Drive, Santa Clara, CA 95051.

- *The introduction of low-cost (about \$100) preprogrammed business calculators.* Another winner! Virtually all major calculator manufacturers have introduced inexpensive special purpose models. Casio, Inc. (Consumer Products Div., One World Trade Center, New York, N.Y. 10048), for example, offers one model, the Mini Root, which can supply square roots at the touch of a button and which provides automatic percentages for figuring mark-ups and discounts, at a list price of only \$54.95. The Cole-Parmer Instrument Co. (7425 North Oak Park Ave., Chicago, IL 60648) offers a metric conversion computer with full 5-function capability at a list price of only \$84.50. And these are but a small sampling of the models introduced during 1974!

- *Digital electronic test instruments, such as VOM's and frequency meters, at prices comparable to those of instruments using moving-coil meter movements.* Is there any doubt?

- *Development of a new semiconductor manufacturing technique or a refinement in current techniques which will*

improve quality, increase yield rates, and lower costs. I admit to "hedging" slightly on this prediction, offering two alternatives. However, fortunately for the OM, both options were fulfilled during 1974. Nearly every major semiconductor manufacturer was able to improve production techniques to the point of boosting product quality while, at the same time, lowering prices. In addition, several firms introduced new techniques. RCA, for example, introduced a technological advance for the semiconductor industry by combining MOS and bipolar devices—PMOS, bipolar and COS/MOS—on a single chip. The first device offered based on the new technology is the CA3130 operational amplifier.


Supplied in an 8-lead TO-5 package, the CA3130 features a gate-protected p-channel MOSFET input stage with an extremely high input impedance of 1.5×10^{12} ohms and a complementary-symmetry (COS/MOS) output stage capable of swinging the output signal voltage to within a mere 10 mV of either supply voltage terminal. In addition, the device offers a wide 15-MHz bandwidth and has a sink and source current capability of 20 mA. Short-circuit protected, the CA3130 has a broad range of applications, including ground-referenced single-supply and fast sample-hold amplifiers, long duration timers and monostables, high-input-impedance comparators and wide-band amplifiers, voltage-followers and regulators, peak detectors, single-supply full-wave precision rectifiers, and photo-diode sensor amplifiers.

- *The announcement of an unusual new solid-state device.* Another score! Not one, but several unusual new devices were introduced during 1974, many of which were discussed in these pages (including the CA3130). In making the original prediction, I suggested that one possibility was a special type of LED, speculating that it might have bilateral switch characteristics. In fact, a family of unusual new LED's was introduced by Litronix, Inc. (19000 Homestead Road, Vallco Park, Cupertino, CA 95014)—the RCL-200 series. These devices do not have switching characteristics as we speculated, but do incorporate a built-in bipolar current-regulator IC, permitting their use on dc supply voltages of from 4.5 to 12.5 volts without an external current limiting resistor.

Things to Come. Now for our predictions for 1975:

- *A price break-through on solid-state imaging devices,* possibly as a result of a new manufacturing technique. On a long term—several year—basis, I anticipate that video cameras will one day be as compact as home movie cameras and, perhaps, priced in a comparable range. [Next month's issue will fulfill Lou Garner's prophecy—Ed.]
- *The development of personal health monitors for patients subject to sudden attacks or seizures.* I envision a device no larger than a hearing aid which would alert the user in advance of a possible attack.
- *Digital electronic watches in the range of \$50 to \$60.* At the same time, I expect electronic watches in the hundred-dollar range to include a calendar feature, and, perhaps, even an integral alarm.
- *A digital MPG (miles-per-gallon) meter for automotive applications.* Such an instrument has been proposed but, as yet, is not in commercial production. I expect that it will be introduced first as a custom add-on accessory for retrofitting, but will be offered later as an optional accessory by one or more major manufacturers.
- *A low-cost electronic calculator designed specifically for the children's market.* As I visualize this product, it will

Find whatever circuit you need — instantly



THE LARGEST COLLECTION EVER

Over 3,600 circuit diagrams, complete with component values, in one handy volume, all clearly indexed and cross-referenced for speedy answers to your immediate design needs.

Just published

GUIDEBOOK OF ELECTRONIC CIRCUITS

By John Markus

1068 pages, \$24.50

Whatever your project—a hi-fi system, a burglar alarm, a solid state metal detector, an automatic timer—you name it, you'll find the circuit that best meets your needs in this, the largest single-volume collection of illustrated circuits ever to be published.

131 CHAPTERS, each devoted to a particular type of circuit, present 3,600 individual circuits, all with essential construction and adjustment details, design precautions and other practical data. The advantages and disadvantages of the various circuits are also given so you can decide quickly and easily what best meets your needs at the moment.

FAST, EASY USE. The Index has over 10,000 entries that list—and cross-reference—circuits by all their different names, by performance parameters, by applications, and by a host of other relevant categories. Perfect for super-fast looking or leisurely leafing.

SAMPLE CONTENTS quadrasonic circuits . . . tape recorder circuits . . . citizens band circuits . . . measuring circuits . . . filter circuits . . . amplifier circuits . . . code circuits . . . telephone circuits . . . signal generator circuits . . . flasher circuits . . . switching circuits . . . and thousands more!

And in case you missed Markus' two previous circuit books, use the coupon below to order examination copies. 92,000 already sold. Absolutely no duplication of circuits in these three volumes.

SOURCEBOOK OF ELECTRONIC CIRCUITS

By John Markus 888 pp. 8½" x 11" \$23.50

3,000 different circuits with values and exact source citations.

ELECTRONIC CIRCUITS MANUAL

By John Markus 892 pp. 8½" x 11" \$24.75

3,181 different circuits with values and exact source citations.

At your local bookstore or use coupon below for

FREE 10-DAY EXAMINATION

McGraw-Hill Book Company

1221 Avenue of the Americas, New York, N.Y. 10020



Please send me the book(s) I have checked below for a free 10-day examination. In that time I will either remit the price, plus local tax, postage, and handling, or return the book(s) with no further obligation. I understand that if I remit in full, plus local tax, with this order, McGraw-Hill pays postage and handling, and a 10-day return privilege still applies. This order subject to acceptance by McGraw-Hill.

- Guidebook of Electronic Circuits (040445-3) \$24.50
- Sourcebook of Electronic Circuits (040443-7) \$23.50
- Electronic Circuits Manual (040444-5) \$24.75

NAME _____

ADDRESS _____

CITY _____ STATE _____ ZIP _____

This offer good only in the U.S. and Canada. 23-A651-4003-3

be a basic 4-function calculator, but will be sold with a booklet slanted to teach a child not only to use the calculator, but to relate to standard mathematical techniques. It may also include several "game" features. The selling price probably will be well under \$20.00, based on present values.

- *An increasing variety of multipurpose consumer and office electronic products.* Typically, a combination alarm clock/calendar/calculator or a combination intercom/dictating machine.
- *The development of low-cost portable electronic games.* These would be based on calculator technology, but would be self-contained and, unlike Magnavox's *Odyssey*, would not require a TV set.
- *The development of a high-output or high-intensity LED.* A standard LED can be pulsed at currents many times higher than its average continuous rating (typically, 1 A for a 50 mA LED). If designed specifically for pulse applications, it may be possible to use a LED as a light source for special purpose photography (such as infrared microphotography), or even as a warning light.
- *The development although not necessarily the commercial production, of solid-state energy control centers for homes and offices.* With the increasing energy crisis, overall heating/cooling efficiency becomes more and more important. There are many ways in which solid-state circuitry and devices could be used to increase the efficiency of building heating/cooling systems. Typically, controls to monitor temperature and humidity, adjusting energy flow to maintain the proper levels without waste, controls to adjust blower speed to an optimum level for heating or cooling, and warning systems to alert the user to system inefficiencies (such as clogged filters).


That does it! Next January, we'll check our score.

Readers Circuit. If you've used an ohmmeter to any extent, you've probably been frustrated on several occasions when trying to interpolate a value at the "squeezed" end of the nonlinear scale found on most such instruments. A little frustration apparently was too much for reader M. J. Guenther (1169 Prairie Rd., Port Coquitlam, B.C., Canada), for he put on his thinking cap and devised a *linear scale* ohmmeter, which he proceeded to build and has been using for some time. His circuit is illustrated above.

Guenther's design features a pair of op amps, *IC1* and *IC2*, a reference voltage source, established by *R1*, various ranges, selected by *S1*, and a voltmeter readout. Test terminals *BP1* and *BP2* are provided for checking unknown resistance (*R_x*) values.

The reference voltage obtained from *R1*, stabilized by voltage follower *IC1*, is applied to *IC2*'s non-inverting input. At the same time, *IC2*'s output is coupled back to its inverting input through a voltage divider consisting of the unknown resistor, *R_x*, and a preselected range resistor, *R2* thru *R5*. The net result is that *IC2*'s output voltage is equal to the reference voltage plus the reference voltage times the ratio of the unknown and range resistors. When a voltmeter is used to check the potential difference between *IC2*'s noninverting input and its output, the initial reference voltage is cancelled, giving a reading which is *directly proportional* to the unknown resistor's value, the basic requirement for a linear scale.

Guenther used type 741C op amps in his model, but suggests that a single type 747 dual op amp or other 741 types may serve as well. The pin connections will vary, of



Linear scale ohmmeter uses two integrated circuits. When the circuit is properly balanced (via range switch and potentiometers), the meter reading is proportional to the unknown resistor.

course, depending on whether a DIP, TO, or minidip type device is used. Range selector *S1* is a single-pole, four-position rotary switch, *R1* a conventional linear potentiometer, and *R2*, *R3*, *R4* and *R5* are small trimmer pots, although full-sized controls may be used. A dual 18-volt regulated (or zener stabilized) dc power supply is required for operation, while the readout instrument should be a high-impedance VTVM or FET VM.

In his letter, Guenther writes that he assembled his model as part of a home-built FET voltmeter, providing a pushbutton switch between *IC2*'s output and the voltmeter's input to prevent an off-scale reading when the test terminals are open.

Except for establishing the readout voltmeter range, the reference voltage adjustment, *R1*, is completely noncritical, according to Guenther. He suggests calibrating the instrument by using mid-scale value precision (1% or better) resistors as test units to adjust each range potentiometer. In his model, Guenther used test resistors (as *R_x*) of 50, 500, 5,000, and 50,000 ohms, adjusting *R2*, *R3*, *R4*, and *R5*, respectively, to provide ranges of 0-100, 0-1,000, 0-10,000 and 0-100,000 ohms.

Device/Product News. If my discussion of field-effect transistors and their applications in last November's column stimulated your interest in these versatile devices, you may want to investigate recent offerings by Siliconix, Inc. (2201 Laurelwood Road, Santa Clara, CA 95054): these include a pair of vhf/uhf FET's and a new series of monolithic matched dual FET's.

The new vhf/uhf devices are basically the popular U310 n-channel high-frequency JFET supplied in epoxy TO-92 or ceramic OD-81 package configurations. These devices may be used as amplifiers, oscillators or mixers.

Siliconix's new dual JFET's, designated the E410 family, are epoxy-packaged n-channel devices intended for low- and medium-frequency small-signal differential amplifiers requiring matched gate-source voltage, high common-mode rejection ratio and low output conductance. The three units, types E410, E411 and E412, have a maximum G-G voltage of ± 40 V, a maximum G-D or G-S rating of -40 V, and a maximum gate current of 50 mA, with a total

package dissipation of 350 mW. Their common-mode rejection ratio is at least 70 dB.

In addition to its new FET's, Siliconix also has announced a new line of low-capacitance, high-impedance diodes intended for circuits requiring clipping, clamping, or over-voltage protection. Identified as the PAD family (pico-ampere diode), the new devices feature minute leakage currents ranging from 1 pA (PAD-1) to 100 pA (PAD-100) and extremely low interelectrode capacitances of 0.8 to 2.0 pF. The typical forward voltage drop for all units is 0.8 volts, the maximum forward current is 50 mA, and the total device dissipation 300 mW.

A new series of low-voltage varistors has been introduced by GE's Semiconductor Products Department (Bldg. 7, MD #49, Electronics Park, Syracuse, NY 13201). Performing somewhat like back-to-back zener diodes, these devices are ideal for protecting costly power transistors against transient voltage peaks when used in high-current inductive circuits, such as power supplies, inverters, converters, alarms, solenoid drivers, and audio amplifiers. Physically similar to disc ceramic capacitors, the new devices, designated the "ZA" series, are offered with ratings from 26 Volts dc, 20 Volts rms to 81 Volts dc, 60 Volts rms.

Motorola's Semiconductor Products Division (P.O. Box 20924, Phoenix, AZ 85036) has announced five new ruggedized r-f power transistors which should be of interest to hams and other communications buffs. Designed for 40-to-110-MHz mid-band international mobile radio applications, the new devices, types MRF 230 through MRF 234, are drivers and final amplifiers rated at 1.5, 3.5, 7.5, 15 and 25 watts output, respectively. Individual device gains are kept within 10 dB, while operation at VSWR's of up to 30:1, at any phase angle, can be tolerated. Unit prices range from \$2.30 for the MRF 230 to \$16.90 for the MRF 234.

Back East, RCA's Solid State Division (Box 3200, Somerville, NJ 08876) has introduced three new families of medium-power transistors and eight new general-purpose IC op amps.

The RCA29/SDH, RCA31/SDH and RCA41/SDH series are single-diffused homotaxial-base versions of the RCA29, RCA31, and RCA41 epitaxial base series, respectively, and are intended for a wide variety of switching and amplifier applications, such as series and shunt regulators and drivers and output stages of high-fidelity amplifiers. All the devices are supplied in JEDEC TO-22AB packages.

The RCA29/SDH series has typical turn-on and turn-off times of 2.3 μ s and 6 μ s, respectively, with a minimum beta of 15, measured at 1 ampere. V_{CE0} ratings range from 40 to 100 volts, depending on type. Featuring similar turn-on and turn-off times, but a minimum beta of 10, measured at 3 amperes, the RCA31/SDH series is offered with comparable V_{CE0} ratings. Finally, the RCA41/SDH series has typical turn-on and turn-off times of 3.2 μ s and 3.7 μ s, a minimum beta of 15 at 3 amperes, and voltage ratings of 40, 60, and 80 volts, depending on type.

Designated types CA107T, CA207T, CA307T, CA101T, CA101AT, CA201T, CA201AT and CA301AT, RCA's new IC op amps are direct replacements for standard industry types such as the 107, 207, 307, 101, 101A, 201, 201A and 301A in packages with similar terminal arrangements. These are dual-supply, high-input-impedance devices suitable for use in sample and hold, comparator, low-frequency waveform generator, long-interval timer, summing amplifier, and multivibrator applications. All eight types are furnished in 8-lead TO-5 style cases. ◆



New

The 1975 Engineering Manual & Purchasing Guide!

A "must" for
hobbyists, experimenters,
repairmen and technicians!
Thousands of hard-to-get electronic
parts and supplies. Order now!

Send \$1 to Allied Electronics
Dept. PE75, 401 East 8th St.
Fort Worth, Texas 76102

NAME _____

ADDRESS _____

CITY _____

STATE _____ ZIP _____

ALLIED ELECTRONICS
A DIVISION OF TANDY CORPORATION

**EVERYTHING YOU
WANTED TO KNOW
ABOUT CD IGNITION
SYSTEMS BUT DIDN'T
KNOW WHOM TO ASK.**

Send for FREE Tiger booklet (20 pages) which answers all your questions.

Name _____


Address _____

City _____

State _____ Zip _____

CLIP OUT THIS AD AND SEND TO—

TRI-STAR CORP.
P. O. Box 1727 Dept. E
Grand Junction, Colo. 81501
CIRCLE NO. 35 ON READER SERVICE CARD



CB Scene

By Len Buckwalter, K10DH

CB'S RED BARON

THERE we were at 1,000 feet, our wings at a crazy angle, the ground rushing up, when all of a sudden....

That's how it felt when I recently took a ride with one of the world's rarest birds—a flying CB reporter. His name is Morgan Kaolian, and he pilots a flivver of a plane on weekends for a local radio station located near the big boating areas of New York and Connecticut. Morgan's become something of a legend in these parts because he buzzes through the air for 18 hours every weekend to deliver half-hourly broadcasts of weather, fishing, sea conditions and road traffic, plus a few surprises. When I caught wind that Morgan depends heavily on CB, I decided to investigate, and maybe wangle a free hop in his flying machine.

Most people think flying reporters are in helicopters. Not so in this case. The plane is aviation's Model A; a two-place Cessna-150 that cruises about 90 mph, squeezes 15 miles from a gallon of gas and emits about as many decibels as an overweight wasp. A helicopter, on the other hand, noisily chomps the air, costs upwards of \$80 an hour to operate and is usually an expensive big-city bird. Morgan's mini-machine slashes the cost, and CB takes a share of the credit in the electronic department.

When I first spoke to Morgan on the phone he asked me how much I weighed. "One hundred ninety," I replied, wondering if the beefy figure would ground me. The reason he asked is that the plane is loaded to the gunnels with radio equipment and sprouts antennas like a flying porcupine. A two-way vhf link on 161.7 MHz carries his voice to the ground for retransmission over WICC, an AM station on 600 kHz. In the instrument panel there's an AM receiver so he can monitor the radio announcer for cues (but a closer look reveals it to be

a Volkswagen car radio!). Back in the minuscule baggage compartment is a typewriter-size vhf radio and the rest of the cabin is criss-crossed with the microphone cords and dangling headphones. With all this electronics aboard, no wonder Morgan was concerned about poundage.

The CB installation turned out to be something less than you'd find aboard a Boeing and more like a typical hobbyist's shack—a disarray that's understood only by the person who grew it. Since the Cessna's Lilliputian cabin was already bursting with instruments, the CB set was stuffed into a map pocket behind the backrest of a seat. The tiny knobs of the CB rig peeked out of the pouch like a baby kangaroo. The antenna installation, though, was an aircraft-type spike loaded for CB channel 13 and permanently mounted on the fuselage. Power for the rig was picked up through the aircraft's 12-volt dc buss in automobile fashion.

As we taxied out for take-off, the pilot clamped on headphones and handed me a pair. The "cans" were a comfortable set—until Morgan turned up the audio with a wicked smile. All the plane's radios feed into the phones simultaneously. Trying to catch the voices of the control tower, ground controller, CB receiver, vhf receiver and AM monitor would be


easy if I were a 5-channel tape recorder, but Morgan has been doing it for 8 years and easily sorts out the audio bedlam. As the 100 horses of the Cessna engine struggled to lift us into the air, I regretted the box of Oreos I had eaten the night before.

"Hey, here comes Eddie Rickenbacker!" It was the first CB voice of the flight. Morgan wheeled the plane around and headed toward a row of boats moored below, then lowered the plane's right wingtip to point out a single cabin cruiser. "That's the city police," he explained. "They monitor channel 13." Morgan exchanged pleasantries with the floating police and I was suddenly impressed at the good fortune of CB-equipped boatmen in the area. Maybe the U.S. Coast Guard won't hear CB distress calls, but there's a good chance they'll be intercepted by this channel 13 search-and-rescue team.

On an average weekend Morgan saves about two boats in distress. It's most efficient if the boat has a CB rig because its captain simply calls on channel 13 and may speak directly to the aerial angel-of-mercy himself. The range of a CB "air mobile" is very great with its lofty antenna, and talking distances of 50 miles are average (or double that when altitudes rise to three or four thousand feet). If a boat has no CB, Morgan may flit to a nearby boat and direct it to the crippled craft. When radio communications won't work he relies on more sensational feats. He'll drop written instructions in a sandwich bag or fly down low and *shout* directions. "Won't the noise drown out your voice?" I asked, with some doubt. "No, I kill the engine gliding down."

Morgan's uncanny skill at skimming the waves reaps another bonanza for CB'ers in the area. It's fish-spotting by air. To demonstrate, he lowered the Cessna's nose and

*Flying reporter
Morgan Kaolian uses
CB for much of his
aerial communications.*



asked me, "Do you have any aversion to low flying?" As the sea rapidly filled the windshield, I replied, "N-n-n-no." Blue fish, he explained, are visible as they break the surface, while bunkers expose themselves by thrashing about. Schools of fish below the surface look like dark holes. If he spots any giveaway signs, he'll report them to CB'ers below who call in. He's even been known to assist unlucky anglers with a helpful "Follow me."

The plane was now over land and flying parallel to a busy interstate thruway. Although he gives traffic reports on his regular AM broadcasts, I wanted to see the interaction between a CB-equipped plane and an automobile in motion. We raised a mobile who described himself as a yellow Chevy pickup truck with a load



CB set is carried in pocket behind seat.

of lumber travelling on Route 1. Seconds later, over a tangle of roads choked with homeward-bound vehicles, Morgan started circling. "Do you see it?", he asked me. All I could see was traffic—but it seemed he spotted everything below about an hour before I did.

"I see you!" peek-a-boomed the yellow Chevy. Finally, looking like a Tonka Toy, the teeny mobile with its matchstick load of lumber caught my eye. Morgan nudged me and, with a gleam in his eagle eye, said; "I estimate he's going 30 miles per hour." He squeezed the CB mike and fired the question.

"I'm going 30 miles per hour" answered the yellow pickup.

Morgan's ability to interface with road traffic has even rescued lost souls on the ground. One time on CB he heard; "Does anyone know where



Antenna, on plane's fuselage, is cut for channel 13.

the church is on Brooklawn Road? Some fellow is on his way to a wedding and he's lost."

"Where are you?" asked Morgan.

When the driver gave his location, Morgan swooped down like a hawk on a hapless hare.

"Is that you in the red Corvette?"

"That's me."

"Well just keep going, the church is straight ahead." Chalk up another save for CB. Morgan even saw the man going to the wedding!

The airport runway lights were already glowing as our Cessna touched down at the end of the day. Moments before we had listened on channel 10, with its CB-equipped truckers talking of roads and loads, or inviting each other to coffee at the next stop. I was surprised by one trucker who asked another driver if he had a "reefer." Morgan quickly explained that he meant a "refrigerated" truck. (He seems to know a little about everything, which may explain why he's also called the "Flying Mouth.") A twist of the selector to CB channel 9 brought remarkable silence, considering that it's often misused and our receiving range in the air was so great.

Morgan and his aerial antics via CB may serve as an inspiration for other pilots and communities. He's spreading tremendous goodwill for CB and proving the medium's worth in public service. The only precaution is that this sort of activity should be done only by experienced airmen. Morgan has a good luck charm (an "evil eye") pinned to the roof of his cabin, but his 8 years of accident-free reporting is also helped by 4,000 hours in the air and his experience as a military flier. Thanks to him we can say CB is on land, at sea—and in the air, too!

BIG DISCOUNTS

STEREO COMPONENTS

Largest selection of top name brands... try us and see...

It's worth a call
(301) 488-9600



6330 Frankford Ave.
Baltimore, Md. 21206

All mail answered within 24 hours

Phone Daily 9 AM to 9 PM
Saturday 9 AM to 4 PM
Phone (301) 488-9600

CIRCLE NO. 37 ON READER SERVICE CARD

FREE Olson Catalog

VALUE PACKED WITH THOUSANDS OF ELECTRONIC BARGAINS

We Will Send You The Next 7 Issues FREE! You'll Find The Best Of the Name Brands Plus Exclusive Olson Products at Low, Low Prices!

FREE Send Today

Olson Electronics Dept. 13
260 S. Forge St., Akron, Ohio 44327

Name _____


Street _____

City _____

State _____ Zip _____

Apt. No. _____

CIRCLE NO. 26 ON READER SERVICE CARD 93



Amateur Radio

By Herbert S. Brier, W9EGQ

RECEPTION AND THE ATMOSPHERE

HAVE you ever turned your receiver on and tuned across a band only to find that it was completely dead? This has probably happened to every amateur at one time or another. The first reaction is, "Oh, no! Something's gone wrong with my receiver!" In most cases, though, the fault lies not in the gear but in the propagation conditions affecting the band or bands. Why are bands so fickle and unpredictable?

The reasons for such occurrences lay in the interaction of the atmosphere, the sun, and radio waves. Let's consider the nature of these relationships, and how they affect radio communications.

Our atmosphere consists of four distinct regions—the troposphere, the stratosphere, the ionosphere, and the exosphere. Two of these strata directly contribute to the propagation of radio waves. The troposphere, which extends from 0 to 7 miles (0 to 11.2 km) can act as a waveguide for vhf and uhf signals, but has little effect on hf transmissions, as does the stratosphere, which extends from 7 to 25 miles (11.2 to 40 km). From 25 to approximately 250 miles (40 to 400 km) we find the ionosphere. In this region, rarified gas molecules and atoms can lose some of their electrons when excited by solar radiation. They dissociate into ions and free electrons, having positive and negative charges, respectively. Since the ions are thousands of times more massive than the electrons, they tend to be much less mobile. The electrons, however, tend to cluster in layers—the D layer, at 37-57 miles (60-92 km), the E layer, at 62-71 miles (110-115 km), the F₁ layer, at 99 miles (160 km), and the F₂ layer, found between 130 and 261 miles (210-420 km), depending on the season, the degree of ionization, and other variables. (See diagram shown at right.)

At night, the picture changes slightly. In the absence of the ionizing

solar energy, the D layer disappears after sunset. The E layer, which like the D reaches its maximum ionization level at noon, is at a minimum around midnight, when the free electrons recombine with the ions in the absence of solar radiation. The F₁ and F₂ layers merge into a single F layer after sunset, at a distance between those of the individual layers. Since the distribution of atoms at this height is so thin, the recombination process is much slower than in the D or E layers. Maximum ionization occurs at noon, and tapers off very gradually after that, remaining at a fairly high level through the night. A minimum is reached just before sunrise, at which point the ionization increases rapidly. Within an hour or two, it is back to daytime levels.


The final stratum, called the exosphere, is made up mostly of protons (hydrogen nuclei), and other charged particles that have been carried from the sun as part of the "solar wind." This region acts as a primary shield against the buffets of solar disturbances, but its effect on radio propagation is not great.

When the transmitter, at T, causes the antenna to radiate, the waves will leave the antenna at various angles. The one that travels straight up enters through the ionization layers and escapes into space, never to return.

Other waves leave the antenna at various angles from the tangent. Let us look at two of the signals. The wave with the higher departure angle, also called the wave angle or angle of radiation, first enters the D layer, where it is attenuated to a degree inversely proportional to its frequency. This is due to the fact that each time the signal collides with an electron or ion, part of its energy is lost in exciting the particle. Since the D layer is so dense, much attenuation takes place here. D-layer absorption is so great at low frequencies (5 MHz and below) that most of the signal doesn't make it through this layer. This is why 160 and 80 meters are usually "dead" during the daytime, but can open up at night.

If the signal is strong enough, and/or of high enough frequency, it will pass through the D layer with a good degree of strength. It will then travel up to the E layer. If the E ionization is high enough, and the wave angle is below a critical value, it will be reflected back toward the earth at about the same angle as the incident one. The wave will then pass through the D layer and reach the earth at a good distance from the transmitter.

If the E layer is not highly ionized, the wave will pass through it and reach one of the F layers, although its direction may be modified by partial bending. When the wave reaches the F layer, it will be reflected back toward earth if the wave angle is less than the critical value, and the frequency is below the "maximum usable frequency," or MUF. If the angle and/or frequency is greater than these values, the wave will pass into space. If the wave is sent back, it will pass through the other layers, and perhaps be sent back up by the E layer, and reflected down by the F layer at another point. The greatest range available from a "single hop"



Signals may be reflected by a layer of the ionosphere or escape into space. Range is determined by layer height and wave angle.



Rick, WB9EWQ, uses a Heathkit Electronic Keyer with HW-16 and HW-101 transceivers.

off the F layer is about 2500 miles (4000 km), and about 1250 miles (2000 km) from E-layer reflection.

The range available from this ionospheric reflection (also called sky-wave propagation) depends on the height of the layer(s), the degree of ionization, the angle of radiation and transmitter output power. In the diagram are two sky waves received at R_1 and R_2 . The angle of radiation of the wave reaching R_1 is much greater than that appearing at R_2 , and the range, as you can see, is much less. While it is possible to cover the distance to R_2 by more than one hop with a higher angle of radiation, the multi-hop signal will be weaker. Each time the wave hops, it loses about 6 dB or one "S" unit of strength. A two-hop signal would thus be 12 dB weaker than one which arrives after a single jump.

Amateurs who wish to work DX are interested in having antennas which radiate the larger portion of applied power at low angles. It has been found that the median wave angles for distant signals arriving at the receiver antenna on the hf bands are—28 MHz, 9 degrees; 21 MHz, 12-14 degrees; 14 MHz, 15 degrees; 7 MHz, 30 degrees; and 3.5 MHz, under 45 degrees. For horizontal dipoles, the following heights will give the desired radiation patterns: 28, 21 and 14 MHz—70 feet; 7 MHz—70 to 90 feet; and 3.5 MHz—90 to 140 feet. These heights are not absolute, since there are times when a lower or higher height would be more desirable.

Solar Influences. The degree of ionization is dependent on the activities of the sun, and the proximity of the earth to the sun. Sunspots are directly related to the levels of solar radiation. When there are many sun-

spots, the ionization level go up. There is an eleven year sunspot cycle. The last maximum occurred about 5 years ago, and we are now well into the waning period.

As we are well into the waning year of the current sunspot cycle, the 14-, 21-, and 28-MHz bands will normally be dead after dark for the next few months—except for unpredictable "short-skip" propagation conditions that can occur at any time on these bands. In addition, unless you have better-than-average 3.5- and 7-MHz antennas, signals on these frequencies become weak and hard to work as the evening progresses. If your antenna system is less than top-notch, you may hear operators with good 3.5- and 7-MHz antennas having no trouble working stations you can barely copy. Unless you can put up better low-frequency antennas, the easiest way to cope with the situation is to do more daytime operating. Although the 28-MHz band will often be dead, even in the daytime, the 3.5- to 21-MHz bands are and should continue to be useful for distances from 100 to several thousand miles from morning to night for the next few years.

You will also feel the effects of seasonal influences. Since the earth is closer to the sun in winter, F_2 ionization is more intense and higher MUF's are the rule. E-layer MUF's are generally lower in winter than in summer. The F_1 layer often disappears entirely during the winter, while it demonstrates MUF's of about 5 MHz in the summer. Night-time MUF's during the winter of the minima may drop to less than 4 MHz, as you will notice over the next few months.

If hf conditions deteriorate to the point where few contacts are possible, and you are looking for more QSO's, investigate the amateur vhf scene. If your attention has been focussed on the frequencies below 30 MHz, you cannot imagine the population explosion that has taken place on the amateur frequencies above 50 MHz—especially on the 144-148-MHz band. This is due to the wide availability of low-power vhf FM transceivers about the size of a big box of candy. When these units are used in conjunction with the vhf repeaters that have sprung up all over the country, ultra-reliable local communications have become an actuality for any operator within 25 or 30 miles of a repeater. Antennas need not be elaborate.

For further information on modern vhf operation, try the *VHF Handbook For Radio Amateurs*, by Herbert S. Brier, W9EGQ, and William I. Orr, W6SAI, Radio Publications, Inc., Wilton, Conn., or *FM and Repeaters*, ARRL, Newington, Conn. These books are available from most amateur equipment distributors.

In addition, do not hesitate to put out a couple of CQ's on an apparently dead band. One of the never-ending fascinations of amateur radio is its unpredictability. Also, the bands are often open to remote localities; and no one ever finds out because of the lack of activity at the right times and places. Evidence of this is furnished in practically every amateur contest.

News and Views. Send news, comments and pictures for possible publication in this column to: Amateur Radio, Herbert S. Brier, c/o POPULAR ELECTRONICS, One Park Ave., New York, NY 10016. ♦


SELECTED CONTESTS

ARRL VHF SS Contest; 2:00 P.M. local time, Saturday, Jan 7, to midnight, local time, Sunday, Jan. 8, 1975. Exchange: number of contest contact; "A" if your power input is less than 50 watts, "B" if it is 50 watts or more; your call letter; "check" last two digits of year licensed; ARRL section.

International DX Contest (ARRL); 0001 GMT, Feb. 4 to 2359 GMT, Feb. 5, and same time March 4 and 5; phone. Same times, Feb. 17 and 18, and March 17 and 18; CW. Send signal report and name of your state or province to each DX station worked. Receive signal report and power input. Score: add the number of different stations worked on each band and multiply by number of different countries worked.

Novice Roundup (ARRL); 0001 GMT, Feb. 4, to 2359 GMT, Feb. 12; operate a total of 30 hours. Novices can work anybody. Others work only novices. Exchange call letters, signal reports, and name of ARRL section. Novice scoring: add the number of different stations worked to the highest code speed recorded on your ARRL code-proficiency certificate. Multiply by the sum of sections and countries (other than ARRL sections) worked.

Complete literature and last-minute rule changes for each of these contests are available from ARRL, Newington, CT 06111, upon request accompanied by an addressed return envelope. Affix 8 cents postage for 3rd class return, 30 cents for first class. Send scores to same address.



Test Equipment Scene

By Leslie Solomon

REJUVENATING ELDERLY EQUIPMENT

ALTHOUGH most of us would like to purchase the best test gear that we can afford, we often have to compromise when it comes to cost. This means that many workbenches may have test gear whose specifications are not much better than the equipment being tested. In which case, we may be violating one of the basic rules of good engineering (and servicing): test gear must be at least one order of magnitude more accurate than the device being tested.

In many instances, a few more years can be squeezed out of the old gear simply by "swiping" partial or whole circuits out of magazines like *POPULAR ELECTRONICS*. Although most of us never build even a small percentage of the various circuits we see, we should take a close look at them with an eye for ideas to improve our present test equipment. Over the past few years, we have found many circuits that could be used to upgrade our test gear. The best part of this approach is the very low cost involved. (The few hours of bench time required to assemble the circuits are actually enjoyable when you're accomplishing something.)

Consider an elderly square-wave generator. This old timer might do very well at the lower audio frequencies; but as the frequency goes up, the output square wave probably resembles a badly warped triangle wave, at best. You can try to improve the high-frequency response by using the output to drive some digital logic, such as a flip-flop. This would work, but you will need a 5-volt power supply, and the frequency will be halved. A Schmitt trigger circuit would probably work fine. However, you might want to try the circuit shown at (A). It converts the battered old waveform into an impressive square wave with fast rise and fall times, reaching way out in frequency. The amplitude is also constant over the entire span. We built this

circuit right into the old generator, taking the required power from the internal supply. Any silicon switching transistors and diodes can be used.

The input potentiometer (*R1*) is adjusted for the best output waveform. Once set, this control requires no further calibration. Potentiometer *R2* is used to set the output amplitude. Diode *D1* protects the *Q2* emitter-base junction while diodes *D2* and *D3* prevent the clamp voltage from reverse biasing *Q1*. The input is driven from the maximum output of the old square-wave generator.



Another piece of gear that needed help was an old oscilloscope. Although it had the usual 1-megohm impedance, we found that it did load some of the newer circuits, especially where CMOS or bootstrapping were

used. To reduce this loading effect, we began using a 10:1 divider to increase the input impedance. But this, naturally, reduced the signal level available to the scope. We then had to crank the vertical gain way up, and sync sometimes became unstable. The circuit shown at (B) uses a form of bootstrapping to produce an input impedance somewhere around 1000 megohms. The circuit has unity gain, while the upper frequency equalization is determined by the setting of the 5000-ohm potentiometer.

The rise time is quite fast, and is estimated at about half a microsecond. The circuit was built on a narrow pc board and mounted within an old metal cigar tube container, as a probe. We have had no circuit loading problems.

Although we have shown only a couple of relatively simple ideas, there are many more. Where do these ideas come from? When we receive our quota of construction and ham magazines, besides reading those articles that interest us, we take a look at all the circuits, searching for ideas that may sometime be useful. Once we see something that could be of use, we clip it out and file it in a set of folders that are categorized by applications—audio, test gear, power supplies, etc. If you don't like the idea of cutting up

Circuit (A) can be used to improve the waveform on a square-wave generator; while (B) can be added to an oscilloscope to reduce input impedance.





**spend a
dime,
save a mint.**

Invest a dime and send for our catalog. We'll prove to you that you can have selection and convenience and still get a great price.

For an immediate FREE copy of our 64-page catalog, including pull-out "HiFi Primer" section, mail the coupon below to the location nearest you. Please print.



Midwest HiFi Wholesale

& MAIL ORDER DIVISION

1626 Ogden Ave. (US 34), Downers Grove, Ill. 60515
3309 E. Carpenter Frwy. (Texas 183), Irving, Tex. 75062

NAME

ADDRESS

CITY/STATE

ZIP

PE '6-01

CIRCLE NO. 25 ON READER SERVICE CARD

**LARGE-LARGE
DISCOUNTS
LOW - LOW
PRICES**

NATIONALLY
ADVERTISED STEREO EQUIPMENT
AT LOWEST PRICES!


TURNABLES * SPEAKERS * RECEIVERS
AMPLIFIERS * TAPE RECORDERS

WRITE FOR QUOTE ON
NATIONALLY ADVERTISED BRANDS OF STEREO
COMPONENTS. SATISFACTION
GUARANTEED!

Clifford's

HI-FI WHOLESALE
P. O. Box 809
Kankakee, Illinois 60901
(815)-939-7868

CIRCLE NO. 10 ON READER SERVICE CARD



Electronics Library

THE COMPLETE SHORTWAVE LISTENER'S HANDBOOK

by Hank Bennett

Here is a thorough, "hands-on" discussion of all the facets of shortwave radio listening. The author, using his own SWL experience, and that of others, answers questions such as "What SWL's hear," "Why they listen," and "How to get started," among others. The purpose of the book is to expose newcomers to the hobby, and to provide the experienced listener with valuable information to hunt down new stations.

The reader is introduced to the terminology and the hardware of the hobby, as well as propagation phenomena. Tips are given on the selection of a receiver, installation of an antenna, and times and frequencies for the reception of various parts of the world. The more exotic "sports" of FM and TV DX'ing are given special attention. Chapters are also devoted to amateur and CB radio, logbooks, reports, card swapping, and radio clubs.

Perhaps the most valuable aid in the book is a thorough list of foreign stations, by country, which includes exact frequencies and times of transmission. There is also included a discussion of the DX possibilities for the various frequency bands given the time of day, the season, and the point in the 11-year sunspot cycle. If you are entertaining notions of involving yourself in shortwave listening, there are few sources which can whet your appetite as well as this.

Published by Tab Books, Blue Ridge Summit, Pa. 17214. 281 pages. \$9.95 hardcover; \$6.95 paperback.

TRANSISTOR FUNDAMENTALS AND SERVICING

by B. Larson

The text covers the fundamentals of electronic devices to instruct readers in servicing circuits and systems in which they are found. Among the topics discussed are diodes, power supplies, bipolar transistors, bias circuits, ac amplifiers, FET's, IC's, oscillators, vacuum tubes, and the oscilloscope. Troubleshooting methods for each of these components and networks are given. Packaging and conventions for the various active elements are given. The emphasis in this book is on servicing, rather than design, with circuits reduced to the bare essentials and presented in a

highly simplified manner. Short-answer, multiple-choice questions and problems conclude each chapter.

Published by Prentice-Hall, Inc., Englewood Cliffs, NJ 07632. 462 pages. \$14.95, hard cover.

DIGITAL COMPUTERS: CIRCUITS AND CONCEPTS

by Deem, Muchow, and Zeppa

This is a sophisticated text for the technician, engineering student, or practicing engineer who wants to know how digital systems operate, and how such systems can be designed at minimum cost and parts count. Among the topics covered are number systems, Boolean algebra, logic symbology, code and data representation, Karnaugh maps, and simplification of logical expressions. Circuitry is not neglected. A thorough description of the RTL, DTL, TTL, ECL and CMOS logic families is included. Shift registers, combinational and sequential circuits, decoders and encoders, timing and control operations are analyzed and implemented to realize mathematical operations in the serial and parallel modes. Memories are given special consideration.

Published by Reston Publishing Company, Box 537, Reston, Va. 22090. 376 pages. \$14.95, clothbound.

MODERN RECORDING TECHNIQUES

by R. E. Runstein

This new work introduces the reader to the equipment and practices found in today's multitrack recording studios. In the first chapter, the acoustical, mechanical, electrical and magnetic means of transforming a live performance into a disc are outlined. Later chapters describe consoles, microphones, mixing, noise-reduction and monitoring. Finally, automated mixdown, disc cutting and pressing, and quadraphonic disc systems are presented.

Published by Howard W. Sams & Co., 4300 W 62nd Street, Indianapolis, Ind. 46206. 368 pages. \$9.95, paperback.

BASIC ELECTRICITY: A TEXT-LAB MANUAL (Fourth Edition)

by P. Zbar

Designed as a programmed text for an introductory electricity laboratory course, this volume presents basics of theory as well as practical applications of electricity. The reader is introduced to the passive circuit elements and their properties. Ohm's Law, series and parallel circuits, and voltage dividers are explained with actual circuits the reader can assemble. Kirchoff's Laws, Thevenin's and Norton's Theorems, and maximum power transfer are explored. Time constants, reactive circuits, impedance, and ac analysis conclude the course. If the book is used as a lab manual,

POPULAR ELECTRONICS

students who follow it should gain a basic working knowledge of electrical networks.

Published by McGraw-Hill Book Co., 1221 Avenue of the Americas, New York, NY 10020. \$6.95, soft cover.

VHF HANDBOOK FOR RADIO AMATEURS

by Herb Brier and William Orr

This guide to the "line-of-sight" frequencies begins with a short history of vhf exploration and experimentation. The most popular vhf bands include more than 13 MHz of spectrum space, more than four times the capacity of the hf bands. Since many amateurs are moving higher and higher to avoid congestion and QRM, this book will be a valuable reference work for newcomers to the high bands. Vhf propagation, caused by ionospheric reflection, moonbounce, tropospheric, auroral, and meteor effects is explained. The Oscar series of satellites is examined, and special emphasis is given to earth-station configurations. The very popular FM scene, including repeaters, mobile links, and tone-encoding controls is discussed. Design theory and construction practices for antennas, solid-state amplifiers and receiving circuits are explained and illustrated.

Published by Radio Publications, Box 149, Wilton, CT 06897. 336 pages. \$5.95, soft cover.

ELECTRONIC TEST EQUIPMENT —AND HOW TO USE IT

by J. Risse

A guide to the practical uses and proper operation of test equipment, this book gives principles, functions, and applications for tube and semiconductor testers, signal generators, capacitance and inductance bridges, and oscilloscopes. A list of key questions is included at the end of each chapter to allow the reader to check himself on new material as it is presented.

Published by Tab Books, Blue Ridge Summit, PA 17214. 204 pages. \$7.95, hard cover; \$4.95, paperback.

SOLID STATE IGNITION SYSTEMS

by R. Graf and G. Whalen

Fundamentals of the various electronic ignition systems that are becoming more and more popular in today's cars are discussed, and the conventional Kettering system is examined. Inductive-discharge and capacitive-discharge using solid-state components are covered by describing representative types offered by auto manufacturers and supply houses. Trigger methods, from breaker-point (with CDI) to magnetic "pointless" systems available as an option on most new American cars are included.

Published by Howard W. Sams & Co., 4300 W 62nd Street, Indianapolis, IN 46206. 136 pages. \$4.50.



Ampzilla is here...

Why spend \$750 to \$1200 dollars for an amplifier? The Great American Sound Company sells one with a full complementary series connected output for much less. In short AMPZILLA is here. In the September 1974 Popular Electronics, Hirsch-Houck Labs says "...solidly in the audio monster amplifier class

using 8 ohm loads . . . THD was less than 0.01% for all power levels . . . up to 200 watts . . . 'per channel' . . . all in


all we cannot imagine a less expensive way of obtaining several hundred watts.' Yes, we, your friendly GAS company, have the goods complete with a fan for ultra cool operation. Available with direct reading power meters in kit (\$375) or fully assembled (\$525). Also the same amp but no meters in kit (\$340) and assembled (\$475). Write us for complete specs, or read Popular Electronics, September 1974.

Available directly from

GAS
THE GREAT AMERICAN SOUND COMPANY, INC.


8780 Shoreham Drive, West Hollywood, California 90069
CIRCLE NO. 17 ON READER SERVICE CARD

Plug in...wire...modify...build...test



PAT. PENDING

without soldering
for as little as \$300




UNIQUE NEW
SNAP/LOCK DESIGN

New Continental Specialties QT SOCKETS® and BUS STRIPS offer expanded, flexible breadboarding without shorts or burnt fingers. Simply SNAP/LOCK together as many QTs as you need and you can test ICs, transistors, resistors, capacitors and more. Just plug-in, connect with solid #22 AWG hook-up wire — no soldering or patch cords needed! And QTs are totally reusable. 10 different sizes. Prices from \$3 for QT Sockets . . . from \$2 for Bus Strips.

Write or phone today for FREE Selection Guide, with applications, photos, drawings, specs, socket sizes and ordering information.



Continental Specialties Corporation
44 Kendall St., New Haven, CT 06509, 203/624-3103
CIRCLE NO. 11 ON READER SERVICE CARD



FREE
METRIC
TO
ENGLISH
SLIDE
RULE

Convert lengths, area, weight, volume instantly. Yours FREE with minimum \$5.00 order!

SAVE!

MONEY • TIME • FREIGHT

- ▶ QUALITY STEREO EQUIPMENT AT LOWEST PRICES.
- ▶ YOUR REQUEST FOR QUOTATION RETURNED SAME DAY.
- ▶ FACTORY SEALED CARTONS—GUARANTEED AND INSURED.
- ▶ SAVE ON NAME BRANDS LIKE:

A.D.C.	KLH
A.R.	SHURE
DYNACO	KOSS
SONY	FISHER

AND MORE THAN 50 OTHERS
BUY THE MODERN WAY
BY MAIL—FROM

illinois audio

Department 217S
12 East Delaware
Chicago, Illinois 60611
312-664-0020

CIRCLE NO. 18 ON READER SERVICE CARD

DIXIE SAVE ON Brand Name Audio Components BY MAIL

Write Today for Our FREE Audio Catalog

DIXIE is one of the oldest and largest audio component mail order houses in the country. Our prices on brand name components are actually LOWER than "Discounters". See our new catalog or call us for a price quote. Everything shipped factory-sealed with full manufacturer's warranty.




DIXIE HI-FIDELITY

5600 Second St., N. E., Washington, D. C. 20011
Phone: 1-202-635-4900

Please rush me your FREE Audio Catalog and complete information. I understand there is no obligation.

Name _____
Address _____
City _____
State _____ Zip _____ PE1




Hobby Scene

TONE CONTROL FOR BACKGROUND MUSIC

Q. I purchased a low-cost, general-utility, solid-state preamplifier and power amplifier to supply background music on my open patio. Now I find that I need some form of tone control to get a better sound. Is there a simple way to do this?


A. The tone control shown here can be inserted between the preamp and the power amplifier. You will have to get the power supply from the amplifier.



ONE-TRANSISTOR PUSH-PULL OUTPUT

Q. Is it possible to arrange a one-transistor push-pull output to drive two speakers—one in the emitter circuit and one in the collector?

A. This circuit can be used to drive a pair of 4-ohm speakers with a 1-watt output. Adjust the value of R1 to give the voltage drops shown across the speakers and the output stage.




A ONE-TIME SWEEP GENERATOR

Q. I need some kind of r-f sweep generator to align the i-f of a receiver I built. I have no need for a commercial unit—just something simple for this one-shot alignment.

A. You could try the basic circuit shown here. The UJT output goes to

the horizontal (external) input of the scope; and you can set the desired sweep rate with the potentiometers. The varactor can be any one in the range of about 50 pF. Use a Miller 9003 coil with a range of 380 to 1000 kHz for a 455-kHz i-f or a Miller 4505 (10 to 14 MHz) for a 10.7-MHz i-f. Other coils can be used for other ranges.



ELECTRONICS MARKET PLACE

NON-DISPLAY CLASSIFIED: COMMERCIAL RATE: For firms or individuals offering commercial products or services, \$1.80 per word (including name and address). Minimum order \$27.00. Payment must accompany copy except when ads are placed by accredited advertising agencies. Frequency discount; 5% for 6 months; 10% for 12 months paid in advance. **READER RATE:** For individuals with a personal item to buy or sell, \$1.10 per word (including name and address.) No minimum! Payment must accompany copy. **DISPLAY CLASSIFIED:** 1" by 1 column (2-1/4" wide), \$215.00. 2" by 1 column, \$430.00. 3" by 1 column, \$645.00. Advertiser to supply cuts. For frequency rates, please inquire.

GENERAL INFORMATION: First word in all ads set in bold caps at no extra charge. All copy subject to publisher's approval. All advertisers using Post Office Boxes in their addresses **MUST** supply publisher with permanent address and telephone number before ad can be run. Advertisements will not be published which advertise or promote the use of devices for the surreptitious interception of communications. Closing Date: 1st of the 2nd month preceding cover date (for example, March issue closes January 1st. Send order and remittance to **POPULAR ELECTRONICS**, One Park Avenue, New York, New York 10016, Attention: Hal Cymes.

FOR SALE

FREE! Bargain Catalog—I.C.'s, LED's, readouts, fiber optics, calculators parts & kits, semiconductors, parts. Poly Paks, Box 942PE, Lynnfield, Mass. 01940.

GOVERNMENT Surplus Receivers, Transmitters, Snooperscopes, Radios, Parts, Picture Catalog 25 cents. Meshna, Nahant, Mass. 01908.

LOWEST Prices Electronic Parts. Confidential Catalog Free. KNAPP, 3174 8th Ave. S.W., Largo, Fla. 33540.

ELECTRONIC PARTS, semiconductors, kits. FREE FLYER. Large catalog \$1.00 deposit. BIGELOW ELECTRONICS, Bluffton, Ohio 45817.

RADIO—T.V. Tubes—36 cents each. Send for free catalog. Cornell, 4213 University, San Diego, Calif. 92105.

AMATEUR SCIENTISTS, Electronics Experimenters, Science Fair Students... Construction plans—Complete, including drawings, schematics, parts list with prices and sources... Robot Man — Psychedelic shows — Lasers — Emotion/Lie Detector — Touch Tone Dial — Quadrasonic Adapter — Transistorized Ignition — Burglar Alarm — Sound Meter... over 60 items. Send 25 cents coin (no stamps) for complete catalog. Technical Writers Group, Box 5994, University Station, Raleigh, N.C. 27607.

METERS—Surplus, new, used, panel or portable. Send for list. Hanchett, Box 5577, Riverside, CA 92507.

WE SELL CONSTRUCTION PLANS, TELEPHONE: Answering Machine, Speakerphone, Carphone, Phonevision, Auto Dialer, Touch Button Dialer, Central Dial System. TELEVISION: \$35.00 Color Converter, Video Tape Recorder. \$25.00 Camera. HOBBYIST: Electron Microscope, 96 Hour Tape Music System, Ultrasonic Dishwasher, Radar-Oven, Plans \$4.95 each. NEW ITEM: \$75. Electronic Pocket Calculator, \$7.50. COURSES: Telephone Engineering \$39.50. Detective Electronics \$22.50. Integrated Circuit Engineering, \$49.50. NEW SUPER HOBBY CATALOG plus year's subscription to Electronic News Letter AIRMAILED \$1.00. Don Britton Enterprises, 6200 Wilshire Blvd., Los Angeles, Calif. 90048.

CONSTRUCTION PLANS: Laser...\$2.00. Rocket Tracking Transmitter...\$2.00. Space Monitor-Missile Tracker...\$2.00. Free Catalog. Electro-Research, P.O. Box 20285, Ferndale, Michigan 48220.

CD IGNITIONS, VHF/UHF monitors, crystals, CB radios, Southland, Box 3591-B, Baytown, Texas 77520.

PAIA HAS... modular SYNTHESIZER KITS

demo record \$1.00 free catalog

PAIA ELECTRONICS, INC.
BOX P14359, OKLAHOMA CITY, OK 73114

BUGGED??? New locator finds them fast. Write, Clifton, 11500-L N.W. 7th Avenue, Miami, Florida 33168.

TELEPHONE "BUGGED"? Countermeasures Brochure \$1.00. Negeye, Drawer 547, Pennsboro, W. VA 26415.

HEAR POLICE/FIRE Dispatchers! Catalog shows exclusive directories of "confidential" channels, receivers. Send 10 cent stamp. Communications, Box 56-PE, Commack, N.Y. 11725.

CONVERT any television to sensitive, big-screen oscilloscope. Only minor changes required. No electronic experience necessary. Illustrated parts. \$2.00. Sanders, Dept. A-33, Box 92102, Houston, Texas 77010.

YOU WILL SAVE BIG MONEY! Surplus, Clearouts, Bankruptcy, Inventory, Deals. Catalog \$1 (redeemable). ETCOA Electronics, Box 741, Montreal, H3C 2V2. U.S. Inquiries.

BURGLAR-FIRE alarm supplies and information. Free catalog. Protecto Alarm Sales, Box 357-G, Birch Run, Michigan 48415.

COMPLETE CONSTRUCTION PLANS—TELEPHONE: Answering Device, Automatic Dialer, "Black Boxes", Call Diverter, Call Limiter, Conference Bridge, Central Dial Exchange, Melodic Ringing, Recorder-Actuator, Remote Control, Schematics, Speakerphone, Teletink Burglar Alarm, Voice Scrambler, \$3.00 each. ELECTRONIC: Biofeedback Conditioner, Horticulture Stimulator, Multifrequency Encoder Network (Speeds telephone calling 100%). \$5.00 each. ONE YEAR SUBSCRIPTION: Telephone-Electronics Newline \$3.00. Super illustrated 16 page catalog of plans, many more, 50 cents. All of the construction plans above, \$19.95. TELETRONICS COMPANY OF AMERICA, P.O. Box 3486, Hollywood, California 90028. USA.

PRINTED CIRCUIT TECHNIQUES for the Hobbyist. Booklet: \$2.00. Trumbull, 833 Balra Drive, El Cerrito, Calif. 94530.

INTERNATIONAL ELECTRONICS UNLIMITED

TTL			
7400	\$.19	7474	\$.43
7401	.19	7475	.75
7402	.19	7476	.47
7403	.19	7483	1.11
7404	.22	7486	.44
7405	.22	7489	2.75
7406	.39	7490	.76
7407	.39	7491	1.29
7408	.25	7492	.79
7409	.25	7493	.79
7410	.19	7494	.89
7413	.79	7495	.89
7416	.39	7496	.89
7418	.39	74107	.49
7417	.39	74121	.57
7420	.19	74123	.99
7423	.35	74125	.69
7425	.39	74126	.79
7426	.29	74141	1.23
7427	.35	74145	1.15
7430	.22	74150	1.09
7432	.29	74151	.89
7437	.45	74153	1.29
7438	.39	74154	1.59
7440	.19	74157	1.29
7441	1.09	74161	1.39
7442	.99	74163	1.59
7443	.99	74164	1.89
7444	1.10	74165	1.99
7445	1.10	74166	1.85
7446	1.15	74173	1.65
7447	1.15	74177	.99
7448	1.15	74180	1.09
7450	.24	74181	3.65
7453	.27	74182	.89
7454	.39	74190	1.59
7460	.19	74193	1.39
7464	.39	74194	1.39
7465	.39	74195	.99
7472	.36	74198	2.19
7473	.43	74199	2.19

Data sheets supplied on request
Add \$.50 for items less than \$1.00

LINEAR CIRCUITS			
301	Hi perf. op amp	mDIP	\$.32
307	Op amp	mDIP	.35
308	Micro-pwr op amp	mDIP	1.10
309K	5V reg 1A	TO-3	1.65
311	Hi perf. V comp	mDIP	1.05
319	Hi-speed dual comp	DIP	1.29
324	Quad op amp	DIP	1.95
339	Quad comp	DIP	1.69
340T	Pos V reg (5V, 6V, 8V, 12V, 15V, 18V, 24V)	TO-220	1.95
380	2V audio amp	DIP	1.49
380-8	.6w audio amp	mDIP	.89
381	Lo noise dual preamp	DIP	1.79
550	Prec. V reg	DIP	.79
555	Timer	mDIP	.99
560	Phase locked loop	DIP	2.75
565	Phase locked loop	DIP	2.65
709	Op amp	DIP	.29
723	Volt reg.	DIP	.69
741	Comp. op amp	mDIP	.35
747	Dual 741	DIP	.39
748	Freq adj 741	mDIP	.69
1458	Dual Comp op amp	mDIP	.69
3900	Quad amp	DIP	.65
3905	Pres. timer	DIP	.65
8038	Function gen.	DIP	5.95
75451	Dual prl. driver	mDIP	.39
75452	Dual prl. driver	mDIP	.39
75453	Dual prl. driver	mDIP	.39
75491	Quad seq driver	DIP	.79
75492	Hex dig. driver	DIP	.89

Data sheets supplied on request
Add \$.50 for items less than \$1.00

JANUARY SPECIALS

7406	Hex inverter	\$.35
7440	Dual 4 input buffer	.17
7454	And-or-invert gate	.23
7474	Dual D flip flop	.29
74125	T.S. quad buffer	.55
74175	Quad D flip flop	1.80
8230	T.S. 2.4 line mux	1.95
8830	Dual line driver	1.75
8836	Quad 2 input rec.	.25
301	Hi perf. amp	.19
380	2 w audio amp	1.35
3900	Quad amp	.39
1103	1024-bit dyn. Ram	2.95
5316	6 dig. alarm clock	6.95

ALL DUAL-IN-LINE

MEMORIES

1101	256 bit RAM MOS	\$1.75
1103	1024 bit RAM MOS	4.95
5260	1024 bit RAM low power	3.95
7489	64 bit RAM TTL	2.75
8223	Programmable ROM	4.95
74200	256 bit Ram-tri-state	7.95

LED'S AND OPTO ISOLATORS

MV10B	Red TO 18	\$.25 ea.
MV50	Axial leads	.20
MV5020	Jumbo visible red	.33
ME4	Infra red diff. dome	.60
MAN1	Red 7 seg. .270"	2.50
MAN2	Red alpha num. .32"	4.95
MAN3A	Red 7 seg. .127"	.79
MAN3M	Red 7 seg. .127" claw	1.15
MAN4	Red 7 seg. .190"	2.15
MAN5	Green 7 seg. .270"	2.95
MAN7	Yellow 7 seg. .270"	3.95
MAN8	60° high dir. view	4.65
MAN66	60° high dir. view	4.65
DL707	Red 7 seg. .3"	2.15
MCD2	Opto-iso diodes	1.09
MCT2	Opto-iso transistor	.69

CMOS

74C00	\$.39	74C42	2.15
74C04	.75	74C76	1.70
74C08	.75	74C173	2.90
74C10	.65	80C97	1.50

4000 SERIES RCA-EQUIV.

CD4001	\$.55	CD4017	2.95
CD4009	.85	CD4019	1.35
CD4010	.85	CD4022	2.75
CD4011	.55	CD4023	.55
CD4012	.55	CD4025	.55
CD4013	1.20	CD4027	1.35
CD4016	1.25	CD4035	2.85

ON ORDERS OVER \$25.00 DEDUCT 10%

All items are new, unused surplus parts - tested functional. Satisfaction is guaranteed. Shipment will be made via first class mail - postage paid - in U.S., Canada and Mexico within three days from receipt of order. Minimum order - \$5.00. California residents add sales tax.

INTERNATIONAL ELECTRONICS UNLIMITED
P.O. BOX 1708 MONTEREY, CALIF. 93940 USA

(408) 659-4773

LOOKING FOR A NEW CHALLENGE?

... then build a TV camera!

ONLY SOLID-STATE CAMERA AVAILABLE IN KIT FORM OR FACTORY ASSEMBLED. COMPLETE KIT WITH VIDEO TUBE ONLY \$166.00. POSTPAID DELIVERY ANYWHERE IN U.S.A., CANADA AND MEXICO. OPTIONAL AUDIO SUBCARRIER \$18.95. WRITE OR PHONE NOW FOR COMPLETE CATALOG OF KITS, PARTS AND PLANS. Dial 402-987-3771.

1301 BROADWAY ATV Research DAKOTA CITY, NEBR. 68731

DIGITAL ELECTRONICS: Complete schematics, parts lists, theories - Discrete Component Digital Clock, \$3.00 - Sound Sensitive Switch, \$1.50. Increase technical competence, hobby skills - Complete Course in Digital Electronics is highly effective, \$10.00. Free literature. DYNASIGN, Box 60A7, Wayland, Mass. 01778.

MECHANICAL, ELECTRONIC devices catalog 10 cents. Greatest Values - Lowest Prices. Fertik's, 5249 "D", Philadelphia, Pa. 19120.

SOUND SYNTHESIZER KITS—Surf \$12.95, Wind \$12.95, Wind Chimes \$17.95, Electronic Songbird \$6.95, Musical Accessories, many more. Catalog free. PAIA Electronics, Box J14359, Oklahoma City, OK 73114.

DISCOUNT PRICES

B & K, SENCORE, LEADER and RCA Test Equipment
RAYTHEON, ICC/MULLARD Tubes
TELEMATIC Test Jigs

Free Catalog

FORDHAM RADIO SUPPLY CO., INC.
558 Morris Ave. • Bronx, N.Y. 10451

FREE CATALOG. Parts, circuit boards for POPULAR ELECTRONICS projects. PAIA Electronics, Box C14359, Oklahoma City, OK 73114.

CRYSTALS, Scanners, \$3.88, include make and frequency. G Enterprises, P.O. Box 461PC, Clearfield, UT 84105.

FREE CATALOG. Kits, Components, audio equipment. Electronic Supply Pacs, Box 175, Floral Park N.Y. 11001.

PRACTICAL Applications of Digital IC's. 100's of tips, circuits, projects, on TTL. 443pp \$19.95. Money Back Guarantee. GEA, P.O. Box 285, Northfield, Ohio 44067.

ALPHA/THETA BRAINWAVE biofeedback instruments. Analog instruments from \$125; digital processing systems from \$225. BioScan, Box 14168-E, Houston, Texas 77021.

SURPRISE! Build inexpensively, the most Unusual Test Instruments. Futuristic Gadgets using Numerical Readouts! Catalogue Free! GBS, Box 100A, Green Bank, West Virginia 24944.

ELECTRONIC ORGAN KITS, KEYBOARDS and many components. Independent and divider tone generators. All diode keying. I.C. circuitry. Supplement your Artisan Organ, 35 cents for catalog. DEVTRONIX ORGAN PRODUCTS, Dept. C., 5872 Amapola Dr., San Jose, Calif. 95129.

ELECTRONIC IGNITION: Capacitor, transistor, pointless. Auburn sparkplugs. Information 10 cents. Anderson Engineering, Epsom, N.H. 03234.

WHOLESALE Scanners, CB, Crystals, Directories, SSB/AM, Catalog 25 cents. G—Enterprises, Box 461P, Clearfield, Utah 84105.

CALCULATOR OWNERS: Use Your +x- calculator to compute square roots, trigonometric functions, logarithms, and more! Quickly, Accurately, Easily! Send today for the First and Best Calculator Manual... now in use throughout the world... still only \$2.00 Postpaid with Unconditional Money-Back Guarantee! Mallmann Optics and Electronics, Dept. 23A, 836 South 113, West Allis, Wisconsin 53214.

FREE 1975 Electronics Catalog. McCord Electronics, Box 276-N, Sylvania, Ohio 43560.

AUTORANGING DMM, deluxe VOM's, logic probes and more. Lowest prices. Free catalog. Electro Industries, 4201 Irving Park, Chicago, Illinois 60641.

ARE YOU PREPARED? 10,000 cubic foot, pull ring ignited emergency smoke grenades are now available! 3 for \$7.50, 9 for \$20.00. Postpaid. Pacific Aero Supply, Box 601, Malibu, Calif. 90265.

PYROTECHNICAL chemicals, casings, tools, supplies, fuse. Price List 50 cents. Westech, Logan, Utah 84321.

TELEPHONES UNLIMITED, equipment, supplies. Catalog 50 cents. Box 1654E, Costa Mesa, Calif. 92626.

CARBON FILM RESISTORS. Brand new as low as 2-1/4 cents. FREE samples and specifications. COMPONENTS CENTER—PE, Box 134, New York, NY 10038.

7,000 SEMICONDUCTORS. 100's Electronic Circuit Kits, Technical Reports, Energy Conservation, Computers. Cat. 50 cents. E/S Lab, Box 738, College Park, MD 20740.

UNSCRAMBLERS: Fits any scanner or monitor, easily adjusts to all scrambled frequencies. Only 4" square \$29.95, fully guaranteed. Dealer inquiries welcomed. PDQ Electronics, Box 841, North Little Rock, Arkansas 72115.


LEARN DESIGN TECHNIQUES. Electronics Monthly Newsletter. Digital, linear construction projects, design theory and procedures. Sample copy \$1.00. Valley West, Box 2119-B, Sunnyvale, California 94087.

BURGLAR—FIRE ALARM components, hardware. Free Catalog—Information. Salmar, 133 S. W. 57 Ave., Miami, Florida 33144.

WE SELL MONEY MAKING CONSTRUCTION MANUALS!!! — Reclaim GOLD, SILVER for EXCELLENT full or part time money!!! — PLUS, we buy scrap gold & silver — ALSO, we sell 99.999% pure SILVER BARS!!! — Color Catalog 25 cents — Airmailed 50 cents — Creative Products, Dept. PE-175, 4913 Northridge NE, Albuquerque, New Mexico 87111.

DIGITAL IC Manual—Latest Edition—1500 types by types/diagram number \$3.95. 32—function digital computer kit—IC, transistors, instructions, \$14.00. IC applications manual—numerous circuits—Analog/Digital, \$3.95. Electronetics, P. O. Box 127, Hopedale, Mass. 01747.

ALPHA/THETA BRAINWAVE



BIOFEEDBACK INSTRUMENTS The only biofeedback instruments available with powerful built-in digital processing. AlphaScan 400 shown at \$225; others from \$125—\$795. Write for free literature including our booklet, "Some

Technical Considerations for EEG Biofeedback Instrumentations." BioScan Corporation, Box 14168-E, Houston, Tex. 77021 "ELECTRONIC INSTRUMENTATION FOR THE LIFE SCIENCES"

ELECTRONIC COMPONENTS—all kinds, send for free catalog. Epic, Box 20152A, Minneapolis, Minn. 55420.

QUALITY military and industrial surplus electronics. Send 25 cents for last 3 of our monthly picture flyers. US only. Startronics, Box 17127, Portland, OR 97217.

COMPUTER SCHEMATICS. 256 bits, expandable to several K. Many other schematics available. SP Electronics, Box 5E, Prospect Heights, Illinois 60070.

FREQUENCY COUNTER for under \$75.00; provisions to 200MHz, Nixie or LED readout 8 digit; uses standard IC's, complete details \$3.00, postpaid. East Coast Electronics, 50 Scott, Hamburg, New York 14075.

COMPUTER countless uses. 8 bit word, powerful instruction set. Complete \$225. Brochure 10 cents. RAECO, Box 14, Readville, Mass. 02137.

TEN Batteries 1-1/2V. Send \$2 for batteries and price list. Electronics, Box 33071, District Hts., MD 20028.

ELECTRONIC SURPLUS 1974 Catalog 25 cents. Refundable w/order. Atlantis, Box 12654P, Tucson, AZ 85711.

SUBSCRIBE NOW!

LEARN THE SECRETS OF YOUR TELEPHONE

Telephone Electronics Line®

FACTS NEVER PUBLISHED FOR THE PUBLIC

A UNIQUE REFERENCE GUIDE TO THE INSIDE STORY

FROM THE HOBBIST TO THE TECHNICIAN

Current News Items • Plans • Illustrations

Stories • History • Comics • Facts • Games

Code Numbers • Projects • And Many More

— One year subscription only \$ 3.00 —

TELETRONICS COMPANY OF AMERICA P.O. BOX 3485 LOS ANGELES, CA. 90028

DESCRAMBLERS several models that work with all scanners and tunable receivers. Automatic Activated Phone Patch, Proximity Alarm Kit, Telephone Scrambler Kit, Tone Signaling Kits, Jinni-1 Semiconductor Tester with LED readout indicators, other kits, parts, plans. Catalog 25 cents, KRYSTAL KITS, Box 445, Bentonville, Ark. 72712.

ELECTRONICS parts, low prices, free flyer: DARTEK ELECTRONICS, Box 2460, Dartmouth, Nova Scotia, Canada. U.S. Inquiries.

WHOLESALE BURGLAR ALARM supplies. Catalog \$1.00 (refundable). Ellin, 161W Bonad, Chestnut Hill, Mass. 02167.

ELECTROENCEPHALOPHONE/Brain activity control. Z.J. Daszewski Lab., 361 Garretton Ave., Perth Amboy, N.J. 08861. Tel: (201) 826-3061. Please send 25 cents or self-addressed envelope with inquiry.

7400	\$.18	TTL	74182	.89
7401	.19		74184	2.30
7402	.19	7475	74185	2.19
7403	.19	7476	74187	6.00
7404	.21	7480	74190	1.50
7405	.22	7482	74191	1.50
7406	.39	7483	74192	1.35
7407	.39	7485	74193	1.35
7408	.25	7486	74194	1.39
7409	.25	7488	74195	.95
7410	.19	7489	74196	1.25
7411	.29	7490	74197	.99
7412	.40	7491	74198	2.19
7413	.79	7492	74199	2.19
7416	.39	7493	74200	6.95
7417	.39	7494		
7418	.25	7495		
7420	.19	7496	CD4001	\$.55
7421	.35	74100	1.50	CD4002 .55
7423	.35	74107	.47	CD4007 1.25
7425	.39	74121	.55	CD4009 .85
7426	.29	74122	.47	CD4010 .65
7427	.35	74123	.99	CD4011 .55
7429	.40	74125	.60	CD4012 .55
7430	.22	74126	.79	CD4013 1.10
7432	.29	74141	1.15	CD4016 1.25
7437	.45	74145	1.10	CD4017 2.50
7438	.39	74150	1.05	CD4019 1.25
7439	.50	74151	.89	CD4020 1.50
7440	.19	74153	1.29	CD4023 .55
7441	1.08	74154	1.25	CD4025 .55
7442	.99	74155	1.19	CD4027 1.25
7443	.99	74156	1.29	CD4030 .60
7444	1.10	74157	1.29	MC3022 2.00
7445	1.10	74160	1.65	74C00 .35
7446	1.10	74161	1.39	74C04 .69
7447	1.10	74163	1.59	74C20 .65
7448	1.10	74164	1.89	74C173 2.50
7450	.24	74165	1.89	
7451	.27	74166	1.65	
7453	.27	74170	3.00	
7454	.39	74173	1.65	
7459	.25	74174	1.85	
7460	.19	74175	1.85	
7470	.45	74176	.89	
7472	.36	74177	.89	
7473	.43	74180	1.05	
7474	.42	74181	3.50	

20% Discount for 100 Pieces Combined 7400

CMOS

8001	.59	8000 SERIES
8092	.59	
8095	1.39	
8123	1.59	
8130	2.19	
8200	2.59	
8210	3.49	
8223	4.00	
8288	1.15	
8520	1.29	
8826	5.00	
8880	1.33	

Christmas SPECIALS



Digital LCD Watch

Liquid Crystal Display
Constant on-Shock Proof
uses Field effect display
Accuracy to 1 Minute-a-Year.

5 Year Warranty \$149.95ea
Unassembled Kit 99.95ea
California Res. Add 6% Tax

USA MADE



CALCULATORS

5m8-4 Function 9V \$29.95 ea
6 Month Warr. Red Led
SL8M-4 Function Memory \$53.00 ea
%Add on Disc.-Tilt Lens
5m-20-5 Function Memory \$39.95 ea
Constant 9V-1 Yr.W.



TIME-Temp Display

6 digit LED Display
Liquid Crystal Temp. Display
115 Volt-1 Yr. Warr. \$39.95
—Kit from \$29.95

IC sockets
8 pin DIL .22 36 pin DIL 1.70
14 pin DIL .26 40 pin DIL 1.90
16 pin DIL .29 **WIRE WRAP** 8263 4.00
18 pin DIL .46 **LEVEL #3** 2513 12.00
22 pin DIL .65 14 pin DIL .46 2518 7.00
24 pin DIL .68 16 pin DIL .55 2524 6.00
28 pin DIL .99 24 pin DIL 1.05 7805 2.00

PROJECTS
Satisfaction Guaranteed. All Items 100% Tested
\$5.00 Min. Order — 1st Class Mail — No Charge
California Residents — Add 6% Sales Tax
Wholesale Outlets — Write for Special Discounts
Write for FREE Catalog — Data Sheets .20¢ each

JAMES

P.O. BOX 822, BELMONT, CA 94002
PHONE ORDERS (415) 592-8097
CIRCLE NO. 20 ON READER SERVICE CARD

LM300	LINEAR	\$.79
LM301H/N		.30
LM302H	Voltage Follower	.75
LM304H	Negative Volt Reg	1.10
LM305H	Positive Volt Reg	1.00
LM307H/N	Op Amp (Super 741)	.35
LM308H/N	Micro Power Op Amp	.99
LM309K	5 Volt Regulator/Amp	1.25
LM310H	Improved Volt Follower	1.35
LM311H/N	Hi-perform Volt.Comp.	.89
LM318N	Hi-Speed Op Amp	2.00
LM320K	To 3 Neg. Regulator	1.50
LM324N	Quad 741 Op Amp	1.75
LM339	Quad Comparator	1.65
LM340K	Positive Volt Regulator	1.89
LM370N	A 6 C - Squelch Amp	1.55
LM373N	AM/FM \$\$\$ B Strip	3.30
LM380N	2 Watt Audio Power Amp	1.15
LM555N	Timer	.75
LM565-LM566-LM567	Phase L.L.	2.00ea
LM703H	RF/IF Amp	.45
LM709H/N	Op Amp	.29
LM723H/N	Voltage Regulator	.55
LM741H/N	Comp. Op Amp	.30
LM747H/N	Dual Compn. Op Amp	.79
LM748N	Freq. Adj. 741	.40
LM1310P	Stereo Demodulator	3.50
LM1458N	Dual Comp. Op Amp	.65
LM1556N	5 Times Faster 741	1.85
LM2307P	Current Controlled 05 Cil.	3.15
LM3065N	T.V.-FM Sound System	.75
LM3900N	Quad Amp	.50
LM3905N	Precision Timer	.65
LM7522	Core Memory Sense Amp.	2.50
LM7524	Core Memory Sense Amp.	1.50
LM7535	Core Memory Sense Amp.	1.00
LM75451	Dual Peripheral Driver	.49
LM75452	Dual Peripheral Driver	.49
LM75453	Dual (LM351)	.65

LMV10	5/1	POWERSUPPLY KITS
MV50	6/1	Variable Power Supply
MV5024	5/1	5 to 25 Volt 1 Amp
MAN-1	1.95	1 Amp Chassis \$19.95 per Kit
MAN-3	.95	FIXED POWER SUPPLY
MAN-4	1.95	1 Amp - Specify one of the
MAN-7	1.00	ten available voltages plus
DL33	1.95	Plus Voltage: 5-6-12-15-24
DL747	2.50	Minus Voltage: 5-6-12-15-24
		Less - Chassis \$16.95 per Kit

"ALL LED" MONSANTO READOUTS

MONSANTO TYPE	CHAR. HT.	SALE EACH	Quantity Discounts
MAN-1	.27	\$3.50	3 for \$ 9.
MAN-2	.32*	4.95	3 for \$14.
MAN-3	.12	1.00	3 for \$ 2.50
MAN-6	.60	4.50	3 for \$12.
MAN-64	.4	3.50	3 for \$ 9.
MAN-7	.27	1.50	3 for \$ 3.

*35 LED matrix

POLY PAKS BLUE RIBBON Policy
INCLUDES

- 20-Years of Business INTEGRITY
- 20-Years of Money-Back GUARANTEES
- 20-Years of Economy! LOWEST PRICES!

48-HR. SERVICE

THE SIMPLEST! FINEST! SMALLEST!

6-FUNCTION AC-DC CALCULATOR KIT! \$24.50

- Lightweight, pocket size
- Extra large display
- 6 functions plus, minus, floating decimal
- Chain and Mix calculations
- True credit balance
- Simplified indexing
- Mark up and Mark down times, percentage, constant and division
- AC adaptor jack

Designed specifically for Poly Paks under the Daltone 80 brand. IMAGINE! Only 2 1/2 x 1 x 4 1/2". Slides easily into your vest pocket, brief case, or handbag. We hunted everywhere to find a calculator kit that can be small, do the many functions, with fine engineering design and SIMPLE TO BUILD! WHY? Because it has the fewest parts in a kit. Imagine the pc board only has the chip, 4 resistors, two transistors, two driver ic's with the 9 digit readout, SIMPLE! You bet it is. The entire kit is even packed in a multicolor attractively designed box that in itself tells the mini calculator story. Kit includes: attractive black case with red filter; Flex Key (type 20SK-66) 18 key keyboard that measures only 2 1/2" x 2" with 2 switches, one for ON-OFF, one for K constant; MAIN pc board; readout board; famous Cal Tech 6030 26-pin calculator chip; two 75491 ic drivers; Hewlett Packard 9 digit array; resistors; back protective plate; necessary wire plugs; easy instructions. (Less 9 volt standard battery and AC adapter)

EASIEST KIT TO BUILD

WRISTWATCH LIQUID CRYSTAL DISPLAY

\$9.95 3 1/2 digit, 7-segment only 1 1/16 x 1 1/16 x 1 1/4". Includes readout, socket, "slide-in-place chrome slide face plate". Same display as found in \$200. units.

NATIONAL LINEAR OP AMPS

LM-309K	1.50
LM-319	1.19
LM-320	1.25
LM-340	2.50
LM-380	1.39
LM-381	1.69
LM-703	.41
LM-703M	.41
LM-709	.25
LM-710	.29
LM-711	.29
LM-723	.61
LM-725	.69
LM-733	1.75
LM-741	.31
LM-741CV	.31
LM-1303	.79
LM-1304	1.10
LM-1307	.79
LM-1458	.69
LM-1496	.99
LM-3028	1.50
LM-3090	.69
LM-4250C	2.10

\$29.95
Buy 3 for \$75.

6 DIGIT DIGITAL CLOCK

First time ever offered! Mini design makes this unit adaptable to about any room at home, office, lab, shop, school. Uses famous National clock chips. Gold anodized construction. Easy to read numbers. Three pressure sensitive switches, for HOLD, HOURS, SECONDS, 12 or 24 hours in rear of unit. THIS IS NOT A KIT! Completely wired ready to go. Size: 6 x 2 x 1 1/2". Gift boxed. With instruction guide booklet. Wt. 1/2 lb., 110V/VAC, 60 cycle operation.

\$3.98 2 for \$7

35 WATT AUDIO AMPLIFIER BASIC

For Class AB use. Basic includes: Signetics 540 30 transistor high power driver TO-5 "IC", with a pair of complementary 35-watt plastic transistors, i.e. 2N5296 npn and 2N6109 pnp. With schematics, printed circuit and parts board layouts.

\$2.50 3 FOR \$6.00

GENERAL ELECTRIC 3-WATT AUDIO AMP

Delivers 3.5 watts continuous, 10 watts peak. With heat sinks; micro-mini size; 1/2" x 1/2" x 9/16" 30V supply. High sensitivity. 8 to 16 ohms.

\$6.99

CLOCK CHIPS as Low as

ON A "DIP" WITH DATA SHEETS

MMS311	6-digit 28-Pin	\$6.99
MMS312	4-digit 24-Pin	6.99
MMS313	6-digit 28-Pin	6.99
MMS314	6-digit 24-Pin	6.99
MMS316	4-digit 40-Pin, alarm	6.99
MMS316-A	no alarm	3.95
CT7001	4-6-digits Alarm & Calendar	9.95

\$55

TIMERS

2 u Seconds to 1-hr. (Mini DIP)

2 for \$1
Sale good till Feb. 15, 1975

GET KEY THE PARTS!

Calculator Basics

READOUTS

MAKE YOUR OWN CALCULATORS WITH OUR LOW PRICED

6-8-12 DIGIT BASICS

CHIP KEY BOARD

BASIC KIT #1 — includes case, all-function Flex Key Keyboard, Cal Tech CT5002 calculator chip, 9-digit Antex LED display with built-on individual magnifiers, plus sheets. **\$16.95**

BASIC KIT #2 — same as Basic #1 except calculator chip is National 8-digit MM5725. **\$16.95**

BASIC KIT #3 — same as Basic #1 except calculator chip is National 6-digit MM5736 and 75492. **\$16.95**

12 DIGIT BASIC #4 — Key parts include: CT5001 chip, 4-3 digit readouts, factory etched PC board, case, carrying case, 2-resistor networks, decimal switch. Wild Rover Keyboard with ON-OFF switch diagrams. **Sale \$24.95**

8-DIGIT MINI CALCULATOR BASIC KIT #6 — world's smallest. Needs least amount of components to complete kit. Includes CT-5030 chip, mini case, with lens, keyboard, with on-off and constant switches & percentage. 9-digit array (Hewlett Packard). Includes diagrams. **\$19.95.**

8-DIGIT "TEXAS INSTRUMENT" BASIC KIT #7 — includes Texas keyboard, 1K5149, standard 4-function. With T-1 calculator chip TMS-0128, p.c. board, case, lens. Microswitch (on-off). 9-digit ANTEX array; includes diagram. **\$19.95.**

MINI CALCULATOR BASIC KIT #8 — 4-Function Same as KIT #6 except less percentage and constant. Includes CT-5031 chip. **\$17.95.**

ANY CASE for above Calculator Basics \$2.50 3 for \$6.

CALCULATOR ACCESSORIES

Texas Instrument Keyboard	6.95	3 for \$18.
Wild Rover Keyboard	6.95	3 for \$18.
P.C. Boards "as tested" in above kits	\$2.50	3 for \$ 6.

AC ADAPTERS FOR CALCULATORS

9-Volt Charger & Converter	\$2.95	3 for \$ 7.
1.2 VDC @ 2A for Nicad Batteries	\$2.95	3 for \$ 7.

60-WATT STEREO AMPLIFIER \$9.95

All Solid State, Printed Circuitry
Slide Rule Dial
All Purpose, All Family System

Features: 4-speaker system, built-in FM antenna, record player jacks on separate panel. Another external panel consists of provisions for external FM and AM antennas, "satellite" speakers to provide 4-speaker sound, jacks for connecting a tape recorder to radio tuner or phono of systems to record. Lower inputs for connecting tape deck that will play back thru the internal amplifier for systems. AC jack for phone power connection. RED GREEN and CLEAR indicators for Phono, AM, and FM respectively. Includes red indicator on front panel for STEREO indicator. Has separate input to plug into mike, guitar and other musical instruments as well as another jack for plugging in a pair of stereo headphones.

Has controls on front panel. PHONO-STEREO-AM-FM, MONO, FM STEREO, GUITAR, TAPE, MIKE master control switch. LOUDNESS, BALANCE, TREBLE, BASS controls, with power ON-OFF rocker switch, and AFC ON-OFF. Designed for all audio-philos to use as well unit in DEN or FAMILY ROOM, or control unit by easy chair in family room, or for those who wish to design their own console or modular system. With 6 ft. 115 VAC cord and plug. Only 13 x 7 x 3 1/2" deep. No escutcheon, but we include template for one, plus diagram. Shpg. wt. 3 lbs. With knobs.

4 WATT GUITAR AMP SOLID With Tremolo \$7.95 AMPEREX

Musical instrument amplifier at low, low price! Peak power output 10 watts. Two input circuits are equalized for normal or solo guitar. The four controls are VOLUME, TONE, TREMOLO INTENSITY and TREMOLO SPEED. There are terminals on board for normally open foot switch connection. Supply voltage 18vdc. Output to 8 ohm impedance. Input impedance 33,000 ohms. Current drain 20 ma. External power supply required. Wt. 1 lb. With instructions, hookups and diagrams. Size 8 x 2 1/2 x 3.

60-WATT STEREO HIGH FIDELITY AMPLIFIER \$39.95

Wall "Slim-Line" Type!
Tape, Record Player, PA & Musical Instruments!

The most amazing audio offer for the hi-fi-ers. PA men, and an ideal unit for the family room, or any room in the house, office, etc. Comes complete with hookup, escutcheon, and knobs. 5 separate controls: LOUDNESS, BALANCE, TREBLE, BASS, circuits switch for PHONO, TUNER, TAPE, MIKE, AUX. 3 switches for SCRATCH FILTER, RUMBLE FILTER, and POWER "ON-OFF" with built-in lite. 4-output transistors, each 30 watts. Separate accessory mounting panel for 4 speaker attachment, mike and musical instrument jack, tape, tuner, and power jacks. 6-ft. cord set for 115VAC, 60 cycles. Measures only 13 x 7 x 3". Wt. 3 lbs. With attractive multi-color escutcheon. Made by leading US maker.

20-20,000 cycles Resp • 4-Channel Spkr. Systems!

THREE QUARTER INCH DIGITS BY OPCOA \$4.95

Any color
3 for \$13.
* 0 to 9
* 0.7 character
* 7 Segments
30 mils

Order by Type
SLA-3H
SLA-4H
SLA-13
SLA-14*
SLA-23
SLA-24
*Plus or Minus one

LOWEST PRICES ON NATIONAL 'CALCULATOR CHIPS'

CT 5001	12-Digits, 40 pin	\$4.95	3 for \$12.
CT 5002	9-Volt version of 5001	6.50	3 for \$18.
CT 5005	12-Digits, 28-pin, with 3-function memory	7.50	3 for \$21.
CT 5030	4-Function with %	9.95	3 for \$24.
CT 5031	4-Function Only	9.95	3 for \$18.
TMS-0128	4-Function by Texas.	6.95	3 for \$24.
MM 5725	8-Digits, 4-funct. LED	4.95	3 for \$12.
MM 5736	6-Digits, 28-pin, 9V	4.95	3 for \$12.

First Time!

ANY 10 IC'S BUY 100
FROM OUR 2 PAGE AD
TAKE 15% TAKE 25%

Inflation-Fighting ECONOMY IC PRICES

Order by type number! Spec sheets on request "ONLY" • Factory Marked

SN7400	\$1.19	SN7430	.24	SN7472	.42	SN74107	.49	SN74161	1.59
SN7401	.19	SN7432	.28	SN7473	.52	SN74108	.95	SN74162	1.75
SN7402	.24	SN7437	.45	SN7474	.39	SN74112	.95	SN74164	2.85
SN7403	.19	SN7438	.49	SN7475	.91	SN74113	.95	SN74165	2.85
SN7404	.24	SN7440	.19	SN7476	.52	SN74114	.95	SN74166	1.85
SN7405	.24	SN7441	1.00	SN7477	.75	SN74121	.49	SN74173	1.85
SN7406	.79	SN7442	1.00	SN7478	.59	SN74122	.51	SN74174	2.25
SN7407	.48	SN7443	1.00	SN7479	.59	SN74123	1.09	SN74175	1.99
SN7408	.27	SN7444	1.00	SN7482	.99	SN74125	.65	SN74176	1.25
SN7409	.27	SN7445	1.00	SN7483	1.19	SN74126	.89	SN74177	1.25
SN7410	.19	SN7446	1.10	SN7485	2.50	SN74129	1.25	SN74180	1.10
SN7411	.31	SN7447	1.10	SN7486	.49	SN74140	2.49	SN74181	3.95
SN7412	.55	SN7448	1.45	SN7489	2.95	SN74141	1.19	SN74182	1.05
SN7413	.89	SN7450	2.27	SN7490	1.81	SN74145	1.19	SN74185	2.34
SN7414	2.25	SN7451	.28	SN7491	1.35	SN74148	2.95	SN74187	2.34
SN7415	.45	SN7452	.28	SN7492	.99	SN74150	1.19	SN74189	1.10
SN7416	.45	SN7453	.39	SN7493	.99	SN74151	.99	SN74191	3.95
SN7417	.50	SN7455	.28	SN7494	1.05	SN74153	1.39	SN74194	1.89
SN7420	.22	SN7460	.26	SN7495	.99	SN74154	1.69	SN74195	1.10
SN7421	.50	SN7461	.26	SN7496	.99	SN74155	1.29	SN74196	1.20
SN7422	.29	SN7462	.39	SN7497	1.90	SN74156	1.45	SN74197	1.10
SN7423	.32	SN7464	.39	SN74104	1.25	SN74157	1.45	SN74198	1.45
SN7425	.35	SN7465	.39	SN74105	.95	SN74158	1.45	SN74199	2.45
SN7426	.31	SN7470	.49	SN74106	.95	SN74160	1.85	SN74200	7.50
SN7427	.35	SN7471	.55						

INTEGRATED CIRCUIT SOCKETS

14-Pin, DIP	\$.45
14-Pin, Side Mount	1.00
16-Pin, DIP	.50
TO-5 or TO-18 Pins	.29
8-Pins (Mini DIP)	.39
14-Pin, Wire Wrap	.69c
16-Pin, Wire Wrap	.89c

Buy Any 3
Take 10%
Discount!

Terms: add postage. Rated: net 30.
Photo Orders: Wakefield, Mass. (617) 245-8829
Retail: 16-18 Del Carmine St., Wakefield, Mass. (off Water Street) C.O.D.'S MAY BE PHONED

20c CATALOG on Fiber Optics, IC's, Semi's, Parts
MINIMUM ORDER — \$4.00

POLY PAKS

P.O. BOX 942E, LYNNFIELD, MASS. 01940

DIGITAL MODEM SYSTEMS, \$45.00, IC's under 10 cents each, miscellaneous computer equipment. Send SASE for free flier, MNH—Applied Electronics, P.O. Box 1208, Landover, MD 20785.

RESISTORS 1/2, 1/4 watt 2 cents minimum \$2.00. 5314 clock chip \$5.00, SLA-1 readouts \$1.00. Lectronix, Box 42, Madison Heights, MICH 48071.

FREE—Catalog of Electronic Surplus Component Bargains. 10 cent stamp to TRI-TEK, Box 14206, Phoenix, AZ 85063.

CONSTRUCTION PLANS. New projects every month. Send for complimentary copy. Electronic Projects Newsletter, Box 1026S, Fremont, Calif. 94538.


CIRCUIT board service. Circuit boards made from your layouts. Send for information. Printed Circuits, 22 Maple Avenue, Lackawanna, New York 14218.

FREE BARGAIN CATALOG. Transistors, LED's, Readouts, Micro-Miniature Parts, Unusual Electronic Components. Chaney's, Box 15431, Lakewood, Colorado 80215.

TELEPHONE OR OFFICE BUGGED???? Learn How To Protect Yourself. Details \$1.00. SECURITY, Box 671, Westwood, New Jersey 07675.

KEYBOARD, ASCII, \$35.00; UART, \$10.00, 2102 memories, \$10.00, 1101 A, \$2.20, some microprocessor parts. CMOS RCA CD4017, \$1.00. Beckman, 1618 James, Syracuse, N.Y. 13203.

VIDEO 1/4" Tape System—Portable. AKAI VT-100 \$700.00. ZELL, Box 17017, Euclid, Ohio 44117.



NEW: ROTARY CIRCUIT LOCALIZER

Visual Aid Disks—turning reveals visual electrical effects and explanations simultaneously of capacitor inductor and resistor components.

\$4.50 a Set—Condensed Elect. Theory
PeriCalc
Box 523, San Francisco, CA 94101

ALARM CLOCK CHIP MM5316, \$6.50! HP5082-7730 7 seg LED, \$1.50! 60 cents postage. BDJ Electronics, Tappan, New York 10983.

WANTED

QUICKSILVER, Platinum, Silver, Gold, Ores Analyzed. Free Circular. Mercury Terminal, Norwood, Mass. 02062.

PLANS AND KITS

ATTENTION AUDIO FREAKS!!! ... Audio Processing Circuits ... designs, kits, units. Laboratory tested designs for hobbyist through professional use—limiters, compressors, equalizers, phasers, mixers and more! Send now—\$1.00 (refundable) for complete catalog—CIRCUIT RESEARCH LABS, 3920 E. Indian School, Phoenix, AZ 85018.

KITS

UNIQUE CANADIAN ELECTRONICS CATALOGUE \$1.00 (refundable on 1st purchase)



featuring

- SINCLAIR hi-fi modules and calculator kits. We will include the new 32-page Project 80 hi-fi module construction manual.
 - AMTRON electronic kits—over 100 types!
 - Speaker kits and components
- American enquiries welcome!

GLADSTONE-ELECTRONICS

1736 AVENUE RD., TORONTO, ONT.
M5M 3Y7. DEPT. PE-1

FREE CATALOG. 200+ unique electronic projects. Bio-feedback, acupuncture, more! Cimarron Labs, 4183A Springfield St., Burton, Michigan 48509.



complete calculator

KITS

ALL PARTS, INSTRUCTIONS INCLUDED
SIMPLIFIED PC BOARD CONSTRUCTION
12 DIGIT CAPACITY. 5x3x1 SIZE
SELECTABLE DECIMAL BATTERY OR AC

- 8 digit display — \$19.95, 9 digit — \$22.95. NiCad power pack — \$3.95
- AC adapter/recharger — \$2.95
- Manual only — \$2.00 (deductible from Kit). Shipping — \$1.50

WIZARD ELECTRONICS: Dept. PE-1
P.O. Box 161 Agnew Santa Clara California 95054

USE your transistor radio as a sensitive direction finder. Great for emergencies. Complete plans. Guaranteed results. \$1.00. RADIO COMPASS, Dept. B, Box 606, Webb City, Missouri 64870.

TESLA COIL—40" SPARKS! Plans \$7.50. Information 75 cents. Huntington Electronics, Box 2009-P, Huntington, Conn. 06484.

HIGH FIDELITY

DIAMOND NEEDLES and Stereo Cartridges at Discount prices for Shure, Pickering, Stanton, Empire, Grado and ADC. Send for free catalog. LYLE CARTRIDGES, Dept. P, Box 69, Kensington Station, Brooklyn, New York 11218.

SAVE 50%. Build your own speaker systems featuring Nor-elco, Eminence and CTS. Famous brands from world's largest speaker factories at lowest wholesale prices. Write for free catalog of speakers and electronic accessories. McGee Radio Company, 1901 McGee Street, Kansas City, Missouri 64108.

LISTEN TO SPECTACULAR 4-CHANNEL SOUND!

Expand your stereo to quadraphonic Hi-Fi. Build the VISTA Full Logic "SQ" Decoder. Latest CBS licensed circuitry using 3 IC's to provide Full Logic and Wave Matching. Exclusively ours. Kit SQ-1 \$37.50. Shipped prepaid in USA & CANADA. Send for information.

PHOTOLUMÉ CORPORATION

118 East 28th Street, New York, N.Y. 10016

SHOTGLASS. As seen in Esquire. Glasscone Column Speaker. \$129.50 each. F.O.B. Moneyback Guarantee. TECHYON®, Box 1012, Roselle, Illinois 60172.

MOVIE FILMS

8MM-SUPER 8-16MM MOVIES! Biggest Selection! Lowest Prices! Free Catalog! Cinema Eight, Box PE, Chester, Connecticut 06412.

ELECTRICAL SUPPLIES & EQUIPMENT

PLATING Equipment, Portable Platers, Supplies and "Know-How." Build your own tanks for nickel, chrome, etc. Easy-to-install PVC liners. Rectifier components—all sizes. Schematics, parts lists, formulas, operating instructions for all plating. Guaranteed to save you 25%-75%. Some good units for sale. Write for details. Platers Service Company, 1511-PE Esperanza, Los Angeles, Calif. 90023.


BURROUGHS PANAPLEX




BURROUGHS PANAPLEX II 12 digit display BR13251 is a multi-digit, segmented, thin panel display in a common envelope. Any or all digits may be used, along with periods and commas. The characters are 0.25", and are ideal for any device requiring multiple digits, clocks, counters, calculators etc. Compatible with DTL, TTL & CMOS circuitry and chips. Display is neon glow discharge, orange color. We provide many pages of data & applications. Cost is less than 1.00 per digit. 1"x3 3/4" for 12 digit display.

STOCK NO.F220 11.95 ea, 2/21.00

12 VOLT DC SIREN



Hard to find 12 volt DC SIREN ideal for alarm systems or any 12 volt auto.
STK. No. F5219 11.95 2/20.00



Heat sink assembly of 2 2N4904 PNP 87 watt power transistor. Other transistor is complimentary to above. Specs are same as 2N3055 except Bveco is 40 volts. All transistors mounted in sockets. Distributor price of transistors is 3.35 ea. Extra NPN xistors available for .75 ea.

STOCK NO.F9034 assembly 3.50 3/9.00

MINIMUM ORDER \$5.00. Include postage, excess refunded. New edition of our catalog now available.



DELTA ELECTRONICS CO.

BOX 1, LYNN, MASSACHUSETTS 01903
Phone (617) 388-4705

Planning to move?

Let us know 8 weeks in advance so that you won't miss a single issue of **POPULAR ELECTRONICS**.

Attach old label where indicated and print new address in space provided. Also include your mailing label whenever you write concerning your subscription. It helps us serve you promptly.

Write to: P.O. Box 2774, Boulder, CO 80302, giving the following information:

- Change address only.
- Extend subscription. Enter new subscription.
- 1 year \$6.98
- Payment enclosed (1 extra BONUS issue)
- Bill me later

AFFIX LABEL

If you have no label handy, print OLD address here.

name	please print	zip-code	0890
address	please print	state	
city		city	
state		state	

Add'l postage: \$2 per year outside U.S., its poss. & Can.

C-MOS

4000AE	\$.55	10 up
4001AE	.54	.53
4002AE	.54	.53
4004AE	5.90	5.90
4006AE	3.90	3.80
4007AE	.65	.60
4008AE	3.60	3.30
4009AE	.95	.94
4010AE	.95	.94
4011AE	.54	.53
4012AE	.54	.53
4013AE	1.15	1.05
4014AE	3.70	3.25
4015AE	3.80	3.70
4016AE	1.15	1.05
4017AE	2.90	2.70
4018AE	3.20	3.05
4019AE	1.30	1.20
4020AE	3.90	3.30
4021AE	3.80	3.60
4022AE	2.75	2.55
4023AE	.54	.53
4024AE	2.30	2.00
4026AE	.54	.50
4028AE	9.80	7.10
4027AE	1.35	1.22
4028AE	2.95	2.75
4029AE	5.40	4.60
4030AE	1.25	1.05
4035AE	2.85	2.80
4040AE	4.60	4.40
4041AE	3.30	3.20
4042AE	2.95	2.85
4043AE	2.95	2.85
4044AE	2.95	2.85
4047AE	3.70	3.60
4048AE	1.50	1.40
4049AE	1.35	1.05
4050AE	1.35	1.05
4056AE	3.50	3.46
4060AE	5.20	4.90
4066AE	3.20	2.96
4069AE	.85	.75

Schottky TTL

SN74S00N	\$.80
SN74S02N	.80
SN74S03N	.80
SN74S04N	.80
SN74S08N	.80
SN74S10N	.80
SN74S11N	.80
SN74S20N	.80
SN74S30N	.80
SN74S32N	.80
SN74S40N	.80
SN74S41N	.80
SN74S64N	.80
SN74S74N	1.50
SN74S85N	6.10
SN74S86N	2.90
SN74S112N	2.50
SN74S113N	1.50
SN74S133N	1.00
SN74S138N	4.50
SN74S139N	3.90
SN74S140N	1.00
SN74S151N	3.30
SN74S153N	3.30
SN74S154N	3.40
SN74S157N	2.70
SN74S158N	3.00
SN74S160N	6.60
SN74S161N	6.60
SN74S174N	4.75
SN74S175N	4.00
SN74S181N	11.50
SN74S189N	5.10
SN74S194N	3.30
SN74S195N	4.40
SN74S251N	4.20
SN74S253N	4.20
SN74S275N	3.20
SN74S258N	3.70
SN74S260N	.90
SN74S280N	5.70
SN74289N	5.00
93S10	6.80
93S16	6.80
93S21	3.50
93S22	3.20
93S48	3.70

HIGH SPEED TTL

74H00N	.34
74H01N	.49
74H04N	.36
74H05N	.38
74H08N	.44
74H10N	.44
74H11N	.44
74H15N	.38
74H20N	.39
74H40N	.36
74H74N	.69

I-Amp Rectifiers

1N4001	\$ 1.00	1000
1N4002	1.10	700
1N4003	1.20	900
1N4004	1.30	1000
1N4005	1.40	1100
1N4006	1.50	1200
1N4007	1.60	1300

Waveform Generator Kit



XR205K Only \$28.00
Here's a highly versatile lab instrument at a fraction of the cost of conventional unit. Kit includes two XR205 IC's, data & applications, PC board (etched & drilled, ready for assembly) and detailed instructions.

FM Stereo Demodulator

XR1310 \$3.90

Audio Amps

LM352A	6-15V, 1.15W, 8Ω	1.60
LM354A	6-27V, 2.80W, 8Ω	2.50
TAAG11B12	6-15V, 1.15W, 8Ω	1.60
TAAG11A12	6-27V, 1.40W, 8Ω	2.00
TBAG41B11	6-18V, 2.20W, 4Ω	3.00
TBAG00	5-30V, 4.70W, 8Ω	2.20
TB810AS	4-20V, 2.50W, 4Ω	3.00
TB820	3-16V, 0.75W, 4Ω	1.70
TCA830	5-20V, 2.00W, 4Ω	2.20
TCA940	6-24V, 6.50W, 8Ω	4.40

Power Transistors

BU204	3A	1300V	\$4.14
BU205	3A	1500V	4.95
BU206	3A	1700V	5.94
BU207	6A	1300V	5.95
BU208	6A	1500V	6.93
BU209	6A	1700V	8.64

2N512B	\$3.00
2N1136	1.50
2N1483	1.20
2N1534	1.00
2N1540	1.10
2N1544	.90
2N3053	.35
2N3055	.95
2N3375	5.50
2N3442	2.20
2N3730	1.70
2N3731	2.00
2N3732	1.50
2N3771	2.20
2N3772	2.30
2N3773	3.40
2N3789	3.00
2N3866	.95
2N4347	1.60
2N4348	2.00
2N4395	1.30
2N4427	1.10
2N5109	2.10
2N5322	.92
2N5323	.75
2N6099	.80
2N6101	.80
2N6103	.90

7400N TTL

7400N	\$.16
7401N	.23
7402N	.22
7403N	.22
7404N	.25
7405N	.29
7406N	.38
7407N	.48
7408N	.24
7409N	.54
7410N	.24
7411N	.29
7412N	.51
7413N	.78
7414N	2.81
7416N	.46
7417N	.64
7420N	.19
7421N	.51
7423N	.49
7425N	.39
7426N	.29
7427N	.35
7428N	.51
7430N	.22
7432N	.28
7433N	.61
7437N	.44
7438N	.44
7439N	1.01
7440N	.19
7441AN	1.16
7442N	.98
7445N	.98
7447N	1.50
7448N	1.29
7450N	.23
7451N	.28
7453N	.25
7454N	.26
7460N	.24
7470N	.30
7472N	.39
7473N	.46

DUAL LOW NOISE OP AMP

LM331N	
V _{io}	= 6mV
I _{ie}	= 1000nA
I _b	= 2000nA
Noise	= 1.5dB
	\$2.20

HYBRID POWER AMPLIFIERS

SI-1010G	10W	\$ 6.90
SI-1020G	20W	9.90
SI-1030G	30W	18.70
SI-1050G	50W	25.90

PREMIUM QUALITY COMPONENTS

We've been buying and selling top quality components for nearly ten years. Our annual volume exceeds \$3 million. We handle only original parts, from the world's leading manufacturers and our customers include some of the largest and most quality-conscious companies.

Now you can take advantage of our component buying skills and power and select from a broad range of advanced circuits.



IC sockets


Solder	3 pin	Teflon	.55
8 pin DIL	.22	4 pin TO-5	.65
14 pin DIL	.26	8 pin TO-5	.90
16 pin DIL	.29	8 pin TO-5	1.10
24 pin DIL	.75		
28 pin DIL	1.10		
36 pin DIL	1.70		
40 pin DIL	1.90		

Wire Wrap

14 pin DIL	.40
16 pin DIL	.45

Model 4440

A PORTABLE 4 1/2 DIGIT MULTIMETER FOR \$299. A 10 MHz COUNTER OPTION FOR \$50.



Calculator Limited QUANTITY \$19.00



Digital Watch

with liquid crystal display. Beautiful, reliable and accurate. \$149.00 plus \$2.50 for shipping and handling.



Memories

P1101A	\$6.90
P1101A1	8.50
P1402A	7.90
P2102	15.00
P3101	5.50
P3101A	5.50
MM6560N	5.00
MM6561N	5.00
DM8599N	5.00
93403	5.00

Decoded Read/Write RAM

P1103	\$6.20
-------	--------

1024 Bit N-Channel RAM



2602B	\$21.00
2602-1B	25.00
7552-1CPE	21.00
7552-1CPE	25.00

LOW POWER TTL

74L00N	\$.34
74L02N	.34
74L03N	.39
74L04N	.39
74L10N	.34
74L20N	.39
74L42N	1.62
74L47N	2.60
74L51N	.34
74L73N	.79
74L74N	.84
74L90N	1.62
74L93N	1.74
74L95N	1.62

Interface Modules

CY1010	Instr. Amp., Bipolar Input	\$ 29.00
CY1011A	Instr. Amp., Bipolar Input	49.00
CY1020	Instr. Amp., FET Input	34.00
CY1021	Instr. Amp., FET Input	49.00
CY1021A	Instr. Amp., FET Input	59.00
CY2018	DAC, 8 Bit, 2 Quad Multiplying	99.00
CY2137	DAC, 12 Bit, Low Drift	39.00
CY2218	DAC, 12 Bit, 2 Quad Multiplying	149.00
CY2236	DAC, 12 Bit, Fast Settling, Low Drift	89.00
CY2237	DAC, 12 Bit, Low Drift	69.00
CY2735	DAC, 4 Digit BCD, Low Cost	79.00
CY2737	DAC, 4 Digit BCD, Low Drift	139.00
CY3035	ADC, 8 Bit, Sect. Counting, Low Cost	89.00
CY3635	ADC, 3 Digit BCD, Sect. Count, Low Cost	119.00



9-Digit Display \$7.90

• 1/8" character height
• compact, thin PC package
• wide viewing angle

Displays

SLA1	Red	\$2.25
SLA11	Green	4.25
SLA21	Orange	4.25
SLA2	±1 Red	2.25
SLA12	±1 Grn	2.25
SLA22	±1 Org	2.25
SLA3	Red	7.50
SLA4	Red	7.50
XAN72	Red	2.50
XAN52	Green	2.50

Optoisolator

MCT2	1.45
MV50	Red \$.30

Voltage Regulators

LM100H	\$ 5.50
LM104H	6.50
LM105H	5.10
LM105F	8.50
LM109H	9.50
LM109K	6.30
LM200H	3.80
LM204H	4.70
LM205H	3.00
LM209H	3.50
LM209K	3.70
LM300H	.90
LM300N	1.40
LM304H	1.40
LM305H	1.10
LM305AH	1.40
LM305N	1.20
LM309H	1.75
LM309K	1.95
LM340-05K	2.60
LM340-06K	2.60
LM340-08K	2.60
LM340-12K	2.60
LM340-15K	2.60
LM340-18K	2.60
LM340-24K	2.60
LM723H</	

TUBES

RADIO & T.V. Tubes—36 cents each. Send for free Catalog. Cornell, 4213 University, San Diego, Calif. 92105.

RECEIVING & INDUSTRIAL TUBES, TRANSISTORS. All Brands — Biggest Discounts. Technicians. Hobbyists. Experimenters — Request FREE Giant Catalog and SAVE! ZALYTRON, 469 Jericho Turnpike, Mineola, N.Y. 11501.

TUBES receiving, factory boxed, low prices, free price list. Transletronic, Inc., 1306 40th Street, Brooklyn, N.Y. 11218A, Telephone: 212-633-2800.

TUBES "Oldies", latest. Lists free. Steinmetz, 7519 Maplewood, Hammond, Indiana 46324.

TUBES 60% OFF LIST PRICE. McCord Electronics, Box 276-T, Sylvania, Ohio 43560.

TAPE AND RECORDERS

RENT 4-Track open reel tapes—all major labels—3,000 different — free brochure. Stereo-Parti, 55 St. James Drive, Santa Rosa, Ca. 95401.

1930-1962 Radio Programs. Reels, \$1.00 Hour! Cassettes, \$2.00 Hour!... Mammoth Catalog, \$1.25. AM Treasures, Box 192F, Babylon, N.Y. 11702.

CASSETTE LABELS
Plain white cassette labels. Norelco cassette cleaners, paper mailer boxes hold Norelco type plastic box. Famous brand cassettes. "Like new" 10-1/2" metal or fiberglass reels. Send for open reel and cassette discount catalog. 1-9 10-99 100 1000
Cassette Labels (Multiples of 10) 1-9 10-99 100 1000
Norelco Cassette Cleaner .65 .60 .55 .50
Cassette Paper Mailer Boxes .03 .025 .022 .02
Scotch Cassette SC90HE, Buy 2, get ONE FREE 2.72 2.55 2.44 2.39
10-1/2" Fiberglass Reels, Used .50 .50 .40 .35
10-1/2" Metal, NAB Hole, Used 1.00 1.00 .90 .80
Plus Postage by Weight and Zone Minimum Order, \$5.00
1776 COLUMBIA ROAD, N.W.
WASHINGTON, D.C. 20009

SAXITONE TAPE SALES

GOVERNMENT SURPLUS

GOVERNMENT Surplus. How and Where to Buy in Your Area. Send \$2.00. Surplus 30177-PE Headquarters Bldg., Washington, D.C. 20014.

MANUALS for Govt Surplus radios, test sets, scopes. List 50 cents (coin). Books, 7218 Roanne Drive, Washington, D.C. 20021.

PERSONALS

MAKE FRIENDS WORLDWIDE through international correspondence. Illustrated brochure free. Hermes, Berlin 11, Box 110660/ZD, Germany.

INVENTIONS WANTED

CASH-ROYALTIES for patented, unpatented inventions. Global Marketing Service, 2354-P Telegraph, Oakland, California 94612.

INVENTORS: Protect your ideas! Free "Recommended Procedure". Washington Inventors Service, 422T Washington Building, Washington, D.C. 20005.

FREE PAMPHLET: "Tips on Safeguarding Your Invention." Write: United States Inventors Service Company, 708-T Carry Building, Washington, D.C. 20005.

FILE your own patent application. Complete information and materials. Write: Inventor's Guide, 468-R, Goodspeed Road, Virginia Beach, Virginia 23451.

TEKTRONIX 321A
PORTABLE ALL-TRANSISTORIZED
3", 5MHz TRIGGERED SCOPES
WITH 10:1 PROBE \$450.00

MINIATURE TRIM POTS
5K, 10K, 25K, 50K, 100K,
\$.75 EA. 3/\$2.00

MULTI-TURN TRIM POTS
Similar to Bourns 3010 style 3/16" x 3/8" x
1 1/4" 50, 100, 500, 2000, 5000, 10,000
ohms. \$1.50 ea. 3/\$4.00

PRINTED CIRCUIT BOARD
4 1/2" x 6 1/2" single sided fiber
glass board, 1/16" thick, un-
etched \$.50 ea. 5/\$2.20

LIGHT ACTIVATED SCR'S,
TO-18 200V 1A \$1.75

TRANSISTOR SPECIALS

2N256 PNP GE TO-3 \$.50
2N404 PNP GE TO-5 4/\$1.00
2N1137B PNP GE TO-3 \$.95
2N1016A NPN Si TO-82 \$ 1.95
2N3904 NPN Si TO-92 4/\$1.00
MPS3393 NPN Si TO-92 4/\$1.00
2N3906 PNP Si TO-92 4/\$1.00
MPS A13 NPN Si TO-92 3/\$1.00
2N3767 NPN Si TO-66 \$.70
2N2222 NPN Si TO-18 5/\$1.00
2N3055 NPN Si TO-3 \$ 1.00
2N5296 NPN Si TO-220 \$.50
2N6109 PNP Si TO-220 \$.55
2N4898 PNP Si TO-66 \$.60
MJ2252 NPN Si TO-66 \$.90
2N3638 PNP Si TO-5 5/\$1.00
2N2218A NPN Si TO-5 4/\$1.00

C/MOS (DIODE CLAMPED)

74C 02 \$.55
74C 10 \$.60
74C 157 \$2.15
74C 165 \$3.50
CD 4001 \$.55
CD 4002 \$.65
CD 4009 \$.80
CD 4010 \$.65
CD 4011 \$.55
CD 4012 \$.50
CD 4013 \$1.20
CD 4016 \$1.25
CD 4019 \$1.35
CD 4022 \$2.25
CD 4023 \$.55
CD 4025 \$.55
CD 4027 \$1.35
CD 4030 \$.65
CD 4050 \$1.35

Full Wave Bridges

PRV 2A 6A 25A
200 .95 1.25 4.00
400 1.15 1.50 5.00
600 1.35 1.75 6.00

NIXIE TUBES
Similar to Raytheon 8650
tubes, with socket & data
sheet \$2.25 3/\$6.00

FPA-711 — THESE PHOTO DIODE
ARRAYS ARE USED TO READ
SEVEN LEVEL TAPE 100 ma
SPACING \$5.95

TIS 73 N FET \$5.95
2N4891 UJT \$.50
ER900 TRIGGER DIODES 4/\$1.00
2N6027 PROG. UJT \$.75
ITS 1233 DUAL FET \$1.95

CAPACITORS

6V 30 UF TANT. 5/\$1
20V 4.7UF TANT. 5/\$1 MAN-1, RED OR YELLOW
12V 100UF ELECT. 5/\$1 LED READOUTS \$2.50
50V 100UF ELECT. \$.40 MAN-3 READOUTS \$1.75
25V 300UF ELECT 4/\$1.00 MAN-4 READOUTS \$2.00

1103 1024 bit RAM \$4.75
NEC 6003 2048 bit RAM \$9.50
1101 256 bit RAM \$1.75
8225 64 bit-write RAM \$2.75
8223-PROGRAMMABLE
ROM \$4.75
MM5203-2048 BIT ERASABLE
PROM \$23.95

5311—CLOCK CHIP 6 DIGIT BCD
HOLD COUNT, OUTPUT
STROBE \$7.75
5314—CLOCK CHIP 6 DIGIT HOLD
COUNT, OUTPUT STROBE \$7.75
5316—ALARM CLOCK CHIP \$8.50

2513-64x7x5
CHARACTER GEN \$9.95
2516-64x6x8 STATIC
CHARACTER GEN \$9.95

SANKEN AUDIO POWER AMPS

Si 1010 Y 10 WATTS \$ 6.40
Si 1025 E 25 WATTS \$17.95
Si 1050 E 50 WATTS \$24.95

VERIPAX PC BOARD
This board is a 1/16" single
sided paper epoxy board,
4 1/2" x 6 1/2" (standard veripax),
DRILLED and ETCHED which
will hold up to 21 single 14 pin
IC's or 8, 16 or LSI DIP IC's with
busses for power supply con-
nections. Is also etched for 22
pin connector \$5.25

FLV 100 VISIBLE LED \$.50
ME-4 IR LED \$.40
MCD-2 OPTO-ISOL \$.90
GREEN GAP OSL-16 LED \$.60
RED GAP OSL-3 LED \$.40
14 PIN DIP SOCKETS \$.40
16 PIN DIP SOCKETS \$.50

Conductive Elastometer low
profile calculator keyboard. A
2 3/4" x 3 3/4" x 1/2" flex key,
19SK-6 keyboard having 0-9, .,
+, -, x, =, =, K+C buttons with
off, on switch. \$6.00

CT5005-12 DIGIT CALCULA-
TOR CHIP \$7.95

TTL IC SERIES

74100—30 7476—47
7400—18 7480—65
7401—18 7483—1.10
7402—18 7485—1.30
7403—18 7486—48
7404—22 7489—2.75
7405—22 7490—75
7406—37 7491—1.30
7407—37 7492—75
7408—24 7493—75
7410—18 7496—99
7411—30 8220—1.50
7412—45 74107—50
7413—75 74121—60
7416—37 74123—1.00
7417—37 74125—1.40
7426—30 74126—1.40
7427—33 74150—1.15
7430—18 74151—95
7432—30 74153—1.10
7437—44 74154—1.65
7438—37 74157—1.25
7440—21 74163—1.60
7441—1.05 74164—2.05
7442—1.00 74165—2.05
7445—1.10 74173—1.80
7446—1.15 74177—1.80
7447—1.15 74181—3.60
7448—1.20 74192—1.50
7450—18 74193—1.45
7472—40 74195—1.00
7473—43 75324—1.75
7474—43 75491—1.10
7475—75

Silicon Power Rectifiers

PRV	1A	3A	12A	50A
100	.06	.11	.30	.80
200	.07	.16	.35	1.15
400	.09	.20	.50	1.40
600	.11	.25	.70	1.80
800	.15	.35	.90	2.20
1000	.20	.45	1.10	2.60

LINEAR CIRCUITS

LM 309K 5V 1A REGULATOR \$1.65
723-40 +40V REGULATOR \$.58
301/748-HI Per. Op. Amp. \$.35
LM 320-5 or -15V REGULATOR \$1.75
LM 376-V to 37V POS REG. \$.58
741A or 741C OP. AMP. \$.35
709C OPER AMP \$.29
340T-5, 12, 15, 18, 24V
POS. REG. TO-220 \$1.75
101 OPER. AMP. HI PERFORM \$.75
LM 308 OPER. AMP., LOW POWER. \$1.05
747-DUAL 741 \$.75
536-FET INPUT OPER. AMP. \$2.60
537-PRECISION OP. AMP. \$2.60
LM 3900-QUAD OP. AMP. \$.58
LM 324-QUAD 741 \$2.20
560-PHASE LOCK LOOP \$2.60
561-PHASE LOCK LOOP \$2.60
565-PHASE LOCK LOOP \$2.60
567-TONE DECODER \$2.95
703-RF-IF AMP. \$.55
LM 370-AGC SQUELCH AMP. \$1.15
555-2 us - 2 HR. TIMER \$.98
1458 DUAL OP. AMP. \$.60
1456 OPER. AMP. \$.95
LM 380-2W AUDIO AMP. \$1.45
LM 377-2W STEREO AUDIO AMP. \$2.60
LM 381-STEREO PREAMP \$1.75
LM 382-DUAL AUDIO PREAMP \$1.75
LM 311-HI PER. COMP. \$.95
LM 319-DUAL HI SPEED COMP. \$1.25
LM 339-QUAD COMP. \$1.65

**REGULATED MODULAR
POWER SUPPLIES**

+15VDC AT 100 ma, 115VAC
INPUT \$19.95
5VDC AT 1A, 115VAC
INPUT \$19.95
IN 4148 \$14/\$1.00

TRIACS

PRV	1A	10A	25A	1.5A	6A	35A
100	.40	.70	1.30	.40	.50	1.20
200	.70	1.10	1.75	.60	.70	1.60
400	1.10	1.60	2.60	1.00	.20	2.20
600	1.70	2.30	3.00			3.00

Terms: FOB Cambridge Mass. Send check or Money Order. Include Postage. Minimum Order \$3.00

8038C IC VOLTAGE CON-
TROLLED OSCILLATOR \$4.95

Send 20c for our catalog featuring Transistors and Rectifiers; 145 HAMPSHIRE ST. Cambridge, Mass.

SOLID STATE SALES
P.O. BOX 74A
SOMERVILLE, MASS. 02143 TEL. (617) 547-4005

WE SHIP OVER 95%
OF OUR ORDERS THE
DAY WE RECEIVE THEM

inventors
...Manufacturers Need
New Products

If you have an idea for a new product, or a way to make an old product better, contact us, "the idea people." We'll develop your idea, introduce it to industry, negotiate for cash sale or licensing.

Send for our FREE "Invention Kit." It has a special "Invention Record Form," an important brochure, "Your Invention — Its Development, Protection & Marketing," and a Directory of 500 Corporations Seeking New Products. You'll learn how ideas become a reality!

RAYMOND LEE ORGANIZATION
230 Park Avenue, New York, N.Y. 10017

I'd like to find out how to take action on my idea. Send Free "Invention Kit No. A-112"

Name _____ Please Print
Address _____
City _____ State _____ Zip _____

SAN FRANCISCO LOS ANGELES TORONTO VANCOUVER DENVER CHICAGO

INSTRUCTION

LEARN ELECTRONIC ORGAN SERVICING at home all makes including transistor. Experimental kit—trouble-shooting. Accredited NHSC, Free Booklet. NILES BRYANT SCHOOL, 3631 Stockton, Dept. A, Sacramento, Calif. 95820.

LEARN WHILE ASLEEP, Hypnotize! Strange catalog free. Auto-suggestion, Box 24-2D, Olympia, Washington 98501.

DEGREE IN ELECTRONICS through correspondence. Free catalog. Grantham, 2000 Stoner Avenue, Los Angeles, California 90025.

INTENSIVE 5 week course for Broadcast Engineers. F.C.C. First Class license. Radio Engineering Incorporated, 61 N. Pineapple Ave., Sarasota, Florida 33577.

SHORTCUTS To Success! Highly Effective, Profitable Short Courses (75 Choices). Study At Home. Diploma Awarded. Our 29th Year. Free Literature. CIEE-D, Box 20345, Jackson, Miss. 39209.

F.C.C. EXAM MANUAL

Test-Answers for FCC First and Second Class Commercial License

PASS FCC EXAMS! Memorize, study — "Test-Answers" for FCC 1st and 2nd class Radio-Telephone licenses. Newly revised multiple choice questions and diagrams cover all areas tested in FCC exams plus "Self-Study Ability Test." \$9.95 postpaid. Moneyback Guarantee.

COMMAND PRODUCTIONS P.O. BOX 26348-P
RADIO ENGINEERING DIVISION SAN FRANCISCO, CALIF. 94126

DEGREE Program in Electronics Engineering. Our 29th Year! Free literature. Cook's Institute, Dept. 13, Box 20345, Jackson, Miss. 39209.

LOGIC MICRO/MINI-
COMPUTER NEWS

LOGIC NEWSLETTER ©
SAMPLE COPY \$1.00
LOGIC NEWSLETTER
POB 252
WALDWICK, N.J. 07463

Altaj Electronic Bargains

PRICES SLASHED! WE WANT YOUR BUSINESS. SATISFACTION GUARANTEED ON EVERY ITEM

MM5314 NATIONAL CLOCK CHIP

The most popular clock chip around. We made a huge special purchase of factory fresh, prime units. Lowest price in USA. 24 Pin DIP. 4 or 6 Digits. With Specs. **\$3.94 EACH (3 For \$10)**

DIGITAL ALARM CLOCK IC

The newest and easiest to use alarm chip on the market today. Features:

1. Single supply voltage.
2. LED Intensity control
3. Simple time set.
4. 4 or 6 Digit LED Display
5. AM-PM Indication
6. 24 Hr. Alarm.
7. 10 minute snooze.
8. Outperforms MM5316

Order #70250 — \$6.95 (2 FOR \$12)



RCA STYLE C-MOS

CD4001-39¢ CD4012-44¢
 CD4002-39¢ CD4013-89¢
 CD4009-75¢ CD4017-1.95
 CD4011-39¢

LM309K

TO-3 Case, 1 AMP 5 VDC Voltage Regulator. Brand New By National 95¢

7805 STYLE REGULATORS

TO-220 Plastic Case 5VDC Regulator. Brand New by National — 89¢

GE POWER

TRANSISTOR ASSORTMENT

Plastic power devices. Includes NPN and PNP, darlingtons, high voltage, high current, and various other types. Cases are color coded for easy sorting. Untested but includes many useable units.

SPECIAL — 20 FOR \$1

TTL IC ASSORTMENT

Various types. Most are marked. Our best selling assortment. Untested but includes many useable devices. **200 PCS FOR \$3.95**

TIP-3055 BY TI

Plastic version of 2N3055. NPN Silicon. **89¢**

1 AMP SILICON RECTIFIERS

IN4002 — 100 PIV — 8¢
 IN4007 — 1000 PIV — 17¢

ZENERS


IN746 — 400MW — 3.3V
 IN752 — 400MW — 5.6V
 YOUR CHOICE
8 FOR \$1

PLASTIC DRIVER TRANSISTORS

For clocks or calculators. 2N3904 — NPN 2N3906-PNP
 YOUR CHOICE
6 FOR \$1

MAN-3 LED READOUTS

Brand new, factory prime units. .12 in. character. Common cathode. Perfect for calculators. **3 FOR \$1 Best Price Anywhere!**



DIGITAL WRIST WATCH CRYSTAL

Brand new, mfg. by CTS-KNIGHT. 32.768 KHZ. Standard, most popular type. Special \$2.50 ea.

NI-CAD BATTERY SPECIAL

Two cell pack. 2.75 V. Capacity is 250 MA Hours. Two of these packs make a great supply for TTL. 95¢ ea.


MINI CORE MEMORY SPECIAL

Mfg. by DATARAM. Stores 180 words of 18 bits each. With sense amps and associated drive circuits. A complete memory system. We include 50 pages of data and schematics. Data only \$2.50 Brand New. Special \$24.95



CALCULATOR BASIC KIT WITH TI CHIP

Includes case with matching all function keyboard, and 9 digits of LED readouts plus a Texas Instruments TMS 103 NC calculator chip. (Same style chip as in TI Datamath calculator). All the basics for building your own hand held calculator. Special — \$11.95 Kit Quantity Limited.



BURROUGHS PANAPLEX II 12 DIGIT READOUT

#BR13251 Neon 7 segment readout. Latest design for calculators, etc. Requires 160 VDC. Right hand decimals. Brand new, factory fresh. We include mating socket FREE. Special — \$5.95 NOTE: With purchase of above readout array we offer motorola 2N5401 PNP High Voltage driver transistor for 10¢ each.

REGULATED DC POWER SUPPLY

Brand new by wanlass. DC output 17 to 30 V. Rated 60 WATTS out. Our tests show these units will put out 12 VDC by changing one resistor. #OEM 60-3. Original cost \$57.50. In original factory boxes, with specs. Special \$14.95

FACTORY NEW LED'S

Jumbo Red-Like MV5024-8/\$1
 Jumbo Green-Like MV5222-5/\$1
 Jumbo Yellow-5/\$1
 Mini Red-Like MV50-10/\$1



ELECTROLYTIC CAPACITOR SPECIAL

220 MFD at 25 WVDC. AXIAL Leads by GI. Brand New **8 FOR \$1**

MINIATURE SWITCH

Rocker style. Small size. SPDT. Perfect for use on digital clocks. **4 FOR \$1**

PRIME TTL DIP IC'S

7400-16¢	7440-16¢	7492-85¢	74165-1.50
7402-16¢	7442-69¢	7493-85¢	74174-1.75
7404-16¢	7445-69¢	74121-38¢	74175-1.49
7406-24¢	7447-85¢	74123-66¢	74181-2.75
7408-16¢	7448-85¢	74150-69¢	74192-1.25
7410-16¢	7473-39¢	74151-69¢	74193-1.25
7413-49¢	7474-38¢	74153-95¢	74195-95¢
7420-16¢	7475-69¢	74154-95¢	74197-1.25
7430-16¢	7476-42¢	74157-1.19	
7437-39¢	7483-79¢	74161-1.15	
7438-39¢	7490-75¢	74164-1.29	

Quality Electronic Components

SPECIAL SAVINGS DISCOUNT ON LINEAR AND DIGITAL INTEGRATED CIRCUITS
 Deduct 4% from the total of your I.C. order if it exceeds \$25.00 based on single lot prices, 7% for \$50.00 or more, 10% for \$100.00 or more. Additional large quantity discounts offered.

DIGITAL INTEGRATED CIRCUITS

7400N .25.5c	7437N .42.0c	7480N .70.5c	74154N \$2.22
7401N .25.5c	7438N .42.0c	7482N .99.0c	74155N \$1.17
7402N .25.5c	7440N .25.5c	7483N \$1.17	74156N \$1.14
7403N .25.5c	7441N \$1.40	7485N \$1.40	74157N \$1.11
7404N .30.0c	7442N .90.0c	7486N .45.0c	74158N \$1.53
7405N .30.0c	7445N \$1.49	7489N .44.0c	74160N \$1.50
7406N .48.0c	7446N \$1.14	7490N .66.0c	74161N \$1.50
7407N .48.0c	7447N \$1.11	7491N \$1.05	74162N \$1.50
7408N .28.5c	7448N \$1.22	7492N .66.0c	74163N \$1.50
7409N .28.5c	7450N .25.5c	7493N .66.0c	74164N \$1.58
7410N .25.5c	7451N .25.5c	7494N \$1.10	74165N \$2.45
7411N .25.5c	7453N .25.5c	7495N \$1.14	74166N \$2.00
7413N .60.0c	7454N .25.5c	7496N \$1.14	74175N \$1.00
7416A .46.5c	7459N .28.5c	74107N .45.0c	74180N \$1.17
7417N .46.5c	7460N .25.5c	74121N .46.5c	74181N \$3.42
7418N .31.5c	7470N .33.0c	74122N .49.5c	74182N \$1.14
7420N .25.5c	7472N .36.0c	74123N \$1.08	74192N \$1.73
7421N .25.5c	7473N .43.5c	74141N \$1.10	74193N \$1.73
7423N .72.0c	7474N .43.5c	74150N \$1.53	74198N \$2.75
7426N .33.0c	7475N .69.0c	74151N \$1.17	74199N \$2.75
7430N .25.5c	7476N .46.5c	74153N \$1.17	

LINEAR INTEGRATED CIRCUITS

555V MINIDIP TIMER 82.5c	558V MINIDIP DUAL AMP 75.0c
565A DIP PLL \$3.38	567V MINIDIP DECODER \$3.38
709V MINIDIP OP AMP 36.0c	723A DIP VOLTAGE REG. 82.5c
741V MINIDIP OP AMP 50.0c	747A DIP DUAL AMP 97.5c
748V MINIDIP OP AMP 42.0c	LM3900 DIP QUAD AMP 60.0c
LI29 5 VOLT REG \$1.80	LI30 12 VOLT REG \$1.80
LI31 15 VOLT REG \$1.80	

MINIATURE ALUMINUM ELECTROLYTIC CAPACITORS

AXIAL LEAD TYPE —
 -40°C plus 85°C Tolerance -10 plus 50% (greater than 4.7 UF) -10 plus 75% (4.7 UF or less)

1.0 UF/50V 14c	12c	10c	33 UF/16V 15c	12c	10c	330 UF/16V 35c	25c	24c
2.2 UF/50V 14c	12c	11c	33 UF/25V 17c	13c	12c	330 UF/25V 44c	35c	32c
3.3 UF/50V 14c	12c	11c	47 UF/16V 17c	14c	13c	470 UF/16V 37c	30c	27c
4.7 UF/50V 14c	12c	11c	47 UF/25V 19c	14c	13c	470 UF/25V 49c	39c	35c
10 UF/16V 14c	12c	11c	100 UF/16V 19c	15c	14c	1000 UF/16V 49c	39c	35c
10 UF/25V 14c	12c	11c	100 UF/25V 24c	18c	17c	1000 UF/25V 75c	60c	55c
22 UF/16V 14c	12c	11c	220 UF/16V 24c	18c	17c	2200 UF/16V 75c	60c	55c
22 UF/25V 15c	12c	12c	220 UF/25V 29c	24c	24c			

1 AMP SILICON RECTIFIERS

1N4001 50 PIV 12/S1 100/56 1000/548	1N4005 600 PIV 8/S1 100/59 1000/570
1N4007 1000 PIV 6/S1 100/S11 1000/588	

SILICON SIGNAL & SWITCHING DIODE

1N4148 (1N914 equiv.) 12/S1 100/57 1M/\$50 5M/\$220

MOLEX SOLDERCON IC TERMINALS

100/S1 500/\$4.20 1000/\$8.20 5000/\$38.20 50,000/\$275

LED 7 SEGMENT DISPLAYS

DATALIT-704 . . . \$1.00	DATALIT-707 . . . \$1.50
--------------------------	--------------------------

IC SOCKETS 4 AMP SLID SWITCHES

8 Pin DIP Solder 35c	SPST 12c	10/S1 DPDT 25c	10/S2
14 Pin DIP Solder 45c			
16 Pin DIP Solder 50c			
24 Pin DIP Solder \$1.25			

REED RELAY

6 AMP CONTACT 5 VOLT/20MA COIL
\$2.00 10/S15 100/S125

VOLTAGE REGULATORS

\$1.80 ea.

LI29 5V 600mA
LI30 12V 500mA
LI31 15V 450mA

1/2 & 1/4 WATT CARBON COMP. RESISTORS

5 each of the 85 standard 10% values (2.2-22M) 1/4 W Resistors (425 pcs.) Sorted by value \$12/set 2-4 are \$11/set 5-9 are \$10/set.
 5 each of the 70 standard 10% values (10-5.6M) 1/4 W Resistors (350 pcs.) Sorted by value \$12/set 2-4 are \$11/set 5-9 are \$10/set.
 Resistors also available individually, in other assortments or in boxes of 1000 pcs. per value. 1/4 W are hot molded MIL-R-11F specification types.

SILICON TRANSISTORS

EN18 TO-106	19 18.99 100	2N3645 TO-105	20 17.5c 16.0c
EN930 TO-106	21c 18.5c 16.5c	2N3646 TO-106	22c 19.0c 17.5c
EN222 TO-106	21c 18.5c 16.5c	2N3904 TO-92	22c 19.0c 17.5c
EN2369A TO-106	21c 18.5c 16.5c	2N3906 TO-92	22c 19.0c 17.5c
EN2907 TO-106	21c 18.5c 16.5c	2N4124 TO-92	22c 19.0c 17.5c
2N2712 TO-98	18c 16.0c 14.5c	2N4126 TO-92	22c 19.0c 17.5c
2N3911A TO-98	22c 19.0c 17.5c	2N4401 TO-92	22c 19.0c 17.5c
2N3932 TO-98	22c 19.0c 17.5c	2N4403 TO-92	22c 19.0c 17.5c
2N3939 TO-98	22c 19.0c 17.5c	2N5087 TO-92	22c 19.0c 17.5c
2N3994 TO-98	22c 19.0c 17.5c	2N5089 TO-92	22c 19.0c 17.5c
2N3563 TO-106	20c 17.5c 16.0c	2N5129 TO-106	19c 17.0c 15.0c
2N3565 TO-106	20c 17.5c 16.0c	2N5133 TO-106	19c 17.0c 15.0c
2N3638 TO-105	20c 17.5c 16.0c	2N5134 TO-106	19c 17.0c 15.0c
2N3638A TO-105	20c 17.5c 16.0c	2N5137 TO-106	19c 17.0c 15.0c
2N3640 TO-106	22c 19.0c 17.5c	2N5138 TO-106	19c 17.0c 15.0c
2N3641 TO-105	20c 17.5c 17.5c	2N5139 TO-106	19c 17.0c 15.0c
2N3643 TO-105	20c 17.5c 16.0c	2N3055 TO-3	\$1.00 95.0c 85.0c

FIELD EFFECT TRANSISTORS

MPF102 TO-92	44 380 350	2N5457 TO-92	47 420 375
------------------------	------------	------------------------	------------

NPN DARLINGTON TRANSISTOR

MPS-A13 TO-92	Min. DC Current Gain of 5,000 at 10mA.	36 320 290
-------------------------	--	------------

Send for Free Catalog or Mail Readers Service Card

COD ORDERS ACCEPTED FOR SAME DAY SHIPMENT CALL 218-681-6674

Orders Less than \$10.00 add 50c Service Charge—Others Postpaid

"Only Quality Components Sold!"

DIGI-KEY CORPORATION

P.O. Box 126 Thief River Falls, MN 56701

CIRCLE NO. 38 ON READER SERVICE CARD

SCORE high on F.C.C. Exams... Over 300 questions and answers. Covers 3rd, 2nd, 1st and even Radar. Third and Second Test, \$14.50; First Class Test, \$15.00. All tests, \$26.50. R.E.I., Inc., Box 806, Sarasota, Fla. 33577.

FCC LICENSE through tape recorded lessons. Also Radar Enhancement. Radio License Training, 1060D Duncan, Manhattan Beach, Calif., 90266.

FCC LICENSE, electronics design, satellite communications, through correspondence. Free catalog. Genn Tech, 5540 Hollywood Blvd., Los Angeles, CA 90028.

SELF-STUDY CB RADIO REPAIR COURSE. THERE'S MONEY TO BE MADE REPAIRING CB RADIOS. This easy-to-learn course can prepare you for a career in electronics enabling you to earn as much as \$16.00 an hour in your spare time. For more information write: CB Radio Repair Course, Dept. PE-0175, 531 N. Ann Arbor, Oklahoma City, Okla. 73127.

MUSICAL INSTRUMENTS

30% DISCOUNT name brand musical instruments. Free Catalog. Freeport Music, 455N, Route 110, Melville, N.Y. 11746.

WHOLESALE! Professional Guitars, PA Systems, Altec Speakers, 240W RMS Amplifiers. Free Catalog, Carvin, Escondido, Calif. 92028.

30% + DISCOUNT. Name Brand Musical Instruments. Free Catalog. Continental Music, Dept. H, P.O. Box 3001, Garden City, New York 11530.

BUSINESS OPPORTUNITIES

I MADE \$40,000.00 Year by Mailorder! Helped others like me money! Free Proof. Torrey, Box 318-NN, Ypsilanti, Michigan 48197.

FREE CATALOGS. Repair air conditioning, refrigeration. Tools, supplies, full instructions. Doolin, 2016 Canton, Dallas, Texas 75201.

MAILORDER MILLIONAIRE helps beginners make \$500 weekly. Free report reveals secret plan! Executive (1K1), 333 North Michigan, Chicago 60601.

PIANO TUNING LEARNED QUICKLY AT HOME! Tremendous field! Musical knowledge unnecessary. GI approved. Information free. Empire School, Box 450327, Miami 33145.

\$200.00 DAILY In Your Mailbox! Your opportunity to do what mail-order experts do. Free details. Associates, Box 136-J, Holland, Michigan 49423.

\$178.00 WEEKLY. Work one hour daily. Free brochure. FAS, Box 13703-A, San Antonio TX, 78213.

Wanted

DEALER-DISTRIBUTORS

Send this Ad to:

PAL ELECTRONICS CO.

P. O. Box 778 • Westminster, Ca. 92683

HOW TO SELL BOOKS BY MAIL. FREE INFORMATION. McCord, Box 276-D, SYLVANIA, OHIO 43560.

OPPORTUNITY PACKAGE! Three amazing business plans. Free details; Gray Bros., 4830 So. 137 St., Suite 72U-1, Omaha, Nebraska 68137.

SELL TO GOVERNMENT—Complete instruction package \$4. RMP, Box 33071, District Hts., MD 20028.

WANT MORE MONEY, BETTER JOB? Get valid College Degrees without studying...legally! Complete details for stamp, Counseling, Box 1162-PE1, Tustin, Calif. 92680.

FREE BOOK "2042 unique proven enterprises." Work home! Hayling-B, Carlsbad, CA 92008.

POVERTY to riches in six easy steps. Invest \$2 for our money making booklet. P.O. Box 8071, Cranston, R.I. 02920.

FREE BOOK "999 Successful, Little-Known Businesses." Work Home! Plymouth-TFC, Box 1056, Weston, CT 06880.

HIGHLY PROFITABLE ONE-MAN ELECTRONIC FACTORY

Investment unnecessary, knowledge not required, sales handled by professionals. Postcard brings facts about this unusual opportunity. Write today!

Barta-DM, Box 248, Walnut Creek, CA 94597.

EMPLOYMENT OPPORTUNITIES

ELECTRONICS/AVIONICS EMPLOYMENT OPPORTUNITIES. Report on jobs now open. Details FREE. Aviation Employment Information Service, Box 240, Northport, New York 11768.

TREASURE FINDERS

FREE FACT-FILLED CATALOG! World's largest selection! Metal detectors starting at \$79.50. Two year guarantee! Three factories, U.S.-Canada. 1,200 dealers - Service Centers nationwide. Finest instruments at any price! Budget Terms. Dealer inquiries invited. Write: White's Electronics, Inc. Dept. PD50, 1011 Pleasant Valley Road, Sweet Home, Oregon 97386.

TREASURE FINDER locates buried gold, silver, coins, treasures. 6 powerful models. Instant financing available. Write or call for free catalog. Phone (713) 682-2728 day or night. Dealer inquiries invited. Relco, Dept. AA20, Box 10839, Houston, Texas 77018.

REAL ESTATE

NEW...BIG...FREE...SPRING CATALOG! Over 2,500 top values in FARMS, RANCHES, ACREAGES, RECREATIONAL PROPERTIES, BUSINESSES, TOWN and COUNTRY HOMES in 40 states coast to coast! Over 3,800 PHOTOS! UNITED FARM AGENCY, 612-EP West 47th St., Kansas City, MO 64112.

STATEMENT OF OWNERSHIP, MANAGEMENT AND CIRCULATION

(Act of August 12, 1970: Section 3685, Title 39, United States Code). 1. Title of Publication: Popular Electronics. 2. Date of filing: October 1, 1974. 3. Frequency of issue: Monthly. 4. Location of known office of publication: One Park Avenue, New York, New York 10016. 5. Location of the Headquarters or General Business Offices of the publishers: One Park Avenue, New York, New York 10016. 6. Names and addresses of publisher, editor, and managing editor: Publisher, Edgar W. Hopper, One Park Avenue, New York, New York, 10016; Editor, Arthur P. Salsberg, One Park Avenue, New York, New York, 10016; Manager Editor, John R. Riggs, One Park Avenue, New York, New York 10016. 7. Owner: Ziff-Davis Publishing Company, One Park Avenue, New York, N.Y. 10016; 1. William Ziff, One Park Avenue, New York, N.Y. 10016; 2. Dirk S. Brady, Charles Housman, Jules I. Whitman, Trustees F/B/O Dirk Ziff et al. 16 Ervilla Drive, Larchmont, N.Y. 10538; 8. Known bondholders, mortgagees, and other security holders owning or holding 1 percent or more of total amount of bonds, mortgages or other securities: None. 9. For optional completion by publishers mailing at the regular rates (Section 132.121, Postal Service Manual). 39 U.S.C. 3626 provides in pertinent part: "No person who would have been entitled to mail matter under former section 4359 of this title shall mail such matter at the rates provided under this subsection unless he files annually with the Postal Service a written request for permission to mail matter at such rates." In accordance with the provisions of this statute, I hereby request permission to mail the publication named in Item 1 at the reduced postage rates presently authorized by 39 U.S.C. 3626.

William L. Phillips, Assistant Treasurer

11.	Average no. copies each issue during preceding 12 months	Actual no. of copies of single issue published nearest to filing date
Extent and nature of circulation		
A. Total No. Copies Printed (Net Press Run)	435,093	426,301
B. Paid Circulation		
1. Sales through Dealers and Carriers, Street Vendors and Counter Sales	55,520	55,000
2. Mail Subscriptions	304,275	295,969
C. Total Paid Circulation	359,795	350,969
D. Free Distribution by Mail, Carrier or Other Means		
1. Samples, Complimentary, and Other Free Copies	6,015	5,791
2. Copies Distributed to News Agents, but Not Sold	67,698	67,900
E. Total Distribution (Sum of C and D)	433,508	424,660
F. Office use, Left Over, Unaccounted, Spoiled After Printing	1,585	1,641
G. Total (Sum of E & F—should equal net press run shown in A)	435,093	426,301

I certify that the statements made by me above are correct and complete.

WILLIAM L. PHILLIPS, Assistant Treasurer

ADVERTISERS INDEX

READER SERVICE NO.	ADVERTISER	PAGE NUMBER
1	Adva Electronics	111
	Allied Electronics	91
2	Allison Automotive	6
3	Altaj Electronics	109
	Ancrona Corporation	107
6	Audio-Technica U.S., Inc.	25
7	B&K Products of Dynascan	2
	Bell & Howell Schools	74, 75, 76, 77
	CREI Capitol Radio Engineering Institute	46, 47, 48, 49
9	Cleveland Institute of Electronics, Inc.	84, 85, 86, 87
10	Clifford's HiFi Wholesalers	100
11	Continental Specialties Corp.	101
13	Delta Electronics Co.	106
12	Delta Products, Inc.	17
38	Digi-Key Corporation	110
	Dixie HiFi Wholesalers	102
14	EICO	83
15	Edmund Scientific Co.	112
8	Exact Electronics	13
16	GTE Sylvania	28, 29, 30, 31
17	Great American Sound Co., Inc.	101
5	Heath Company	14, 15
18	Illinois Audio	102
	International Correspondence School	18, 19, 20, 21
19	International Electronics Unlimited	103
37	International HiFi Distributors	93
20	James Electronics	104
21	Lafayette Radio Electronics	7
22	McGraw-Hill Book Company	89
23	McIntosh Laboratory, Inc.	99
24	MITS, Inc.	27
25	Midwest HiFi Wholesalers	100
	NRI Schools	8, 9, 10, 11
	National Technical Schools	64, 65, 66, 67
	OEMorsco	99
26	Olson Electronics	93
27	Pace Communications Corp.	16
28	Phase Linear Corporation	23
29	Pickering & Co.	THIRD COVER
30	Poly Paks	105
31	Radio Shack	5
32	SBE Linear Systems, Inc.	63
33	Solid State Sales	108
34	Southwest Technical Products Corp.	32
35	Tri-Star Corp.	91
36	U.S. Pioneer Electronics Corp.	SECOND COVER, 1
4	United Audio Products Corp.	FOURTH COVER

CLASSIFIED ADVERTISING . . . 103, 104, 106, 108, 110, 111

HOME ENTERTAINMENT FILMS

ENJOY YEAR ROUND MOVIES IN YOUR HOME. Prices continue to raise but we will deliver Columbia Pictures like '74 Super Bowl, '74 Stanley Cup, '73 World Series and Sugar Ray Robinson in Super 8 or Standard 8 Color for \$16.95 each, \$7.50 in B&W until January 25, 1975. Castle and Sportlite catalog available, 25 cents each. SPORT-LITE, Dept. PE-1, Box 24-500, Speedway, Indiana 46224.

MAGAZINES AND BOOKS

FREE catalog aviation/electronic/space books. Aero Publishers, 329PE Aviation Road, Fallbrook, California 92028.

FREE book prophet Elijah coming before Christ. Wonderful bible evidence. Megiddo Mission, Dept. 64, 481 Thurston Rd., Rochester, N.Y. 14619.

BOOKS—thousands titles, bargains. Catalog Free. Cassiano, 92-27 New York Blvd., Jamaica, New York 11433.

CRAFT AUDIO
isn't a lost art. Readers of the Audio Amateur magazine are customizing and scratch building their equipment with gusto and great results. Free prospectus tells all. Box 30P, Swarthmore PA 19081

RECORDS

OLDIES. 45rpm. Free Catalog. Corny's Record Shop, Box 166TA, Mason, Ohio 45040.

RUBBER STAMPS

RUBBER address stamps. Free catalog. 45 type styles. Jackson's, Box 443G, Franklin Park, Ill. 60131.

MADE-TO-ORDER STAMPS. Low Prices. Free Catalog. Allegheny, Box 14A, East McKeesport, PA 15035.

PLASTICS

CASTOLITE pours like water, hardens like glass without heat. Crystal clear, colors. Embed flowers, seashells, mementos, anything. Make fine gifts. Form flexible molds over patterns of any shape, size. Reproduce your own designs in plastics, candlewax, metal, plaster, cement. Send 50 cents for illustrated Manual. Profitable. CASTOLITE, Dept. 75A/PE, Woodstock, Ill. 60098.

REPAIRS AND SERVICES

ELECTRONIC PROTOTYPE Models Built. Wire-Wrap, Hand solder, P.C. Boards. Engineering consultation and drafting service available. ACE Technical Services, 23-13 Steinway St., Astoria, N.Y. 11105. Phone: (212) 728-8284.

HYPNOTISM

SLEEP learning. Hypnotic method. 92% effective. Details free. ASR Foundation, Box 23429EG, Fort Lauderdale, Florida 33307.

FREE Hypnotism. Self-Hypnosis. Sleep Learning Catalog! Drawer H400, Ruidoso, New Mexico 88345.

AMAZING self-hypnosis record releases fantastic mental power. Instant results! Free trial. Write: Forum (AA1), 333 North Michigan, Chicago 60601.

STAMPS

WOW! 110 ALL DIFFERENT GERMANY 10 CENTS. Commemoratives, Airmails, High Values, Big Catalog, bargain lists. Also, fine stamps from our approval service, which you may return without purchases and cancel service at any time. Jamestown Stamp, Dept. A15EG, Jamestown, N.Y. 14701.

DO-IT-YOURSELF

TELEPHONES UNLIMITED, equipment, supplies. Catalog 50 cents. Box 1654E, Costa Mesa, Calif. 92626.

FREE DATA SHEETS WITH EVERY ITEM 739/749 IC WITH EVERY \$10 ORDER*

- REDUCE YOUR PROJECT COSTS
 - MONEY-BACK GUARANTEE
 - 24-HOUR SHIPMENT
 - ALL TESTED AND GUARANTEED
- TRANSISTORS (NPN):
 - 2N3563 TYPE RF Amp & Osc to 1 GHz (pl.2N918) 6/\$1.00
 - 2N3565 TYPE Gen. Purpose High Gain (TO-92/106) 6/\$1.00
 - 2N3567 TYPE High-Current Amplifier/Sw 500 mA 4/\$1.00
 - 2N3866 TYPE RF Pwr Amp 1-2 W @ 100-600 MHz \$1.50
 - 2N3903 TYPE GP Amp & Sw to 100 mA and 30 MHz 6/\$1.00
 - 2N3904 TYPE GP Amp & Sw to 100 mA (TO-92/106) 5/\$1.00
 - 2N3919 TYPE RF Pwr Amp 3-5 W @ 3-30 MHz \$3.00
 - 2N4274 TYPE Ultra-High Speed Switch 12 ns 4/\$1.00
 - MPS6515 TYPE High-Gain Amplifier hFE 250 3/\$1.00
 - Assort. NPN GP TYPES, 2N3565, 2N3641, etc. (15) \$2.00
 - 2N4249 TYPE (PNP) Low-Noise Amp 1 µA to 50 mA 4/\$1.00

- FET's:
 - N-CHANNEL (LOW-NOISE):
 - 2N4091 TYPE RF Amp & Switch (TO-18/106) 3/\$1.00
 - 2N4416 TYPE RF Amplifier to 450 MHz (TO-72) 2/\$1.00
 - 2N5486 TYPE RF Amp to 450 MHz (plastic 2N4416) 3/\$1.00
 - E100 TYPE Low-Cost Audio Amplifier 4/\$1.00
 - 1TE4868 TYPE Ultra-Low Noise Audio Amp. 2/\$1.00
 - T1574 TYPE High-Speed Switch 40Ω 3/\$1.00
 - Assort. RF & GP FET's, 2N5163, 2N5486, etc. (8) \$2.00
 - P-CHANNEL:
 - 2N4360 TYPE Gen. Purpose Amp & Sw (TO-106) 3/\$1.00
 - E175 TYPE High-speed Switch 125Ω (TO-106) 3/\$1.00

JANUARY SPECIALS:

- 2N3638 TYPE PNP TRANSISTOR GP Amp & Switch 5/\$1.00
- 2N5163 TYPE N-CHANNEL FET GP Amp & Switch 4/\$1.00
- 741 Freq. Compensated Op Amp (DIP/TO-5/MINI-DIP) 3/\$1.00
- 1N914 or 1N4148 TYPE GP DIODE 100 V/10 mA 15/\$1.00
- MM5316 Digital Alarm Clock-Snooze/Alarm/Timer Hrs, Mins, Secs — with Specs/Schematics \$11.95
- MM5736 6-Digit 4-Function Calculator 18 PIN DIP \$ 3.95

- LINEAR IC's:
 - 308 Micro-Power Op Amp (TO-5/MINI-DIP) \$1.00
 - 309K Voltage Regulator 5 V @ 1 A (TO-3) \$1.50
 - 324 Quad 741 Op Amp, Compensated (DIP) \$1.90
 - 380 2.5 Watt Audio Amplifier 34 dB (DIP) \$1.29
 - 555X Timer 1 µs-1 hr, Dif. pinout from 555 (DIP) \$.85
 - 709 Popular Op Amp (DIP/TO-5) \$.29
 - 723 Voltage Regulator 3-30 V @ 1-250mA (DIP/TO-5) \$.58
 - 739 Dual Low-Noise Audio Preamp/Op Amp (DIP) \$1.00
 - 1458 Dual 741 Op Amp (MINI-DIP) \$.65
 - 2566 Dual 555 Timer 1 µsec to 1 hour (DIP) \$1.55

- DIODES:
 - 1N3600 TYPE Hi-Speed Sw 75 V/200 mA 6/\$1.00
 - 1N3893 TYPE RECTIFIER Stud Mount 400 V/12 A 2/\$1.00
 - 1N4608 TYPE GP & Sw 80 V/400 mA 6/\$1.00
 - 1N749 ZENER 4.3 Volt (±10%) 400 mW 4/\$1.00
 - 1N753 ZENER 6.2 Volt (±10%) 400 mW 4/\$1.00
 - 1N755 ZENER 7.5 Volt (±10%) 400 mW 4/\$1.00
 - 1N757 ZENER 9.1 Volt (±10%) 400 mW 4/\$1.00
 - 1N758 ZENER 10 Volt (±10%) 400 mW 4/\$1.00
 - 1N965 ZENER 15 Volt (±10%) 400 mW 4/\$1.00
 - 1N968 ZENER 20 Volt (±10%) 400 mW 4/\$1.00
 - D5 VARACTOR 5-50 W Output @ 30-250 MHz, 7-70 pF \$5.00
 - F7 VARACTOR 1-3 W Output @ 100-500 MHz, 5-30 pF \$1.00

*MAIL NOW! FREE DATA SHEETS supplied with every item from this ad. FREE 739 or 749 Low-Noise Dual Op Amp included (\$1.00 value) with every order of \$10 or more, postmarked prior to 2/28/75.

ORDER TODAY—All items subject to prior sale and prices subject to change without notice.

WRITE FOR FREE CATALOG offering hundreds of semiconductors not listed here. Send 10¢ stamp.

TERMS: All orders must be prepaid. We pay postage. \$1.00 handling charge on orders under \$10. Calif. residents add 6% sales tax.

ADVA ELECTRONICS
BOX 4181 R, WOODSIDE, CA 94062
Tel. (415) 851-0455
CIRCLE NO. 1 ON READER SERVICE CARD

MAGNETS

MAGNETS. All types. Specials-20 disc, or 10 bar, or 2 stick, or 8 assorted magnets, \$1.00. Magnets, Box 192-H, Randallstown, Maryland 21133.

REMAILS


LETTERS FORWARDED, Will Stamp and Zip. Max. 2, 50 cents. Malo, P.O. Box 1597, Boston, Mass. 02104.

MISCELLANEOUS

WINEMAKERS: Free illustrated catalog yeasts, equipment. Semplex, Box 12276P, Minneapolis, Minn. 55412.

NEW-concept in cement. Bonds wood, metal, stones, plastics. Anything. Used by Jewelers, Carpenters, Metalworkers, Craftsmen. \$3.00. Butco, 1626 2nd Ave., N.Y.C. 10028.

**What is it that
feels good,
sounds good-
and will
go anywhere
with you?**



**Pickering's
Model OA-3
dynamic
open audio
lightweight
headphones.**

Expanded Listening Enjoyment. Just plug the special adapter into the earphone jack of any Mono Cassette Recorder, Portable Radio or TV Set and plug the OA-3 into the special adapter and enjoy total sound everywhere you go.

Revolutionary. So slender. So light. So comfortable to use over long periods of time.

Sound Perfection. You have to listen to believe.

Open Audio. Enjoy the sound. Yet, be part of what's going on around you. That's the big thing about "open audio".

Prediction. The OA-3 will be your favorite "component" in your hi-fi stereo system. **\$39.95**

For further information write to: Pickering & Co. Inc., Dept. PE, 101 Sunnyside Blvd., Plainview, New York 11803



"for those who can hear the difference"

CIRCLE NO. 29 ON READER SERVICE CARD

The Dual 1229Q. Why many music lovers will settle for nothing less.



Many serious music lovers are not satisfied unless every component in their system is the very finest in its class, with cost secondary. The 1229Q, Dual's highest-priced multi-play turntable, is one of these "no compromise" components.

The 1229Q is a full-sized turntable with a twelve-inch dynamically balanced platter that weighs a full seven pounds. Its massive platter is driven by Dual's powerful Continuous-Pole/synchronous motor.

The 8-3/4" tonearm is mounted in a true gyroscopic gimbal that centers and balances it within both axes of movement. All four tonearm pivots turn on identical low-friction bearings permitting flawless tracking at as low as 0.25 gram. And since a turntable of the 1229Q's calibre is used most frequently in the single-play mode, the tonearm is designed to track at precisely the correct angle in that mode. With the exclusive Mode Selector, tracking angle can be instantly adjusted for correct tracking at mid stack in the multi-play mode.

Low capacitance tonearm leads and an anti-skating system with separate calibrations for conical, elliptical and CD-4 styli, make the 1229Q compatible with any stereo and four-channel cartridge available or likely to be available in the foreseeable future. Other features include a calibrated illuminated strobe with adjustable viewing angle, and cueing damped up as well as down to prevent bounce.

The 1229Q is too new for test reports to have appeared, but reports on its immediate predecessor, the Dual 1229, indicate why it was the largest selling quality turntable ever made. Stereo Review called its rumble measurements "among the best we have yet made on a turntable." High Fidelity said, "It takes one step further the progressive improvements that have made top Dual models among the most popular turntables in component systems for the better part of a decade, to judge by readers' letters."

Stereo & HiFi Times' noted, "I unhesitatingly recommend it to anyone looking for the best possible record playing equipment." And Popular Electronics rated it "the equal of any combination of record playing components known to us."

Of course, not everyone can afford the 1229Q's price: \$259.95. But every Dual turntable, starting with the 1225 at \$129.95, provides the same high quality materials, carefully finished parts and meticulous quality control that have long earned Dual its reputation for reliability.

Thus which Dual you select is not terribly important. Your choice can be made in terms of the level of refinement you require. And if, like many music lovers, you require every refinement it is possible to have in a multi-play turntable, chances are you too will choose the Dual 1229Q.

Dual® **United Audio Products**
120 So. Columbus Ave., Mt. Vernon, N.Y. 10553
Exclusive U.S. Distribution Agency for Dual